DESIGN WITHIN REACH



ThinAir[®] ADA-COMPLIANT HAND DRYER

The ThinAir[®] Hand Dryer is a high-efficiency model that is surface-mounted and ADAcompliant. ThinAir dries hands in 15 seconds^{*}, uses 960 watts or less and has a slimmer profile to meet ADA compliance standards. The ThinAir Hand Dryer features adjustable speed and sound control, optional on/off heat and a washable pre-filter.

ThinAir[®] HAND DRYER

MODELS: TA - ABS -VOLTAGE (See Chart)





TA-ABS White Polymer (ABS) With SanaFor™ Antimicrobial Additive



OVERALL DIMENSIONS Width: 9 ⁵/₃₂" (233 mm) Height: 13 ¹⁵/₁₆" (354 mm) Depth: 4" (102 mm)

WEIGHT

TA-ABS: 8 lbs. (3.6 kgs.)

ELECTRICAL

Units are Single Phase; 960 Watts or as low as 333 Watts (without heat) and available as specified in:

110-120V	8A	60 Hz	c (UL) us
208-240V	4A	50/60 Hz	cŲLus
230V	3.9A	50 Hz	Œ









FEATURES & BENEFITS

- 15 Second Dry Time*
- Less than 960 Watts; as low as 333 \checkmark Watts with heat turned off
- \checkmark Meets 4" ADA protrusion guidelines to accommodate the visually impaired



OPTIONAL ACCESSORIES

MICROBAN® Antimicrobial Wall Guards: 89W (White), 89B (Black) \checkmark Stainless Steel: 89S (Brushed)

ACTIVATION

Automatic Sensor Activated

ADA COMPLIANCE

ADA guidelines state that fixtures mounted above 27" must not protrude more than 4" from the wall.

37"





Maximum: 48" Recommended: 37"

MOUNTING

Surface-Mounted

SUGGESTED MOUNTING HEIGHTS from floor to bottom of drver:

Men	45"	(114 cm)
Women	43"	(109 cm)

vvoinen	43	(109 CIII)
Teenagers	41"	(104 cm)
Small Children	35"	(89 cm)
Handicapped	37"	(94 cm)



Dry time based on third party testing performed by SGS International on standard Thin Air hand dryer to 0.2g or less of residual moisture.



ИЕ TO THROW IN THE TOWEL[®] DRYER 1.800.255. 9235 EXCELDRYER.COM INC