



# XD-165L

## LOW GRAIN REFRIGERANT

The XPOWER XD-165L Low Grain Refrigerant (LGR) • Dehumidifier is the newest member of the XPOWER LGR dehumidifier line. The XD-165L LGR Dehumidifier achieves maximum humidity control and water removal efficiency. This all new “XXL” category unit is capable of removing up to 165 Pints per day @ AHAM (80°F, 60% RH) and 280 pints per day at full saturation (90°F, 90% RH). The XD-165L LGR Dehumidifier has an electronic display that assists in monitoring the temperature and humidity at the exhaust, as well as recording the total operating life of the dehumidifier. Lay flat ducting can be applied to the exhaust point of the dehumidifier with the dual ducting ring that is included on the unit to transport warm/dry air to where it is needed. It is easily done by hand without any additional tools. The XPOWER XD-165L LGR Dehumidifier also features an auto purge condensate pump, superior compared to industry competitors, that is capable of purging collected moisture through the provided 40' drainage hose. Weighing 121 LBS with rugged wheels and telescoping handle, the ultra-mobile XD-165L gives you class leading LGR performance.



- Water removal capacity: 165 pints/day at AHAM (80°F, 60% RH); 280 Pints/Day at Saturation (90°F, 90% RH)
- LGR performance with operating range between 33°F – 105°F (0.6°C – 40.6°C)
- Optimal dehumidification process with low efficient 10.2 Amps draw
- 476 CFM of warm, dry air passes through the exhaust to help optimize drying capability



# SPECIFICATIONS

- Digital display monitors current humidity and operating time
- Durable and rugged roto-mold housing
- Convenient power cord / drainage hose compartment
- Dual ducting exhaust capabilities
- Telescoping handle and wheels make this unit ultra-mobile
- 10 ft. power cord and 40 ft. long drain hose
- Auto purge pump with drainage hose automatically purges when full: eliminating the task of monitoring collection tank levels
- Automatic speed control increases or decreases the fan speed based on the relative humidity and ambient temperature levels in the space requiring dehumidification

MODEL NO.	<b>XD-165L</b>
WATER REMOVAL EFFICIENCY AT AHAM (80 °F / 60% RH)	<b>165 Pints Per Day</b>
WATER REMOVAL AT FULL SATURATION (90°F / 90% RH)	<b>280 Pints Per Day</b>
VOLTS/HERTZ	<b>115 V~60 Hz</b>
POWER	<b>10.2 A</b>
RATED AIRFLOW	<b>476 CFM</b>
SPEEDS	<b>Automatic Speed</b>
FILTER TYPE	<b>Stainless-Steel Filter</b>
HOUSING	<b>PE</b>
CORD LENGTH	<b>25 Ft.</b>
DRAIN HOSE LENGTH	<b>40 Ft.</b>
TIME METER	<b>Up to 9999 hours 50 minutes</b>
OPERATING RANGE	<b>33°F - 105°F</b>
UNIT WEIGHT	<b>121.3 Lbs.</b>
UNIT DIMENSIONS (LXWXH)	<b>22 x 22.4 x 29.8 in</b>
SAFETY CERTIFICATIONS	<b>ETL / CETL</b>
PALLET QUANTITY	<b>8</b>



## FEATURES




Filter



Handle



Wheels for Easy Transport



Storage