

GRIDDLE STAND REFRIGERATOR

Model: DL108G

108" Griddle Stand Refrigerator

Stainless steel exterior and interior.

Designed to maintain NSF-7 temperatures in 100°F ambient.



Options and Accessories

(upcharge and lead times may apply)

| | |
|---|---|
| Flat top in lieu of marine edge | Adjustable legs |
| 16-gauge stainless steel top (flat or marine) | Digital thermometer |
| Condensing unit left or right | Cylinder locks |
| Automatic, electric condensate evaporator | Stainless steel pans |
| Stainless steel top extensions (flat or marine) | Special electrical requirements (consult factory) |

Consult factory for other model configurations, options and accessories.

Continental
Refrigerator

Toll-Free: 800-523-7138
Phone: 215-244-1400
Fax: 215-244-9579

539 Dunksferry Road
Bensalem, PA 19020
www.continentalrefrigerator.com

Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance-rated refrigeration system

Environmentally-safe R-134a refrigerant

Side-mounted, automatic, energy saving non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, front slide-out condensing unit

CABINET ARCHITECTURE

High density, non-CFC polyurethane foamed-in-place insulation

Easy glide, fully extendable drawers designed to hold 6" deep pans side-by-side

One-piece, snap-in magnetic drawer gaskets

Heavy-duty drawer track with built-in drawer safety clips

Drawers designed to hold 250 lb. capacity

4" casters on support plates

Stainless steel case back

Reinforced stainless steel work top with drip guard marine edge

MODEL FEATURES

Capillary dial thermometer

Front breathing

APPROVAL:

Model Specifications

DIMENSIONAL DATA

| | |
|---|-----------------|
| Net Capacity (cu. ft.) | 27.4 (776 cu l) |
| Width, Overall (in.) | 108 (2743 mm) |
| Depth, Overall (incl. handles) (in.) | 34 3/4 (883 mm) |
| Height, Overall (in.) (incl. 4" casters) | 26 3/8 (670 mm) |
| No. of Drawers | 6 |

REFRIGERANT DATA

| | |
|-----------------------------|------|
| Condensing Unit Size (H.P.) | 1/2 |
| Capacity (BTU/Hr)* | 3100 |

ELECTRICAL DATA

| | |
|-------------------------------------|---------------------|
| Voltage (int'l) | 115/60/1 (220/50/1) |
| Fans | 3 |
| Feed Wires (incl. ground) | 3 |
| Total Amps (int'l) | 14.2 (9.0) |
| 10 ft. Cord/Plug [attached] (int'l) | Yes (No) |

SHIPPING DATA

| | |
|-----------------------|---------------|
| Weight (lbs.) | 760 (345 kg) |
| Height - Crated (in.) | 44 (1118 mm) |
| Width - Crated (in.) | 125 (3175 mm) |
| Depth - Crated (in.) | 39 (991 mm) |

TOP WEIGHT CAPACITY

| | |
|---------------------------------|---------------|
| Max. Top Weight Capacity (lbs.) | 1400 (635 kg) |
|---------------------------------|---------------|

* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-20P Plug
(varies by country)

Continental
Refrigerator

Toll-Free: 800-523-7138
Phone: 215-244-1400
Fax: 215-244-9579

539 Dunkserry Road
Bensalem, PA 19020
www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



Intertek

© Copyright 2016. Continental Refrigerator.

A Division of National Refrigeration & Air Conditioning Products, Inc.



MADE IN THE U.S.A.

Model Plan Views

