

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

BB 23" BASE SERIES—BACK BAR REFRIGERATOR

Shallow depth, back bar, self-contained refrigerators come in two widths of 48" and 72." Two heights include 34" with standard galvanized steel top for under shelf application and 36" when adapted with a stainless steel top. Depth is 23" from face of door to back of cabinet. Handle projects 1/2." Solid door models come standard with locks.

CABINET CONSTRUCTION

Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black exterior finish. Doors are self-closing and include magnetic gaskets for positive seal.

Standard interior construction utilizes galvanized steel walls and ceiling. Reinforced floor and door sills are made from heavy-duty stainless steel to provide long lasting service. Interior, incandescent, lighting is standard with manual on/off switch.

Foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

REFRIGERATION

Refrigeration is fully accessible behind grille to right side of cabinet. Evaporator located above condensing unit permits full use of interior spaces. Forced air is projected the length of cabinet across the ceiling. Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns. Remote refrigeration models include expansion valve installed.


Condensate elimination is automatic and non-electric.

ELECTRICAL

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

SPECIAL FEATURES

 Keg storage is maximized in lieu of shelf storage when required.



BEER EQUIPMENT SOLID DOOR BACK BAR REFRIGERATORS 23" BASE BB SERIES

MODELS: BB48Y/48R BB72Y/72R





BB72Y











Available From:

*Note: Not all markings may apply to all model variations.

Model Specified	Store#
Location	Quantity



Back Bar Refrigerators, 23" Base Models: BB48Y, BB48R, BB72Y, BB72R

MODEL	BB48Y	BB48R	BB72Y	BB72R
EXTERNAL DIMENSIONAL DATA				
Length Overall (inches) Length Overall (mm)	48" 1219	48" 1219	72" 1829	72" 1829
Depth Overall (inches) Depth Overall (mm)	23 1/2" 597	23 1/2" 597	23 1/2" 597	23 1/2" 597
Height Overall— (inches) Height Overall—(mm)	34" 864	34" 864	34" 864	34" 864
Clear Door Width (inches)	16 7/16" x 29 1/4"	16 7/16" x 29 1/4"	17 7/8" x 29 1/4"	17 7/8" x 29 1/4"
Depth With Door Open 90°	41 3/8"	41 3/8"	42 3/4"	42 3/4"
Number of doors	2	2	3	3
INTERNAL DIMENSIONAL DATA				
NET Capacity (cubic ft.) NET Capacity (Liters)	12.1 343	12.1 343	19.4 549	19.4 549
Internal Length Overall (inches) Internal Length Overall (mm)	36" 914	36" 914	60" 1524	60" 1524
Internal Depth Overall (inches) Internal Depth Overall (mm)	18 1/2" 470	18 1/2" 470	18 1/2" 470	18 1/2" 470
Internal Height Overall (inches) Internal Height Overall (mm)	29 1/2" 749	29 1/2" 749	29 1/2" 749	29 1/2" 749
Number of Shelves	4	4	6	6
Number of Kegs (straight wall)	2	2	3	3
ELECTRICAL DATA				
Full Load Amperes 115/60/1	5.0	.5	5.0	.5
REFRIGERATION DATA				
Horsepower	1/4	remote	1/4	remote
WEIGHT DATA				
Gross Weight (Crated lbs)	269	223	366	330
Gross Weight (Crated kg)	122	101	166	150

(ĥ)















*Note: Not all markings may apply to all model variations.

*N/A: Not available at time of printing.

PLAN VIEWS






ELECTRICAL CONNECTION

Units pre-wired at factory and include 8' long cord and plug set.





BEVERAGE-AIR® CORPORATION