

SlidingLid™ Ice Caddies

Standard

175 lb. (79 Kg.) Capacity Models ICS175L, ICS175L4S, ICS175LB

Features & Benefits



- · Indoors or outdoors, in heat or humidity, these sleek models keep their cool and can hold ice cold for days. They provide reliability, value and safer holding for up to 175 lbs. (79 kg.) of ice.
- Unique sliding lid has no latches. Slides back and under into the secured base lid for quick access and it slides shut for safe and sanitary storage. Helps reduce the risk of cross contamination
- Four sturdy thumbscrews secure base lid tightly during transport and when sliding top back and under.
- Service opening is 14" (35,6 cm) x 18" (45,7 cm) for guick and easy loading and unloading of ice.
- Double-wall, high density, polyethylene construction is impact resistant and will not dent, crack, bubble, chip or break. Easy to clean.
- Thick polyurethane foam insulation keeps ice frozen. Reduces frequency of restocking, ensuring quick and convenient service.
- · Recessed, leak proof, quarter-turn faucet is located on the front of every unit for easy access and quick draining.
- Recessed interior well with Camwear® polycarbonate drain shelf keeps ice out of any melted water, ensuring long lasting quality and storage.
- Molded-in handle is sturdy and will not break off. Provides controlled handling and maneuvering.
- · Recessed lift grip on the front for safe, balanced lifting on or off delivery trucks.
- Three choices of wheel configurations meet a variety of transport needs. And 10" (25,4 cm) Easy Wheels make transporting even smoother and virtually effortless.

Model ICSI75L - Four each 5" (12,7 cm) casters, 2 fixed, 2 swivel, 1 w/ brake

Model ICS175L4S - Four each 5" (12,7 cm) casters, 4 swivel, 1 w/ brake

Model ICS175LB - Two each 5" (12,7 cm) front casters, 2 swivel, 1 w/ brake and 2 each 10" (25,4 cm) Easy Wheels

- · No assembly required.
- Available in 13 colors.

Item No.


Specifier Identification No. ______

Model No.____

Quantity_____







10" (25,4 cm) Easy Wheels on ICS175LB Models.

Approvals



Patent Pending



58

SlidingLid[™] Ice Caddies

Standard

175 lb. (79 Kg.) Capacity


Models ICS175L, ICS175L4S, ICS175LB


Item No. _____


Specifier Identification No. _____

Model No.

Quantity_____









~~	ti	^	n	c	

Specifications Dimension Tolerance: +/- 1/4" (0,64 cm)

Code	Description	Interior Dimensions W x D x H	Exterior Dimensions W x D x H	Case Ibs./cube Kg/m³
ICS175L	SlidingLid Ice Caddy	18" x 30" x 18 ¹ / ₈ " (45,7 x 76,2 x 46,7 cm)	24" x 37 ¹ / ₂ " x 29 ¹ / ₄ " (61 x 95,3 x 74,3 cm)	78 (16.30) 35,4 (0,462)
CS175L4S	SlidingLid Ice Caddy	18" x 30" x 18 ¹ / ₈ " (45,7 x 76,2 x 46,7 cm)	24" x 37 ¹ / ₂ " x 29 ¹ / ₄ " (61 x 95,3 x 74,3 cm)	78 (16.30) 35,4 (0,462)
ICS175LB	SlidingLid Ice Caddy	18" x 30" x 18 ¹ / ₈ " (45,7 x 76,2 x 46,7 cm)	24" x 37 ¹ / ₂ " x 29 ¹ / ₄ " (61 x 95,3 x 74,3 cm)	80 (16.30) 36,3 (0,462)

Architect Specs

The standard 175 lb. (79 Kg.) capacity SlidingLid Ice Caddy shall be Cambro Model..., manufactured by Cambro Mfg. Co., Huntington Beach, CA 92648 U.S.A. It shall be constructed of single-molded, double-wall, high-density polyethylene and thick foam injected polyurethane. It shall have a sliding lid without latches. It shall slide back and under secured base lid. It shall have rounded corners and molded-in handles. It shall have a 14" x 18" (35,6 x 45,7 cm) service opening. It shall have a recessed, leakproof, quarter turn faucet on the front. It shall have a recessed interior well with one unbreakable polycarbonate shelf. It shall be available with 3 different wheel configurations, including Model ICS175LB with 2 each 10" (25,4 cm) Easy Wheels. It shall not require any assembly and shall be available in 13 colors.

Standard Colors

- ☐ Black (110) ☐ Dusty Rose (400) ☐ Cold Blue (159) ☐ Dark Brown (131)
- ☐ Gray (180) ☐ Brick Red (402)
- ☐ Granite Gray (191) ☐ Granite Green (192) ☐ Granite Red (193) ☐ Granite Sand (194)
- ☐ Slate Blue (401) ☐ Coffee Beige (157)
- ☐ Navy (186)

Approvals



Patent Pending



Toll Free 800 854 7631