

Camshelving® Premium Series

Stationary - Kits

Post Kits and Shelf Kits
with Camguard™ antimicrobial (shelf plates only)

5 Post Heights

32", 56", 64", 72", 84"
(81,3 cm, 142,2 cm, 162,6 cm, 182,9 cm, 213,4 cm)

4 Shelf Depths

14", 18", 21", 24"
(35,6 cm, 45,7 cm, 53,3 cm, 61 cm)

8 Shelf Lengths

24", 30", 36", 42", 48", 54", 60", 72"
(61 cm, 76,2 cm, 91,4 cm, 106,7 cm,
121,9 cm, 137,2 cm, 152,4 cm, 182,9 cm)



• Post Kit includes:

Two Posts and one each top and bottom Post Connector.
(unassembled)

• Shelf Kit includes:

Two Traverses and Vented or Solid Shelf Plates to complete one shelf.

Features & Benefits

Versatile Storage

For use in any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C). Weldless and rust free.

Fits in Any Space

Units combine together in straight lines by sharing posts of existing units. Corner Connectors, made of reinforced nylon, connect units together in 90° angle. Unique design maximizes valuable space and offers strength and stability. Simplify assembly and reduce costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Easy to Clean

Camshelving Shelf Plates contain Camguard an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Two Post Kits required to complete one unit. Molded in dovetails on Posts ensure that Traverses set easily into place.

Strong as Steel

Posts and Traverses are made of a steel core coated with polypropylene. Uniquely engineered Post Connectors offer exceptional cross stabilization. Shelves up to 48" (121,9 cm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 72" (137,2 - 182,9 cm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 24" (61 cm) to 48" (121,9 cm) traverse.

Item No. _____


Specifier Identification No. _____

Code No. _____

Quantity _____



Four Shelf Unit with Vented Shelves.



Post Kit (unassembled) includes two Posts and one set of Post Connectors.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

Easy to Adjust

Requires use of a rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Sturdy reinforced nylon foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and level.

Optional Accessories

Includes Wall Fastener and Seismic Foot. Each are packed 4 per case. Identification Tags clip easily onto traverses.

Approvals



COMPONENT

Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Tray Slide Rack, Shelf Rails, Divider Bars, and High Density Track and Extension Kits are not NSF Listed.

Camshelving® Premium Series

Post Kits

code	depth		height		case lbs. (cube)	case kg. (cube m ³)
	in.	cm	in.	cm		
CPPK1432	14"	35,6	32"	81,3	8,45 (0,32)	3,83 (0,0091)
CPPK1832	18"	45,7	32"	81,3	8,80 (0,32)	3,99 (0,0091)
CPPK2132	21"	53,3	32"	81,3	9,10 (0,32)	4,13 (0,0091)
CPPK2432	24"	61,0	32"	81,3	9,50 (0,32)	4,31 (0,0091)
CPPK1456	14"	35,6	56"	142,2	13,45 (0,41)	6,10 (0,0116)
CPPK1856	18"	45,7	56"	142,2	13,80 (0,41)	6,26 (0,0116)
CPPK2156	21"	53,3	56"	142,2	14,10 (0,41)	6,40 (0,0116)
CPPK2456	24"	61,0	56"	142,2	14,50 (0,41)	6,58 (0,0116)
CPPK1464	14"	35,6	64"	162,6	15,45 (0,46)	7,0 (0,0130)
CPPK1864	18"	45,7	64"	162,6	15,80 (0,46)	7,17 (0,0130)
CPPK2164	21"	53,3	64"	162,6	16,10 (0,46)	7,30 (0,0130)
CPPK2464	24"	61,0	64"	162,6	16,50 (0,46)	7,48 (0,0130)
CPPK1472	14"	35,6	72"	182,9	17,20 (0,52)	7,80 (0,0147)
CPPK1872	18"	45,7	72"	182,9	17,55 (0,52)	7,96 (0,0147)
CPPK2172	21"	53,3	72"	182,9	17,85 (0,52)	8,10 (0,0147)
CPPK2472	24"	61,0	72"	182,9	18,25 (0,52)	8,28 (0,0147)
CPPK1484	14"	35,6	84"	213,4	19,95 (0,61)	9,05 (0,0173)
CPPK1884	18"	45,7	84"	213,4	20,30 (0,61)	9,21 (0,0173)
CPPK2184	21"	53,3	84"	213,4	20,60 (0,61)	9,34 (0,0173)
CPPK2484	24"	61,0	84"	213,4	21,00 (0,61)	9,52 (0,0173)

Corner Connector Set

Case Pack: 1 set

code	description	case lbs. (cube)	case kg. (cube m ³)
CSCC1	Right and Left	0,76 (0,05)	0,034 (0,0014)

Shelf Kits with Vented Shelf Plates

code	depth		length		case lbs. (cube)	case kg. (cube m ³)
	in.	cm	in.	cm		
24" (61 cm) Traverses						
CPSK1424V1	14"	35,6	24"	61,0	7,43 (0,83)	3,37 (0,0235)
CPSK1824V1	18"	45,7	24"	61,0	7,94 (0,83)	3,60 (0,0235)
CPSK2124V1	21"	53,3	24"	61,0	8,66 (0,83)	3,93 (0,0235)
CPSK2424V1	24"	61,0	24"	61,0	8,73 (0,83)	3,96 (0,0235)
30" (76,2 cm) Traverses						
CPSK1430V1	14"	35,6	30"	76,2	9,16 (0,83)	4,15 (0,0235)
CPSK1830V1	18"	45,7	30"	76,2	9,69 (0,83)	4,40 (0,0235)
CPSK2130V1	21"	53,3	30"	76,2	10,67 (0,83)	4,84 (0,0235)
CPSK2430V1	24"	61,0	30"	76,2	10,92 (0,83)	4,95 (0,0235)
36" (91,4 cm) Traverses						
CPSK1436V1	14"	35,6	36"	91,4	10,89 (0,83)	4,94 (0,0235)
CPSK1836V1	18"	45,7	36"	91,4	11,44 (0,83)	5,19 (0,0235)
CPSK2136V1	21"	53,3	36"	91,4	12,68 (0,83)	5,75 (0,0235)
CPSK2436V1	24"	61,0	36"	91,4	13,11 (0,83)	5,95 (0,0235)
42" (106,7 cm) Traverses						
CPSK1442V1	14"	35,6	42"	106,7	12,66 (0,97)	5,74 (0,0274)
CPSK1842V1	18"	45,7	42"	106,7	13,62 (0,97)	6,18 (0,0274)
CPSK2142V1	21"	53,3	42"	106,7	15,23 (0,97)	6,91 (0,0274)
CPSK2442V1	24"	61,0	42"	106,7	15,31 (0,97)	6,94 (0,0274)
48" (121,9 cm) Traverses						
CPSK1448V1	14"	35,6	48"	121,9	14,35 (1,06)	6,51 (0,0300)
CPSK1848V1	18"	45,7	48"	121,9	14,94 (1,06)	6,78 (0,0300)
CPSK2148V1	21"	53,3	48"	121,9	16,69 (1,06)	7,57 (0,0300)
CPSK2448V1	24"	61,0	48"	121,9	17,50 (1,06)	7,94 (0,0300)
54" (137,2 cm) Traverses						
CPSK1454V1	14"	35,6	54"	137,2	16,12 (1,24)	7,31 (0,0351)
CPSK1854V1	18"	45,7	54"	137,2	17,12 (1,24)	7,76 (0,0351)
CPSK2154V1	21"	53,3	54"	137,2	19,25 (1,24)	8,73 (0,0351)
CPSK2454V1	24"	61,0	54"	137,2	19,70 (1,24)	8,93 (0,0351)
60" (152,4 cm) Traverses						
CPSK1460V1	14"	35,6	60"	152,4	17,39 (1,38)	7,89 (0,0390)
CPSK1860V1	18"	45,7	60"	152,4	18,80 (1,38)	8,53 (0,0390)
CPSK2160V1	21"	53,3	60"	152,4	21,26 (1,38)	9,64 (0,0390)
CPSK2460V1	24"	61,0	60"	152,4	21,32 (1,38)	9,67 (0,0390)
72" (182,9 cm) Traverses						
CPSK1472V1	14"	35,6	72"	182,9	21,10 (1,66)	9,57 (0,0470)
CPSK1872V1	18"	45,7	72"	182,9	22,55 (1,66)	10,23 (0,0470)
CPSK2172V1	21"	53,3	72"	182,9	25,53 (1,66)	11,58 (0,0470)
CPSK2472V1	24"	61,0	72"	182,9	25,96 (1,66)	11,77 (0,0470)

Item No. _____

Specifier Identification No. _____

Code No. _____

Quantity _____

Shelf Kits with Solid Shelf Plates

code	depth		length		case lbs. (cube)	case kg. (cube m ³)
	in.	cm	in.	cm		
24" (61 cm) Traverses						
CPSK1424S1	14"	35,6	24"	61,0	7,79 (0,83)	3,53 (0,0235)
CPSK1824S1	18"	45,7	24"	61,0	8,34 (0,83)	3,78 (0,0235)
CPSK2124S1	21"	53,3	24"	61,0	9,14 (0,83)	4,14 (0,0235)
CPSK2424S1	24"	61,0	24"	61,0	9,27 (0,83)	4,20 (0,0235)
30" (76,2 cm) Traverses						
CPSK1430S1	14"	35,6	30"	76,2	9,62 (0,83)	4,36 (0,0235)
CPSK1830S1	18"	45,7	30"	76,2	10,20 (0,83)	4,63 (0,0235)
CPSK2130S1	21"	53,3	30"	76,2	11,28 (0,83)	5,12 (0,0235)
CPSK2430S1	24"	61,0	30"	76,2	11,61 (0,83)	5,27 (0,0235)
36" (91,4 cm) Traverses						
CPSK1436S1	14"	35,6	36"	91,4	11,45 (0,83)	5,19 (0,0235)
CPSK1836S1	18"	45,7	36"	91,4	12,06 (0,83)	5,47 (0,0235)
CPSK2136S1	21"	53,3	36"	91,4	13,42 (0,83)	6,09 (0,0235)
CPSK2436S1	24"	61,0	36"	91,4	13,95 (0,83)	6,33 (0,0235)
42" (106,7 cm) Traverses						
CPSK1442S1	14"	35,6	42"	106,7	13,29 (0,97)	6,03 (0,0274)
CPSK1842S1	18"	45,7	42"	106,7	14,40 (0,97)	6,53 (0,0274)
CPSK2142S1	21"	53,3	42"	106,7	16,17 (0,97)	7,33 (0,0274)
CPSK2442S1	24"	61,0	42"	106,7	16,40 (0,97)	7,44 (0,0274)
48" (121,9 cm) Traverses						
CPSK1448S1	14"	35,6	48"	121,9	15,11 (1,06)	6,85 (0,0300)
CPSK1848S1	18"	45,7	48"	121,9	15,78 (1,06)	7,16 (0,0300)
CPSK2148S1	21"	53,3	48"	121,9	17,71 (1,06)	8,03 (0,0300)
CPSK2448S1	24"	61,0	48"	121,9	18,63 (1,06)	8,45 (0,0300)
54" (137,2 cm) Traverses						
CPSK1454S1	14"	35,6	54"	137,2	16,94 (1,24)	7,68 (0,0351)
CPSK1854S1	18"	45,7	54"	137,2	18,12 (1,24)	8,22 (0,0351)
CPSK2154S1	21"	53,3	54"	137,2	20,46 (1,24)	9,28 (0,0351)
CPSK2454S1	24"	61,0	54"	137,2	21,08 (1,24)	9,56 (0,0351)
60" (152,4 cm) Traverses						
CPSK1460S1	14"	35,6	60"	152,4	18,29 (1,38)	8,30 (0,0390)
CPSK1860S1	18"	45,7	60"	152,4	19,95 (1,38)	9,05 (0,0390)
CPSK2160S1	21"	53,3	60"	152,4	22,65 (1,38)	10,27 (0,0390)
CPSK2460S1	24"	61,0	60"	152,4	22,96 (1,38)	10,41 (0,0390)
72" (182,9 cm) Traverses						
CPSK1472S1	14"	35,6	72"	182,9	22,20 (1,66)	10,07 (0,0470)
CPSK1872S1	18"	45,7	72"	182,9	23,91 (1,66)	10,84 (0,0470)
CPSK2172S1	21"	53,3	72"	182,9	27,19 (1,66)	12,33 (0,0470)
CPSK2472S1	24"	61,0	72"	182,9	27,89 (1,66)	12,65 (0,0470)

Architect Specs

Posts: Internal steel core, reinforced polypropylene exterior.
Post Connectors: Reinforced polypropylene.
Traverses: Internal steel core, reinforced polypropylene exterior.
Vented/Solid Shelf Plates: Reinforced polypropylene with Camguard™ antimicrobial.
Corner Connectors: Reinforced nylon.
Adjustable Foot: Reinforced nylon.
Seismic Foot: Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided)
Wall Fastener: Stainless steel.

Optional Accessories

Seismic Foot CSEQ3 **Color:** Silver **Case pack:** 4 each
 (Bolts not provided)
Wall Fastener CSWF **Color:** Silver **Case pack:** 4 each
Identification Tag 6" CSID6 **Color:** White/Clear **Case pack:** 12 each
Identification Tag 3" CSID3 **Color:** White/Clear **Case pack:** 12 each

Standard Color

Speckled Gray (480)

Approvals

