

Camshelving®

Stationary - Starter Units

4 Shelf Units, Vented Shelf Plates only with Camguard™ antimicrobial

2 Post Heights

64" (162,6 cm) and 72" (182,9 cm)

3 Shelf Widths

18" (45,7 cm), 21" (53,3) and 24" (61 cm)

5 Shelf Lengths

36", 42", 48", 54", 60" (91,4 cm, 106,7 cm, 121,9 cm, 137,2cm, 152,4 cm)

• Starter Unit includes:

- Two Post Kits.
- Four Vented Shelf Kits.



Features & Benefits

Versatile Storage

For use in any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C). Weldless and rust free.

Fits in Any Space

Units combine together in straight lines by sharing posts of existing units. Corner Connectors, made of reinforced nylon, connect units together in a 90° angle. Unique design maximizes valuable space and offers strength and stability. Simplify assembly and reduce costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Easy to Clean

Camshelving shelf plates contain Camguard™ antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Molded in dovetails on Posts ensure that Traverses set easily into place.

Strong as Steel

Posts and Traverses are made of a steel core coated with polypropylene. Uniquely engineered Post Connectors offer exceptional cross stabilization. Shelves up to 48" (121,9 cm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 72" (137,2 - 182,9 cm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold 400 lbs. (182 kg) for any length traverse.

Easy to Adjust

Requires use of rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Sturdy reinforced nylon foot on bottom of each stationary Post adjusts easily for floor irregularities.

Optional Accessories

Includes Wall Fastener and Seismic Foot. Each are packed 4 per case. Identification Tags clip easily onto traverses. Dunnage stand recommended for heavy usage with shelves 54" (137,2 cm) or longer. Increases capacity of bottom shelf to 1,000 lbs. (450 kg).

Item No. _____


Specifier Identification No. _____

Code No. _____

Quantity _____



Four Shelf Starter Unit consists of two Post Kits and four Vented Shelf Kits.



Dunnage Stand



Set of Left and Right Corner Connectors (1 set required per shelf).

Approvals



Components

* Does not include 6" (15 cm) Shelf Plate, Wall Fastener and Seismic Foot.

Stationary - Starter Units

4 Shelf Units, Vented Shelf Plates only

Four shelf Starter Unit includes two Post Kits and four Vented Shelf Kits

64" (162,6 cm) Height 18" (45,7 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSU48366	36" 91,4	77.36 (5.90)	35,09 (0,1671)
CSU48426	42" 106,7	86.08 (5.90)	39,04 (0,1671)
CSU48486	48" 121,9	91.36 (5.90)	41,44 (0,1671)
CSU48546	54" 137,2	100.08 (5.90)	46,00 (0,1671)
CSU48606	60" 152,4	106.80 (5.90)	48,44 (0,1671)

72" (182,9 cm) Height 18" (45,7 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSU48367	36" 91,4	79.46 (5.90)	36,04 (0,1671)
CSU48427	42" 106,7	88.18 (5.90)	40,00 (0,1671)
CSU48487	48" 121,9	93.46 (5.90)	42,39 (0,1671)
CSU48547	54" 137,2	103.58 (5.90)	47,00 (0,1671)
CSU48607	60" 152,4	108.90 (5.90)	49,40 (0,1671)

64" (162,6 cm) Height 21" (53,3 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSU41366	36" 91,4	82.92 (7.17)	37,61 (0,2030)
CSU41426	42" 106,7	93.12 (7.17)	42,24 (0,2030)
CSU41486	48" 121,9	98.96 (7.17)	44,89 (0,2030)
CSU41546	54" 137,2	109.20 (7.17)	49,53 (0,2030)
CSU41606	60" 152,4	117.24 (7.17)	53,18 (0,2030)

72" (182,9 cm) Height 21" (53,3 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSU41367	36" 91,4	86.42 (7.17)	39,20 (0,2030)
CSU41427	42" 106,7	96.62 (7.17)	43,83 (0,2030)
CSU41487	48" 121,9	102.46 (7.17)	46,48 (0,2030)
CSU41547	54" 137,2	112.70 (7.17)	51,12 (0,2030)
CSU41607	60" 152,4	120.74 (7.17)	54,77 (0,2030)

64" (162,6 cm) Height 24" (61 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSU44366	36" 91,4	85.44 (8.50)	38,75 (0,2407)
CSU44426	42" 106,7	94.24 (8.50)	42,75 (0,2407)
CSU44486	48" 121,9	103.00 (8.50)	46,72 (0,2407)
CSU44546	54" 137,2	111.80 (8.50)	51,00 (0,2407)
CSU44606	60" 152,4	118.28 (8.50)	53,65 (0,2407)

72" (182,9 cm) Height 24" (61 cm) Width

Code	traverse in. cm	case lbs. (cube)	case kg. (cube m ³)
CSU44367	36" 91,4	88.94 (8.50)	40,34 (0,2407)
CSU44427	42" 106,7	97.74 (8.50)	44,33 (0,2407)
CSU44487	48" 121,9	106.50 (8.50)	48,31 (0,2407)
CSU44547	54" 137,2	115.30 (8.50)	52,50 (0,2407)
CSU44607	60" 152,4	121.78 (8.50)	55,24 (0,2407)

Corner Connector Set

Case Pack: 1 set

code	description	case lbs. (cube)	case kg. (cube m ³)
CSSC	Right and Left	0.38 (0.05)	0,02 (0,0014)

Dunnage Stands

Case Pack: 1

6½" (16,5 cm) Height

code	width	case lbs. (cube)	case kg. (cube m ³)
CSDS18	18"	2.90 (0.22)	1,30 (0,0062)
CSDS21	21"	3.10 (0.26)	1,40 (0,0074)
CSDS24	24"	3.30 (0.30)	1,50 (0,0085)

Architect Specs

Posts:	Internal steel core, reinforced polypropylene exterior.
Post Connectors:	Reinforced polypropylene.
Traverses:	Internal steel core, reinforced polypropylene exterior.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard™ antimicrobial.
Corner Connectors:	Reinforced nylon.
Adjustable Foot:	Reinforced nylon.
Seismic Foot:	Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided)
Wall Fastener:	Stainless steel.

Optional Accessories

Seismic Foot	<input type="checkbox"/> CSEQ3	Color: Silver	Case pack: 4 each
(Bolts not provided)			
Wall Fastener	<input type="checkbox"/> CSWF	Color: Silver	Case pack: 4 each
Identification Tag 6"	<input type="checkbox"/> CSID	Color: White/Clear	Case pack: 12 each
Identification Tag 3"	<input type="checkbox"/> CSID3	Color: White/Clear	Case pack: 12 each

Standard Colors

- Speckled Gray (480)

Approvals



NSF Components

* Does not include 6" (15 cm) Shelf Plate, Wall Fastener and Seismic Foot.