

## Camshelving® Elements Series

### Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

#### 4 Shelf Depths

14" (360 mm), 18" (460 mm),  
21" (540 mm), 24" (610 mm)

#### 5 Shelf Lengths

See cutsheet 2BCS for sizes 54" - 78" (1380 mm - 1980 mm)

24" (610 mm), 30" (760 mm),  
36" (910 mm), 42" (1070 mm), 48" (1220 mm)



#### \* Shelf Kit includes:

Two Stationary Traverses, 8 Stationary Dovetails (4 ea. A & B),  
Vented or Solid Shelf Plates to complete one shelf.

#### Features & Benefits

##### Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 78" (1380 - 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

##### Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

##### Shelving for Life

Non-corrosive design will endure all areas of operation - dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings - without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

##### Fits in Any Space

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Corner Connectors bring units together in 90° angle to create corner & U-shaped units. Reduces costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

##### Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Four Shelf Unit with Vented Shelf Plates.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

##### Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

##### Optional Accessories

Wall Fastener and Seismic Foot are packed 4 per case and do not include bolts or screws. Identification Tags clip easily onto traverses.

#### Approvals



COMPONENT

\* Does not include Wall Fastener and Seismic Foot.

# Camshelving® Elements Series

## Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

### Stationary – Shelf Kits with Vented Shelf Plates

| CODE                           | DEPTH<br>IN. MM | LENGTH<br>IN. MM | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|--------------------------------|-----------------|------------------|---------------------|------------------------------------|
| <b>24" (610 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1424V1                      | 14" 360 mm      | 24" 610 mm       | 5.58 (0.96)         | 2,26 (0,03)                        |
| ESK1824V1                      | 18" 460 mm      | 24" 610 mm       | 6.18 (0.96)         | 2,59 (0,03)                        |
| ESK2124V1                      | 21" 540 mm      | 24" 610 mm       | 6.82 (0.96)         | 2,82 (0,03)                        |
| ESK2424V1                      | 24" 610 mm      | 24" 610 mm       | 7.26 (0.96)         | 3,20 (0,03)                        |
| <b>30" (760 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1430V1                      | 14" 360 mm      | 30" 760 mm       | 6.41 (0.96)         | 2,91 (0,03)                        |
| ESK1830V1                      | 18" 460 mm      | 30" 760 mm       | 7.14 (0.96)         | 3,24 (0,03)                        |
| ESK2130V1                      | 21" 540 mm      | 30" 760 mm       | 7.65 (0.96)         | 3,47 (0,03)                        |
| ESK2430V1                      | 24" 610 mm      | 30" 760 mm       | 8.48 (0.96)         | 3,85 (0,03)                        |
| <b>36" (910 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1436V1                      | 14" 360 mm      | 36" 910 mm       | 7.88 (1.51)         | 3,57 (0,04)                        |
| ESK1836V1                      | 18" 460 mm      | 36" 910 mm       | 8,75 (1.51)         | 3,97 (0,04)                        |
| ESK2136V1                      | 21" 540 mm      | 36" 910 mm       | 9.74 (1.51)         | 4,42 (0,04)                        |
| ESK2436V1                      | 24" 610 mm      | 36" 910 mm       | 10.55 (1.51)        | 4,79 (0,04)                        |
| <b>42" (1070 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1442V1                      | 14" 360 mm      | 42" 1070 mm      | 9.36 (2.03)         | 4,24 (0,06)                        |
| ESK1842V1                      | 18" 460 mm      | 42" 1070 mm      | 10.46 (2.03)        | 4,75 (0,06)                        |
| ESK2142V1                      | 21" 540 mm      | 42" 1070 mm      | 11.64 (2.03)        | 5,28 (0,06)                        |
| ESK2442V1                      | 24" 610 mm      | 42" 1070 mm      | 12.58 (2.03)        | 5,70 (0,06)                        |
| <b>48" (1220 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1448V1                      | 14" 360 mm      | 48" 1220 mm      | 9.97 (1.54)         | 4,52 (0,04)                        |
| ESK1848V1                      | 18" 460 mm      | 48" 1220 mm      | 11.12 (1.54)        | 5,05 (0,04)                        |
| ESK2148V1                      | 21" 540 mm      | 48" 1220 mm      | 12.46 (1.54)        | 5,65 (0,04)                        |
| ESK2448V1                      | 24" 610 mm      | 48" 1220 mm      | 13.75 (1.54)        | 6,24 (0,04)                        |

### Corner Connector Set

| CODE | DESCRIPTION    | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|------|----------------|---------------------|------------------------------------|
| ECC1 | Right and Left | 0.70 (0.4)          | 0,031 (0,001)                      |

Case Pack: 1 set

### Architect Specs

|                                   |                                                                                       |
|-----------------------------------|---------------------------------------------------------------------------------------|
| <b>Posts:</b>                     | Proprietary non-corrosive composite material.                                         |
| <b>Post Connectors:</b>           | Glass Filled Polypropylene.                                                           |
| <b>Traverses:</b>                 | Proprietary non-corrosive composite material.                                         |
| <b>Vented/Solid Shelf Plates:</b> | Reinforced polypropylene with Camguard® Antimicrobial.                                |
| <b>Corner Connectors:</b>         | Glass Filled Polypropylene.                                                           |
| <b>Adjustable Foot:</b>           | Glass Filled Nylon.                                                                   |
| <b>Seismic Foot:</b>              | Stainless steel post and wide foot plate, 3 holes for bolts.<br>(Bolts not provided). |
| <b>Divider Bars:</b>              | Glass Filled Nylon.                                                                   |
| <b>Wall Fastener:</b>             | Stainless Steel.                                                                      |
| <b>Dovetails:</b>                 | Resin Nylon.                                                                          |
| <b>Wedges:</b>                    | Resin Polypropylene.                                                                  |

### Stationary – Shelf Kits with Solid Shelf Plates

| CODE                           | DEPTH<br>IN. MM | LENGTH<br>IN. MM | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|--------------------------------|-----------------|------------------|---------------------|------------------------------------|
| <b>24" (610 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1424S1                      | 14" 360 mm      | 24" 610 mm       | 5.76 (0.96)         | 2,38 (0,03)                        |
| ESK1824S1                      | 18" 460 mm      | 24" 610 mm       | 6.48 (0.96)         | 2,77 (0,03)                        |
| ESK2124S1                      | 21" 540 mm      | 24" 610 mm       | 7.40 (0.96)         | 3,15 (0,03)                        |
| ESK2424S1                      | 24" 610 mm      | 24" 610 mm       | 7.40 (0.96)         | 3,50 (0,03)                        |
| <b>30" (910 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1430S1                      | 14" 360 mm      | 30" 760 mm       | 6.88 (0.96)         | 3,03 (0,03)                        |
| ESK1830S1                      | 18" 460 mm      | 30" 760 mm       | 7.55 (0.96)         | 3,42 (0,03)                        |
| ESK2130S1                      | 21" 540 mm      | 30" 760 mm       | 8.38 (0.96)         | 3,80 (0,03)                        |
| ESK2430S1                      | 24" 610 mm      | 30" 760 mm       | 9.13 (0.96)         | 4,14 (0,03)                        |
| <b>36" (910 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1436S1                      | 14" 360 mm      | 36" 910 mm       | 8.23 (1.51)         | 3,73 (0,04)                        |
| ESK1836S1                      | 18" 460 mm      | 36" 910 mm       | 9.23 (1.51)         | 4,19 (0,04)                        |
| ESK2136S1                      | 21" 540 mm      | 36" 910 mm       | 10.65 (1.51)        | 4,83 (0,04)                        |
| ESK2436S1                      | 24" 610 mm      | 36" 910 mm       | 11.40 (1.51)        | 5,17 (0,04)                        |
| <b>42" (1070 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1442S1                      | 14" 360 mm      | 42" 1070 mm      | 9.77 (2.03)         | 4,43 (0,06)                        |
| ESK1842S1                      | 18" 460 mm      | 42" 1070 mm      | 11.09 (2.03)        | 5,03 (0,06)                        |
| ESK2142S1                      | 21" 540 mm      | 42" 1070 mm      | 12.61 (2.03)        | 5,72 (0,06)                        |
| ESK2442S1                      | 24" 610 mm      | 42" 1070 mm      | 13.50 (2.03)        | 6,12 (0,06)                        |
| <b>48" (1220 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1448S1                      | 14" 360 mm      | 48" 1220 mm      | 10.50 (1.54)        | 4,76 (0,04)                        |
| ESK1848S1                      | 18" 460 mm      | 48" 1220 mm      | 11.78 (1.54)        | 5,34 (0,04)                        |
| ESK2148S1                      | 21" 540 mm      | 48" 1220 mm      | 13.70 (1.54)        | 6,21 (0,04)                        |
| ESK2448S1                      | 24" 610 mm      | 48" 1220 mm      | 14.90 (1.54)        | 6,76 (0,04)                        |

### Optional Accessories

|                              |                                |                           |                           |
|------------------------------|--------------------------------|---------------------------|---------------------------|
| <b>Seismic Foot</b>          | <input type="checkbox"/> CSEQ3 | <b>Color:</b> Silver      | <b>Case pack:</b> 4 each  |
| (Bolts not provided)         |                                |                           |                           |
| <b>Wall Fastener</b>         | <input type="checkbox"/> CSWF  | <b>Color:</b> Silver      | <b>Case pack:</b> 4 each  |
| <b>Identification Tag 6"</b> | <input type="checkbox"/> CSID6 | <b>Color:</b> White/Clear | <b>Case pack:</b> 12 each |
| <b>Identification Tag 3"</b> | <input type="checkbox"/> CSID3 | <b>Color:</b> White/Clear | <b>Case pack:</b> 12 each |

### Standard Color

Brushed Graphite (580)

### Approvals



\* Does not include Wall Fastener and Seismic Foot.

COMPONENT

**CAMBRO**  
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.  
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

## Camshelving® Elements Series

### Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

#### 4 Shelf Depths

14" (360 mm), 18" (460 mm),  
21" (540 mm), 24" (610 mm)

#### 4 Shelf Lengths

24" (610 mm), 30" (760 mm),  
36" (910 mm), 42" (1070 mm), 48" (1220 mm)



#### \* Shelf Kit includes:

Two Stationary Traverses, 8 Stationary Dovetails (4 ea. A & B),  
Vented or Solid Shelf Plates to complete one shelf.

### Features & Benefits

#### Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" – 78" (1380 – 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

#### Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

#### Shelving for Life

Non-corrosive design will endure all areas of operation – dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings – without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

#### Fits in Any Space

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Corner Connectors bring units together in 90° angle to create corner & U-shaped units. Reduces costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

#### Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Four Shelf Unit with Vented Shelf Plates.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

#### Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

#### Optional Accessories

Wall Fastener and Seismic Foot are packed 4 per case and do not include bolts or screws. Identification Tags clip easily onto traverses.

### Approvals



COMPONENT

\* Does not include Wall Fastener and Seismic Foot.

# Camshelving® Elements Series

## Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

### Stationary – Shelf Kits with Vented Shelf Plates

| CODE                           | DEPTH<br>IN. MM | LENGTH<br>IN. MM | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|--------------------------------|-----------------|------------------|---------------------|------------------------------------|
| <b>54" (1380 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1454V1                      | 14" 360 mm      | 54" 1380 mm      | 11.55 (2.49)        | 5,24 (0,07)                        |
| ESK1854V1                      | 18" 460 mm      | 54" 1380 mm      | 12.94 (2.49)        | 5,87 (0,07)                        |
| ESK2154V1                      | 21" 540 mm      | 54" 1380 mm      | 14.46 (2.49)        | 6,56 (0,07)                        |
| ESK2454V1                      | 24" 610 mm      | 54" 1380 mm      | 15.88 (2.49)        | 7,20 (0,07)                        |
| <b>60" (1530 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1460V1                      | 14" 360 mm      | 60" 1530 mm      | 13.01 (2.77)        | 5,90 (0,08)                        |
| ESK1860V1                      | 18" 460 mm      | 60" 1530 mm      | 14.62 (2.77)        | 6,63 (0,08)                        |
| ESK2160V1                      | 21" 540 mm      | 60" 1530 mm      | 16.34 (2.77)        | 7,41 (0,08)                        |
| ESK2460V1                      | 24" 610 mm      | 60" 1530 mm      | 17.88 (2.77)        | 8,11 (0,08)                        |
| <b>72" (1830 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1472V1                      | 14" 360 mm      | 72" 1830 mm      | 14.95 (3.31)        | 6,78 (0,09)                        |
| ESK1872V1                      | 18" 460 mm      | 72" 1830 mm      | 16.85 (3.31)        | 7,64 (0,09)                        |
| ESK2172V1                      | 21" 540 mm      | 72" 1830 mm      | 18.91 (3.31)        | 8,58 (0,09)                        |
| ESK2472V1                      | 24" 610 mm      | 72" 1830 mm      | 20.93 (3.31)        | 9,49 (0,09)                        |
| <b>78" (1980 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1478V1                      | 14" 360 mm      | 78" 1980 mm      | 15.89 (3.60)        | 7,21 (0,10)                        |
| ESK1878V1                      | 18" 460 mm      | 78" 1980 mm      | 17.79 (3.60)        | 8,07 (0,10)                        |
| ESK2178V1                      | 21" 540 mm      | 78" 1980 mm      | 19.85 (3.60)        | 9,00 (0,10)                        |
| ESK2478V1                      | 24" 610 mm      | 78" 1980 mm      | 21.87 (3.60)        | 9,92 (0,10)                        |

### Stationary – Shelf Kits with Solid Shelf Plates

| CODE                           | DEPTH<br>IN. MM | LENGTH<br>IN. MM | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|--------------------------------|-----------------|------------------|---------------------|------------------------------------|
| <b>54" (1380 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1454S1                      | 14" 360 mm      | 54" 1380 mm      | 12.15 (2.49)        | 5,51 (0,07)                        |
| ESK1854S1                      | 18" 460 mm      | 54" 1380 mm      | 13.74 (2.49)        | 6,23 (0,07)                        |
| ESK2154S1                      | 21" 540 mm      | 54" 1380 mm      | 15.77 (2.49)        | 7,15 (0,07)                        |
| ESK2454S1                      | 24" 610 mm      | 54" 1380 mm      | 17.10 (2.49)        | 7,75 (0,07)                        |
| <b>60" (1530 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1460S1                      | 14" 360 mm      | 60" 1530 mm      | 13.66 (2.77)        | 6,20 (0,08)                        |
| ESK1860S1                      | 18" 460 mm      | 60" 1530 mm      | 15.58 (2.77)        | 7,07 (0,08)                        |
| ESK2160S1                      | 21" 540 mm      | 60" 1530 mm      | 17.70 (2.77)        | 8,03 (0,08)                        |
| ESK2460S1                      | 24" 610 mm      | 60" 1530 mm      | 19.16 (2.77)        | 8,69 (0,08)                        |
| <b>72" (1830 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1472S1                      | 14" 360 mm      | 72" 1830 mm      | 15.79 (3.31)        | 7,16 (0,09)                        |
| ESK1872S1                      | 18" 460 mm      | 72" 1830 mm      | 17.98 (3.31)        | 8,16 (0,09)                        |
| ESK2172S1                      | 21" 540 mm      | 72" 1830 mm      | 20.61 (3.31)        | 9,35 (0,09)                        |
| ESK2472S1                      | 24" 610 mm      | 72" 1830 mm      | 22.51 (3.31)        | 10,21 (0,09)                       |
| <b>78" (1980 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1478S1                      | 14" 360 mm      | 78" 1980 mm      | 16.73 (3.60)        | 7,59 (0,10)                        |
| ESK1878S1                      | 18" 460 mm      | 78" 1980 mm      | 18.92 (3.60)        | 8,58 (0,10)                        |
| ESK2178S1                      | 21" 540 mm      | 78" 1980 mm      | 21.55 (3.60)        | 9,78 (0,10)                        |
| ESK2478S1                      | 24" 610 mm      | 78" 1980 mm      | 23.45 (3.60)        | 10,64 (0,10)                       |

### Corner Connector Set

| CODE | DESCRIPTION    | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|------|----------------|---------------------|------------------------------------|
| ECC1 | Right and Left | 0.70 (0.04)         | 0,32 (0,001)                       |

Case Pack: 1 set

### Architect Specs

|                                   |                                                                                       |
|-----------------------------------|---------------------------------------------------------------------------------------|
| <b>Posts:</b>                     | Proprietary non-corrosive composite material.                                         |
| <b>Post Connectors:</b>           | Glass Filled Polypropylene.                                                           |
| <b>Traverses:</b>                 | Proprietary non-corrosive composite material.                                         |
| <b>Vented/Solid Shelf Plates:</b> | Reinforced polypropylene with Camguard® Antimicrobial.                                |
| <b>Corner Connectors:</b>         | Glass Filled Polypropylene.                                                           |
| <b>Adjustable Foot:</b>           | Glass Filled Nylon.                                                                   |
| <b>Seismic Foot:</b>              | Stainless steel post and wide foot plate, 3 holes for bolts.<br>(Bolts not provided). |
| <b>Divider Bars:</b>              | Glass Filled Nylon.                                                                   |
| <b>Wall Fastener:</b>             | Stainless Steel.                                                                      |
| <b>Dovetails:</b>                 | Resin Nylon.                                                                          |
| <b>Wedges:</b>                    | Resin Polypropylene.                                                                  |

### Optional Accessories

|                              |                                |                           |                           |
|------------------------------|--------------------------------|---------------------------|---------------------------|
| <b>Seismic Foot</b>          | <input type="checkbox"/> CSEQ3 | <b>Color:</b> Silver      | <b>Case pack:</b> 4 each  |
| (Bolts not provided)         |                                |                           |                           |
| <b>Wall Fastener</b>         | <input type="checkbox"/> CSWF  | <b>Color:</b> Silver      | <b>Case pack:</b> 4 each  |
| <b>Identification Tag 6"</b> | <input type="checkbox"/> CSID6 | <b>Color:</b> White/Clear | <b>Case pack:</b> 12 each |
| <b>Identification Tag 3"</b> | <input type="checkbox"/> CSID3 | <b>Color:</b> White/Clear | <b>Case pack:</b> 12 each |

### Standard Color

Brushed Graphite (580)

### Approvals



\* Does not include Wall Fastener and Seismic Foot.

COMPONENT

**CAMBRO**  
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.  
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

D081511



# Camshelving® Elements Series

## 4-Shelf Vented Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

### 2 Shelf Depths

18" (460 mm), 24" (610 mm)

### 3 Shelf Lengths

36" (910 mm), 48" (1220 mm)

60" (1530 mm)



### \* 4-Shelf Kit includes:

Vented shelf plates for 4 shelves, 8 stationary traverses, 1 bag of 32 stationary traverse dovetails (16 ea. A & B), and instructions.

### Features & Benefits

#### Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" – 78" (1380 mm – 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

#### Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

#### Shelving for Life

Non-corrosive design will endure all areas of operation – dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings – without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

#### Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

#### Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Four Shelf Unit with Vented Shelf Plates.



Vented shelf plates for 4 shelves, 8 stationary traverses, 1 bag of 32 stationary traverse dovetails (16 ea. A & B), and instructions.

### Approvals



\* Does not include Wall Fastener and Seismic Foot.



# Camshelving® Elements Series

## 4-Shelf Vented Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

### 2 Shelf Depths

18" (460 mm), 24" (610 mm)

### 3 Shelf Lengths

36" (910 mm), 48" (1220 mm)

60" (1530 mm)



Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

### \* 4-Shelf Kit includes:

Vented shelf plates for 4 shelves, 8 stationary traverses,  
1 bag of 32 stationary traverse dovetails (16 ea. A & B),  
and instructions.

### 4-Shelf Vented Shelf Kits for Stationary Units

| CODE                           | DEPTH<br>IN. MM | LENGTH<br>IN. MM | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|--------------------------------|-----------------|------------------|---------------------|------------------------------------|
| <b>36" (910 mm) Traverses</b>  |                 |                  |                     |                                    |
| ESK1836V4                      | 18" 460 mm      | 36" 910 mm       | 32.10 (3.75)        | 14,56 (0,11)                       |
| ESK2436V4                      | 24" 610 mm      | 36" 910 mm       | 39.31 (3.75)        | 17,83 (0,11)                       |
| <b>48" (1220 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1848V4                      | 18" 460 mm      | 48" 1220 mm      | 41.04 (4.31)        | 18,62 (0,12)                       |
| ESK2448V4                      | 24" 610 mm      | 48" 1220 mm      | 13.75 (1.54)        | 6,24 (0,04)                        |
| <b>60" (1530 mm) Traverses</b> |                 |                  |                     |                                    |
| ESK1860V4                      | 18" 460 mm      | 60" 1530 mm      | 51.36 (5.84)        | 23,32 (0,16)                       |
| ESK2460V4                      | 24" 610 mm      | 60" 1530 mm      | 64.40 (5.84)        | 29,24 (0,16)                       |

### Corner Connector Set

| CODE | DESCRIPTION    | CASE LBS.<br>(CUBE) | CASE KG.<br>(CUBE M <sup>3</sup> ) |
|------|----------------|---------------------|------------------------------------|
| ECC1 | Right and Left | 0.70 (0.04)         | 0,32 (0,001)                       |

Case Pack: 1 set

### Architect Specs

**Traverses:** Proprietary non-corrosive composite material.  
**Vented/Solid Shelf Plates:** Reinforced polypropylene with Camguard® Antimicrobial.  
**Stationary Dovetails:** Resin Nylon.

### Optional Accessories

**Seismic Foot**  CSEQ3 **Color:** Silver **Case pack:** 4 each  
(Bolts not provided)  
**Wall Fastener**  CSWF **Color:** Silver **Case pack:** 4 each  
**Identification Tag 6"**  CSID6 **Color:** White/Clear **Case pack:** 12 each  
**Identification Tag 3"**  CSID3 **Color:** White/Clear **Case pack:** 12 each

### Standard Color

Brushed Graphite (580)

### Approvals



COMPONENT

\* Does not include Wall Fastener and Seismic Foot.



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.  
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003