

Camshelving® Elements Series

Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

4 Shelf Depths

14" (360 mm), 18" (460 mm),
21" (540 mm), 24" (610 mm)

5 Shelf Lengths

See cutsheet 2BCS for sizes 54" - 78" (1380 mm - 1980 mm)
24" (610 mm), 30" (760 mm),
36" (910 mm), 42" (1070 mm), 48" (1220 mm)



* Shelf Kit includes:

Two Stationary Traverses, 8 Stationary Dovetails (4 ea. A & B),
Vented or Solid Shelf Plates to complete one shelf.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 78" (1380 - 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

Shelving for Life

Non-corrosive design will endure all areas of operation - dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings - without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

Fits in Any Space

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Corner Connectors bring units together in 90° angle to create corner & U-shaped units. Reduces costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____



Four Shelf Unit with Vented Shelf Plates.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

Optional Accessories

Wall Fastener and Seismic Foot are packed 4 per case and do not include bolts or screws. Identification Tags clip easily onto traverses.

Approvals



* Does not include Wall Fastener and Seismic Foot.

Camshelving® Elements Series

Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

Stationary – Shelf Kits with Vented Shelf Plates

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
24" (610 mm) Traverses				
ESK1424V1	14" 360 mm	24" 610 mm	5.58 (0.96)	2,26 (0,03)
ESK1824V1	18" 460 mm	24" 610 mm	6.18 (0.96)	2,59 (0,03)
ESK2124V1	21" 540 mm	24" 610 mm	6.82 (0.96)	2,82 (0,03)
ESK2424V1	24" 610 mm	24" 610 mm	7.26 (0.96)	3,20 (0,03)
30" (760 mm) Traverses				
ESK1430V1	14" 360 mm	30" 760 mm	6.41 (0.96)	2,91 (0,03)
ESK1830V1	18" 460 mm	30" 760 mm	7.14 (0.96)	3,24 (0,03)
ESK2130V1	21" 540 mm	30" 760 mm	7.65 (0.96)	3,47 (0,03)
ESK2430V1	24" 610 mm	30" 760 mm	8.48 (0.96)	3,85 (0,03)
36" (910 mm) Traverses				
ESK1436V1	14" 360 mm	36" 910 mm	7.88 (1.51)	3,57 (0,04)
ESK1836V1	18" 460 mm	36" 910 mm	8,75 (1.51)	3,97 (0,04)
ESK2136V1	21" 540 mm	36" 910 mm	9.74 (1.51)	4,42 (0,04)
ESK2436V1	24" 610 mm	36" 910 mm	10.55 (1.51)	4,79 (0,04)
42" (1070 mm) Traverses				
ESK1442V1	14" 360 mm	42" 1070 mm	9.36 (2.03)	4,24 (0,06)
ESK1842V1	18" 460 mm	42" 1070 mm	10.46 (2.03)	4,75 (0,06)
ESK2142V1	21" 540 mm	42" 1070 mm	11.64 (2.03)	5,28 (0,06)
ESK2442V1	24" 610 mm	42" 1070 mm	12.58 (2.03)	5,70 (0,06)
48" (1220 mm) Traverses				
ESK1448V1	14" 360 mm	48" 1220 mm	9.97 (1.54)	4,52 (0,04)
ESK1848V1	18" 460 mm	48" 1220 mm	11.12 (1.54)	5,05 (0,04)
ESK2148V1	21" 540 mm	48" 1220 mm	12.46 (1.54)	5,65 (0,04)
ESK2448V1	24" 610 mm	48" 1220 mm	13.75 (1.54)	6,24 (0,04)

Corner Connector Set

CODE	DESCRIPTION	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
ECC1	Right and Left	0.70 (0.4)	0,031 (0,001)

Case Pack: 1 set

Architect Specs

Posts:	Proprietary non-corrosive composite material.
Post Connectors:	Glass Filled Polypropylene.
Traverses:	Proprietary non-corrosive composite material.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard® Antimicrobial.
Corner Connectors:	Glass Filled Polypropylene.
Adjustable Foot:	Glass Filled Nylon.
Seismic Foot:	Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided).
Divider Bars:	Glass Filled Nylon.
Wall Fastener:	Stainless Steel.
Dovetails:	Resin Nylon.
Wedges:	Resin Polypropylene.

Stationary – Shelf Kits with Solid Shelf Plates

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
24" (610 mm) Traverses				
ESK1424S1	14" 360 mm	24" 610 mm	5.76 (0.96)	2,38 (0,03)
ESK1824S1	18" 460 mm	24" 610 mm	6.48 (0.96)	2,77 (0,03)
ESK2124S1	21" 540 mm	24" 610 mm	7.40 (0.96)	3,15 (0,03)
ESK2424S1	24" 610 mm	24" 610 mm	7.40 (0.96)	3,50 (0,03)
30" (910 mm) Traverses				
ESK1430S1	14" 360 mm	30" 760 mm	6.88 (0.96)	3,03 (0,03)
ESK1830S1	18" 460 mm	30" 760 mm	7.55 (0.96)	3,42 (0,03)
ESK2130S1	21" 540 mm	30" 760 mm	8.38 (0.96)	3,80 (0,03)
ESK2430S1	24" 610 mm	30" 760 mm	9.13 (0.96)	4,14 (0,03)
36" (910 mm) Traverses				
ESK1436S1	14" 360 mm	36" 910 mm	8.23 (1.51)	3,73 (0,04)
ESK1836S1	18" 460 mm	36" 910 mm	9.23 (1.51)	4,19 (0,04)
ESK2136S1	21" 540 mm	36" 910 mm	10.65 (1.51)	4,83 (0,04)
ESK2436S1	24" 610 mm	36" 910 mm	11.40 (1.51)	5,17 (0,04)
42" (1070 mm) Traverses				
ESK1442S1	14" 360 mm	42" 1070 mm	9.77 (2.03)	4,43 (0,06)
ESK1842S1	18" 460 mm	42" 1070 mm	11.09 (2.03)	5,03 (0,06)
ESK2142S1	21" 540 mm	42" 1070 mm	12.61 (2.03)	5,72 (0,06)
ESK2442S1	24" 610 mm	42" 1070 mm	13.50 (2.03)	6,12 (0,06)
48" (1220 mm) Traverses				
ESK1448S1	14" 360 mm	48" 1220 mm	10.50 (1.54)	4,76 (0,04)
ESK1848S1	18" 460 mm	48" 1220 mm	11.78 (1.54)	5,34 (0,04)
ESK2148S1	21" 540 mm	48" 1220 mm	13.70 (1.54)	6,21 (0,04)
ESK2448S1	24" 610 mm	48" 1220 mm	14.90 (1.54)	6,76 (0,04)

Optional Accessories

Seismic Foot	<input type="checkbox"/> CSEQ3	Color: Silver	Case pack: 4 each
(Bolts not provided)			
Wall Fastener	<input type="checkbox"/> CSWF	Color: Silver	Case pack: 4 each
Identification Tag 6"	<input type="checkbox"/> CSID6	Color: White/Clear	Case pack: 12 each
Identification Tag 3"	<input type="checkbox"/> CSID3	Color: White/Clear	Case pack: 12 each

Standard Color

Brushed Graphite (580)

Approvals



* Does not include Wall Fastener and Seismic Foot.

COMPONENT

CAMBRO
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

D081511



Camshelving® Elements Series

Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

4 Shelf Depths

14" (360 mm), 18" (460 mm),
21" (540 mm), 24" (610 mm)

4 Shelf Lengths

24" (610 mm), 30" (760 mm),
36" (910 mm), 42" (1070 mm), 48" (1220 mm)



* Shelf Kit includes:

Two Stationary Traverses, 8 Stationary Dovetails (4 ea. A & B),
Vented or Solid Shelf Plates to complete one shelf.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" – 78" (1380 – 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

Shelving for Life

Non-corrosive design will endure all areas of operation – dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings – without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

Fits in Any Space

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Corner Connectors bring units together in 90° angle to create corner & U-shaped units. Reduces costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____



Four Shelf Unit with Vented Shelf Plates.



Vented Shelf Kit includes two Traverses and Vented Shelf Set for one shelf.



Solid Shelf Kit includes two Traverses and Solid Shelf Set for one shelf.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

Optional Accessories

Wall Fastener and Seismic Foot are packed 4 per case and do not include bolts or screws. Identification Tags clip easily onto traverses.

Approvals



COMPONENT

* Does not include Wall Fastener and Seismic Foot.



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

2BCS

Camshelving® Elements Series

Single Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

Stationary – Shelf Kits with Vented Shelf Plates

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M ³)
54" (1380 mm) Traverses				
ESK1454V1	14" 360 mm	54" 1380 mm	11.55 (2.49)	5,24 (0,07)
ESK1854V1	18" 460 mm	54" 1380 mm	12.94 (2.49)	5,87 (0,07)
ESK2154V1	21" 540 mm	54" 1380 mm	14.46 (2.49)	6,56 (0,07)
ESK2454V1	24" 610 mm	54" 1380 mm	15.88 (2.49)	7,20 (0,07)
60" (1530 mm) Traverses				
ESK1460V1	14" 360 mm	60" 1530 mm	13.01 (2.77)	5,90 (0,08)
ESK1860V1	18" 460 mm	60" 1530 mm	14.62 (2.77)	6,63 (0,08)
ESK2160V1	21" 540 mm	60" 1530 mm	16.34 (2.77)	7,41 (0,08)
ESK2460V1	24" 610 mm	60" 1530 mm	17.88 (2.77)	8,11 (0,08)
72" (1830 mm) Traverses				
ESK1472V1	14" 360 mm	72" 1830 mm	14.95 (3.31)	6,78 (0,09)
ESK1872V1	18" 460 mm	72" 1830 mm	16.85 (3.31)	7,64 (0,09)
ESK2172V1	21" 540 mm	72" 1830 mm	18.91 (3.31)	8,58 (0,09)
ESK2472V1	24" 610 mm	72" 1830 mm	20.93 (3.31)	9,49 (0,09)
78" (1980 mm) Traverses				
ESK1478V1	14" 360 mm	78" 1980 mm	15.89 (3.60)	7,21 (0,10)
ESK1878V1	18" 460 mm	78" 1980 mm	17.79 (3.60)	8,07 (0,10)
ESK2178V1	21" 540 mm	78" 1980 mm	19.85 (3.60)	9,00 (0,10)
ESK2478V1	24" 610 mm	78" 1980 mm	21.87 (3.60)	9,92 (0,10)

Stationary – Shelf Kits with Solid Shelf Plates

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M ³)
54" (1380 mm) Traverses				
ESK1454S1	14" 360 mm	54" 1380 mm	12.15 (2.49)	5,51 (0,07)
ESK1854S1	18" 460 mm	54" 1380 mm	13.74 (2.49)	6,23 (0,07)
ESK2154S1	21" 540 mm	54" 1380 mm	15.77 (2.49)	7,15 (0,07)
ESK2454S1	24" 610 mm	54" 1380 mm	17.10 (2.49)	7,75 (0,07)
60" (1530 mm) Traverses				
ESK1460S1	14" 360 mm	60" 1530 mm	13.66 (2.77)	6,20 (0,08)
ESK1860S1	18" 460 mm	60" 1530 mm	15.58 (2.77)	7,07 (0,08)
ESK2160S1	21" 540 mm	60" 1530 mm	17.70 (2.77)	8,03 (0,08)
ESK2460S1	24" 610 mm	60" 1530 mm	19.16 (2.77)	8,69 (0,08)
72" (1830 mm) Traverses				
ESK1472S1	14" 360 mm	72" 1830 mm	15.79 (3.31)	7,16 (0,09)
ESK1872S1	18" 460 mm	72" 1830 mm	17.98 (3.31)	8,16 (0,09)
ESK2172S1	21" 540 mm	72" 1830 mm	20.61 (3.31)	9,35 (0,09)
ESK2472S1	24" 610 mm	72" 1830 mm	22.51 (3.31)	10,21 (0,09)
78" (1980 mm) Traverses				
ESK1478S1	14" 360 mm	78" 1980 mm	16.73 (3.60)	7,59 (0,10)
ESK1878S1	18" 460 mm	78" 1980 mm	18.92 (3.60)	8,58 (0,10)
ESK2178S1	21" 540 mm	78" 1980 mm	21.55 (3.60)	9,78 (0,10)
ESK2478S1	24" 610 mm	78" 1980 mm	23.45 (3.60)	10,64 (0,10)

Corner Connector Set

CODE	DESCRIPTION	CASE LBS. (CUBE)	CASE KG. (CUBE M ³)
ECC1	Right and Left	0.70 (0.04)	0,32 (0,001)

Case Pack: 1 set

Architect Specs

Posts:	Proprietary non-corrosive composite material.
Post Connectors:	Glass Filled Polypropylene.
Traverses:	Proprietary non-corrosive composite material.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard® Antimicrobial.
Corner Connectors:	Glass Filled Polypropylene.
Adjustable Foot:	Glass Filled Nylon.
Seismic Foot:	Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided).
Divider Bars:	Glass Filled Nylon.
Wall Fastener:	Stainless Steel.
Dovetails:	Resin Nylon.
Wedges:	Resin Polypropylene.

Optional Accessories

Seismic Foot	<input type="checkbox"/> CSEQ3	Color: Silver	Case pack: 4 each
(Bolts not provided)			
Wall Fastener	<input type="checkbox"/> CSWF	Color: Silver	Case pack: 4 each
Identification Tag 6"	<input type="checkbox"/> CSID6	Color: White/Clear	Case pack: 12 each
Identification Tag 3"	<input type="checkbox"/> CSID3	Color: White/Clear	Case pack: 12 each

Standard Color

Brushed Graphite (580)

Approvals



* Does not include Wall Fastener and Seismic Foot.

COMPONENT

CAMBRO
TRUSTED FOR GENERATIONS™

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003

D081511



Camshelving® Elements Series

4-Shelf Vented Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

2 Shelf Depths

18" (460 mm), 24" (610 mm)

3 Shelf Lengths

36" (910 mm), 48" (1220 mm)

60" (1530 mm)



* 4-Shelf Kit includes:

Vented shelf plates for 4 shelves, 8 stationary traverses, 1 bag of 32 stationary traverse dovetails (16 ea. A & B), and instructions.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" – 78" (1380 mm – 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

Shelving for Life

Non-corrosive design will endure all areas of operation – dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings – without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____



Four Shelf Unit with Vented Shelf Plates.



Vented shelf plates for 4 shelves, 8 stationary traverses, 1 bag of 32 stationary traverse dovetails (16 ea. A & B), and instructions.

Approvals



* Does not include Wall Fastener and Seismic Foot.



Camshelving® Elements Series

4-Shelf Vented Shelf Kits for Stationary Units Shelf Kits with Camguard® Antimicrobial

2 Shelf Depths

18" (460 mm), 24" (610 mm)

3 Shelf Lengths

36" (910 mm), 48" (1220 mm)

60" (1530 mm)



Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

* 4-Shelf Kit includes:

Vented shelf plates for 4 shelves, 8 stationary traverses,
1 bag of 32 stationary traverse dovetails (16 ea. A & B),
and instructions.

4-Shelf Vented Shelf Kits for Stationary Units

CODE	DEPTH IN. MM	LENGTH IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M ³)
36" (910 mm) Traverses				
ESK1836V4	18" 460 mm	36" 910 mm	32.10 (3.75)	14,56 (0,11)
ESK2436V4	24" 610 mm	36" 910 mm	39.31 (3.75)	17,83 (0,11)
48" (1220 mm) Traverses				
ESK1848V4	18" 460 mm	48" 1220 mm	41.04 (4.31)	18,62 (0,12)
ESK2448V4	24" 610 mm	48" 1220 mm	13.75 (1.54)	6,24 (0,04)
60" (1530 mm) Traverses				
ESK1860V4	18" 460 mm	60" 1530 mm	51.36 (5.84)	23,32 (0,16)
ESK2460V4	24" 610 mm	60" 1530 mm	64.40 (5.84)	29,24 (0,16)

Corner Connector Set

CODE	DESCRIPTION	CASE LBS. (CUBE)	CASE KG. (CUBE M ³)
ECC1	Right and Left	0.70 (0.04)	0,32 (0,001)

Case Pack: 1 set

Architect Specs

Traverses: Proprietary non-corrosive composite material.
Vented/Solid Shelf Plates: Reinforced polypropylene with Camguard® Antimicrobial.
Stationary Dovetails: Resin Nylon.

Optional Accessories

Seismic Foot CSEQ3 **Color:** Silver **Case pack:** 4 each
(Bolts not provided)
Wall Fastener CSWF **Color:** Silver **Case pack:** 4 each
Identification Tag 6" CSID6 **Color:** White/Clear **Case pack:** 12 each
Identification Tag 3" CSID3 **Color:** White/Clear **Case pack:** 12 each

Standard Color

Brushed Graphite (580)

Approvals



COMPONENT

* Does not include Wall Fastener and Seismic Foot.



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003