



Product Part Numbers - Order Using Part Numbers Listed Below

Configuration	Inside Dia.	LENGTH				
		24"	36"	48"	60"	72"
HOSE ONLY	1/2"	1650BP24	1650BP36	1650BP48	1650BP60	1650BP72
HOSE ONLY	3/4"	1675BP24	1675BP36	1675BP48	1675BP60	1675BP72
HOSE ONLY	1"	16100BP24	16100BP36	16100BP48	16100BP60	16100BP72
HOSE ONLY	1-1/4"	16125BP24	16125BP36	16125BP48	16125BP60	16125BP72

BTU Flow Capacity (Flow rating BTU 0.64 SP. GR@ 0.5 inch WC pressure drop)

Part #	Inside Dia.	LENGTH					
		12"	24"	36"	48"	60"	72"
1650BP	1/2"	152,000	150,000	120,000	106,000	93,000	87,000
1675BP	3/4"	326,000	291,000	256,000	225,000	198,000	175,000
16100BP	1"	652,000	582,000	512,000	451,000	397,000	350,000
16125BP	1-1/4"	1,204,000	1,075,000	946,000	833,000	733,000	645,000



Approvals & Certifications

NSF NSF International Criteria C-2, Special Equipment and/or Devices
 "Component"

SP ANSI Z21.69 / CSA 6.16 - Connectors for Moveable Gas Appliances
 Meets requirements of ANSI Z223.1 / NFPA 54 - National Fuel Gas Code

Refer to catalog page 23 for additional approvals & certifications and Dormont gas connector limited lifetime warranty

Features & Specifications

THE DORMONT BLUE HOSE:

- Tubing Annealed, 304 stainless steel (ASTM A240)
- Braiding Multi-strand, 304 stainless steel wire
- Coating Antimicrobial (patent #6,742,815) PVC, melts at 350°F, coating will not hold a flame; blue color indicates braided connector
- End Fittings Carbon steel; zinc and yellow dichromate coating; male x male
- Stress Guard 360° rotation of end fittings at both ends before and after installation (patent pending)

