

Project #:_	
-	
ltem #:	



Model RCS10DSE shown

Medium Volume This category of microwave is ideal for...

Applications:

- Coffee shops
- Ethnic restaurants
- Concessions
- Dessert stations

All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times. 866-426-2621.



Medium Volume

Amana Commercial Microwave Model RCS10DSE

Power Output

- 1000 watts of power.
- Four power levels.

Easy to Use

- User friendly ten minute dial timer lights up for at-a-glance monitoring.
- Timer automatically resets to zero if door is opened during heating. User option allows manual reset to zero.
- See-through door and lighted interior for monitoring without opening the door.
- 1.2 cubic ft. (34 liter) capacity accommodates a 14" (356 mm) platter, prepackaged foods and single servings.
- Stackable to save valuable counter space.


Easy to Maintain

- Stainless steel exterior and interior for easy cleaning and a commercial look.
- Constructed to withstand the foodservice environment.
- Non-removable air filter protects oven components.
- Backed by the ACP, Inc. 24/7 ComServ Support Center, 866-426-2621.
- ETL Listed.





Amana Commercial Microwave Model RCS10DSE | Medium Volume



Installation clearance: 2" all sides

Drawings available from KCL CADlog - techs@kclcad.com

Specifications		
Model	RCS10DSE UPC Code 728028129465	
Configuration	Countertop	
Control System	Dial	
Max. Cooking Time	10:00	
Power Levels	4	
Time Entry Option	Yes	
Microwave Distribution	on Rotating antenna, top	
Magnetron	1	
Stackable	Yes	
Stage Cooking	1	
Interior Light	Yes	
Door Handle	Grab & Go	
Signal	End of cycle	
Exterior Dimensions	H 13 ½" (352) W 22" (559) D*19" (483)	
Cavity Dimensions	H 8 ½" (216) W 14 ½" (368) D 15" (381)	
Door Depth	32 ¾" (832), 90°+ door open	
Usable Cavity Space	1.2 cubic ft. (34 liter)	
Exterior Finish	Stainless steel	
Interior Finish	Stainless steel	
Power Consumption	1550 W, 13 A	
Power Output**	1000 W** Microwave	
Power Source	120V, 60 Hz, 15 A single phase	
Plug Configuration / Cord	NEMA 5-15 5 ft. (1.5m)	
equency 2450 MHz		
roduct Weight 41 lbs. (18.6 kg.)		
Ship weight (approx.) 47 lbs. (21.3 kg.)		
Shipping Carton Size	H 17" (432) W 25 ½" (660) D 19 ¾" (502)	
UPS Shippable	Yes	

Specifications

Commercial microwave shall have a user-friendly 10 minute dial timer with illuminated digits and an end of cycle audible signal. Timer shall automatically reset if the door is opened during heating with user option to manually reset to zero. There shall be a four power level and cooking stage. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90°+ opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Interior ceramic shelf shall be sealed and recessed on oven bottom to reduce plate-to-shelf edge impact. Oven shall have a stainless steel exterior and interior and be stackable to save counter and shelf space. The air filter shall be permanently affixed to the front of the oven. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, UL923 for safety and NSF4 for sanitation.

Warranty

Warranty Certificate for this product can be found on the ACP, Inc. website at:

Intertek

www.acpsolutions.com/warranty

Service

All products are backed by the ACP, Inc. 24/7 ComServ Support Center.



Measurements in () are millimeters

- * Includes handle
- ** IEC 60705 Tested

