



We put space to work.

Item # _____

Job _____

Super Erecta® Hot Shelving

Shelves that keep food hot, appetizing, and ready-to-go.

Flexible Design: Configure heated holding solutions almost anyway imaginable by combining with other Super Erecta shelving systems to create

- Stand alone heated holding solutions
- Storage solutions with integrated heated holding
- Workstations with integrated heated holding

Consistent Heat Distribution: High quality, Type 304 stainless steel construction combined with aluminum inner core for consistent, reliable radiant heat across each shelf. Adjustable thermostat, 200°F (93°C) maximum surface temperature.

Low Wattage Design: Requires less power to operate and lower energy consumption.

Adjustability: Shelves can be adjusted at 1" (25mm) increments to customize to desired shelf spacing. Compatible with all Super Erecta SiteSelect posts

Cleanable and Durable: Smooth corrosion resistant stainless steel surfaces are easy-to-clean and durable to stand up to daily usage.

Shelf Sizes: 18 different shelf sizes to choose from.

- 3 depths: 14" (356mm), 18" (457mm), 24" (610mm),
- 6 lengths: 24" (610mm), 30" (762mm), 36" (914mm), 42" (1067mm), 48" (1219mm), 60" (1524mm).

Plastic feet included with every shelf. Posts ordered separately.

Enclosed Shelf Kits: Extend holding time with pass-thru enclosure kits that include a heated shelf, non-heated stainless shelf, side panels, hinged doors on control side, and sliding doors on opposite side. 9 sizes to choose from.

- 3 depths 14" (356mm), 18" (457mm), 24" (610mm)
- 3 lengths 36" (914mm), 42" (1067mm), 48" (1219mm).

Posts ordered separately.

Easy Order Workstations: 5 pre-configured assembly / prep stations with integrated heated holding to boost operational efficiency. 3 models with an open heated shelf and 2 models with an enclosed heated shelf.

Warranty: 2 year parts & labor warranty



Shown as a stand alone counter-top unit with plastic feet.



Shown as a tiered shelving unit.



Shown with heated shelf, enclosure kit and standard Super Erecta shelving.



Heated shelf enclosure kit shown with a Super Erecta workstation.



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

L02-242
Printed in U.S.A. 6/20

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2020 InterMetro Industries Corp.



Super Erecta® Hot Shelving

Specifications

Construction: Type 304 stainless steel exterior surfaces with black epoxy coated corners. Each shelf includes (4) polymer split sleeves to mount to Super Erecta SiteSelect posts (posts sold separately). (4) 3" polymer feet to use on countertop as a heated worksurface.

Heating System: Thermostatically controlled, low wattage foil elements adhered to aluminum diffuser to evenly heat the stainless steel surface with hot air. On / Off power switch and thermostat provide separate individual control of every shelf.

Power Cord: Each shelf has a permanently mounted 6' (183cm) long cord with NEMA 5-15P plug end.

Clearance Requirements: Minimum clearance from bottom of shelf to combustible surface is 1.5" (38mm). Recommended minimum spacing between shelves is 5.73" (146mm)

Shelves

Includes shelf, one bag of split sleeves and (4) plastic feet (posts not included). For actual dimensions add 5/8" (16mm) to depth and subtract 1/16" (2mm) from length.

	120V Model No. & Electrical Specifications (NEMA 5-15P plug)	Nominal Depth x Length (in.)	(mm)	Approx. Shipping Weight	Approx. Shipping Volume
HS1424	120V, 200W, 1.7A	14x24	356x610	14.5 lbs (6.6 kg)	1.2 ft³ (0.03 m³)
HS1430	120V, 200W, 1.7A	14x30	356x762	17.2 lbs (7.8 kg)	1.5 ft³ (0.04 m³)
HS1436	120V, 400W, 3.4A	14x36	356x914	20.3 lbs (9.2 kg)	1.7 ft³ (0.05 m³)
HS1442	120V, 400W, 3.4A	14x42	356x1067	23.1 lbs (10.5 kg)	2.0 ft³ (0.06 m³)
HS1448	120V, 400W, 3.4A	14x48	356x1219	25.8 lbs (11.7 kg)	2.3 ft³ (0.06 m³)
HS1460	120V, 600W, 5.0A	14x60	356x1524	31.7 lbs (14.4 kg)	2.8 ft³ (0.08 m³)
HS1824	120V, 200W, 1.7A	18x24	457x610	17.5 lbs (8.0 kg)	1.5 ft³ (0.04 m³)
HS1830	120V, 200W, 1.7A	18x30	457x762	21.0 lbs (9.5 kg)	1.8 ft³ (0.05 m³)
HS1836	120V, 400W, 3.4A	18x36	457x914	24.8 lbs (11.3 kg)	2.2 ft³ (0.06 m³)
HS1842	120V, 400W, 3.4A	18x42	457x1067	28.3 lbs (12.8 kg)	2.5 ft³ (0.07 m³)
HS1848	120V, 400W, 3.4A	18x48	457x1219	31.8 lbs (14.4 kg)	2.8 ft³ (0.08 m³)
HS1860	120V, 600W, 5.0A	18x60	457x1524	38.0 lbs (17.7 kg)	3.5 ft³ (0.10 m³)
HS2424	120V, 200W, 1.7A	24x24	610x610	22.1 lbs (10.0 kg)	1.9 ft³ (0.05 m³)
HS2430	120V, 400W, 3.4A	24x30	610x762	27.0 lbs (12.3 kg)	2.3 ft³ (0.07 m³)
HS2436	120V, 400W, 3.4A	24x36	610x914	31.6 lbs (14.3 kg)	2.7 ft³ (0.08 m³)
HS2442	120V, 600W, 5.0A	24x42	610x1067	36.4 lbs (16.5 kg)	3.2 ft³ (0.09 m³)
HS2448	120V, 600W, 5.0A	24x48	610x1219	41.0 lbs (18.6 kg)	3.6 ft³ (0.10 m³)
HS2460	120V, 800W, 6.7A	24x60	610x1524	49.9 lbs (22.6 kg)	4.4 ft³ (0.13 m³)



Enclosed Shelf Kits

Includes heated shelf, non-heated stainless shelf, side panels, hinged doors on control side, sliding doors on opposite side, and split sleeves for each shelf (posts not included)

	120V Model No. & Electrical Specifications (NEMA 5-15P plug)	Dimensions Length x Depth x Height (in.)	(mm)	Approx. Shipping Weight	Approx. Shipping Volume
HS1436-EKIT	120V, 400W, 3.4A	36.7x17.7x17.4	933x450x442	71.3 lbs (32.3 kg)	6.0 ft³ (0.17 m³)
HS1442-EKIT	120V, 400W, 3.4A	42.7x17.7x17.4	1085x450x442	79.7 lbs (36.2 kg)	7.0 ft³ (0.20 m³)
HS1448-EKIT	120V, 400W, 3.4A	48.7x17.7x17.4	1237x450x442	86.7 lbs (39.3 kg)	8.0 ft³ (0.23 m³)
HS1836-EKIT	120V, 400W, 3.4A	36.7x 21.7x17.4	933x552x442	78.3 lbs (35.5 kg)	6.0 ft³ (0.17 m³)
HS1842-EKIT	120V, 400W, 3.4A	42.7x 21.7x17.4	1085x552x442	86.5 lbs (39.2 kg)	7.0 ft³ (0.20 m³)
HS1848-EKIT	120V, 400W, 3.4A	48.7x21.7 x17.4	1237x552x442	94.7 lbs (42.9 kg)	8.0 ft³ (0.23 m³)
HS2436-EKIT	120V, 400W, 3.4A	36.7x27.7 x17.4	933x704x442	89.3 lbs (40.5 kg)	7.5 ft³ (0.21 m³)
HS2442-EKIT	120V, 600W, 5.0A	42.7x 27.7x17.4	1085x704x442	98.3 lbs (44.6 kg)	8.7 ft³ (0.25 m³)
HS2448-EKIT	120V, 600W, 5.0A	48.7x 27.7x17.4	1237x704x442	106.6 lbs (48.3 kg)	9.9 ft³ (0.28 m³)





We put space to work.

Super Erecta® Hot Shelving

Workstations with Open Heated Over Shelf

Includes 24" deep stainless steel worksurface, 3 sided open frame to allow under counter storage, stationary posts, and 14" deep overhead heated & wire shelves.

120V Model No. & Electrical Specifications (NEMA 5-15P plug)	Nominal Length x Depth x Height (in.)	Nominal Length x Depth x Height (mm)	Approx. Shipping Weight	Approx. Shipping Volume
EZHS36W-KIT 120V, 400W, 3.4A	36x24x64	914x610x1613	78.0 lbs (35.4 kg)	7.0 ft³ (0.20 m³)
EZHS48W-KIT 120V, 400W, 3.4A	48x24x64	1217x610x1613	93.6 lbs (42.4 kg)	8.9 ft³ (0.25 m³)
EZHS60W-KIT 120V, 600W, 5.0A	60x24x64	1522x610x1613	109.2 lbs (49.5 kg)	10.9 ft³ (0.31 m³)



Workstations with Enclosed Heated Over Shelf

Includes 24" deep stainless steel worksurface, 3 sided open frame to allow under counter storage, stationary posts, and 14" deep overhead enclosed heated shelf.

120V Model No. & Electrical Specifications (NEMA 5-15P plug)	Nominal Length x Depth x Height (in.)	Nominal Length x Depth x Height (mm)	Approx. Shipping Weight	Approx. Shipping Volume
EZHSE36W-KIT 120V, 400W, 3.4A	36x24x64	914x610x1613	120.0 lbs (54.4 kg)	10.5 ft³ (0.30 m³)
EZHSE48W-KIT 120V, 400W, 3.4A	48x24x64	1217x610x1613	142.9 lbs (64.8 kg)	13.4 ft³ (0.38 m³)



SiteSelect™ Posts

Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification. Stationary post heights include leveling foot, mobile posts for use with stem casters



Stationary Post

Post for Stem Caster

Stationary Posts

Model No. Chrome	Model No. Stainless Steel	Actual Height (in.)	Actual Height (mm)	Approx Pkd. Wt. (lbs.)	Approx Pkd. Wt. (kg)
7P	-	7.375	187	0.5	0.3
13P	13PS	14.375	365	1	0.5
27P	27PS	28.375	720	1.75	0.75
33P	33PS	34.375	873	2	0.9
54P	54PS	54.4375	1382	3	1.4
63P	63PS	62.4375	1585	3.5	1.6
74P	74PS	74.5	1892	4	1.8
86P	86PS	86.5	2197	5	2.3
*96P	-	96.5	2450	5.5	2.5

Mobile Posts

Model No. Chrome	Model No. Stainless Steel	Actual Height (in.)	Actual Height (mm)	Approx. Pkd. Wt. (lbs.)	Approx. Pkd. Wt. (kg)
13UP	13UPS	13.75	349	1	0.5
27UP	27UPS	27.75	704	1.75	0.75
33UP	33UPS	33.75	857	2	0.9
54UP	54UPS	53.8125	1366	3	1.4
63UP	63UPS	61.8125	1570	3.5	1.6
-	-	69.75	1771	3.75	1.7
74UP	74UPS	73.875	1876	4	1.8
86UP	86UPS	85.875	2181	4.5	2.0

Replacement Parts & Accessories

Replacement Split Sleeves: **Model # 9985** (bag of 4 sets)
Replacement Feet: **Model # 3FHS-4PK** (Qty = 4)

Plastic Post Glides: **Model # 9991P** (Qty = 1)

Thermostat Cover: **Model # HS-THERMCOVER**

4 Outlet Power Strip: **Model # HS-PSTRIP4** (120V, 15A, 1800W)

an Ali Group Company



The Spirit of Excellence