

m	#			

Job _____

SUPER ADJUSTABLE SUPER ERECTA™ STEM CASTER CARTS — WIRE SHELVES

- Stem Caster Carts combine Super Adjustable
 Super Erecta™ wire shelving features with the mobility
 of stem casters to provide a high-quality, strong and
 versatile material handling cart.
- Carts are preconfigured with two swivel and two swivel brake casters. All Metro casters are non-marking and come complete with a 3½" (89mm) donut bumper.
- Total cart capacity (evenly distributed)
- Cart with Polyurethane casters: 900 lb. (408kg)
- Cart with Resilient Rubber casters: 600 lb. (272kg)
- Unique Design: Open wire surfaces minimize dust accumulation and allow a free circulation of air and greater visibility.
- Reclaim wasted space. Easy "No tool" shelf adjustment. The Corner Release System allows shelves to be repositioned quickly to maximize the use of vertical space.
- Unique Post Design: SiteSelect post design provides a visual guide for positioning and adjusting shelves, saving considerable time during assembly and adjustment. Posts have circular grooves at 1" (25mm) intervals and are numbered every 2" (51mm). An easy-to-identify double groove, every 8" (203mm), offers a quick way to align all shelves.
- Easily Adjustable at 1" (25mm increments):
 Unique Corner Release and SiteSelect Posts create
 a total system that offers "Tool-Free," fast adjustment
 at 1" (25mm) intervals along the entire height of the
 post. Unlock the corner releases, reposition the
 wedges and sleeves, and re-locate the shelf. The
 shelf simply seats into place.
- Versatile Construction: Super Adjustable Super Erecta[™] wire shelving can change as quickly as your needs change. By using various accessories, hundreds of shelving combinations become possible.











SiteSelect Post

Note: For additional caster options see spec sheet 11.20











STANDARD UNITS

Consist of designated number of shelves, (4) posts, plastic split sleeves, donut bumpers, and designated casters. Shelves and posts are Chrome finish. Carts use stem caster posts (Model Number 63UP).

Four-Tier Units

Overall Height 677/8" (1724mm)

	Model Number with Casters					
Two Swivel	Two Swivel					
Two Brake	Two Brake		Shelf		Approx.	
Resilient	Polyuerthane	Widt	Width/Length		Pkd. Wt.	
Rubber Casters	Casters	(in.)	(mm)	(lbs.)	(kg)	
A336BC	A336EC	18x36	457x914	60	27	
A356BC	A356EC	18x48	457x1219	72	32	
A366BC	A366EC	18x60	457x1524	88	40	
A436BC	A436EC	21x36	530x914	69	31	
A456BC	A456EC	21x48	530x1219	81	36	
A466BC	A466EC	21x60	530x1524	98	44	
A536BC	A536EC	24x36	610x914	76	34	
A556BC	A556EC	24x48	610x1219	92	41	
A566BC	A566EC	24x60	610x1524	112	51	

Five-Tier Units

Overall Height 67⁷/₈" (1724mm)

5A336BC	5A336EC	18x36	457x914	70	31
5A356BC	5A356EC	18x48	457x1219	84	37
5A366BC	5A366EC	18x60	457x1524	105	48
5A436BC	5A436EC	21x36	530x914	80	36
5A456BC	5A456EC	21x48	530x1219	95	42
5A466BC	5A466EC	21x60	530x1524	116	52
5A536BC	5A536EC	24x36	610x914	89	40
5A556BC	5A556EC	24x48	610x1219	108	48
5A566BC	5A566EC	24x60	610x1524	133	61

Note: The post used on the carts is model number 63UP.

TO ORDER BY COMPONENTS

- 1. Order shelves from sheet 10.01 or price list. (Will be packed with plastic split sleeves.)
- 2. Order stem casters from sheet 11.20 or price list. Donut bumper comes with caster.

LOAD RATING: Not to exceed 3 times the caster load rating.

** Carts with polyurethane casters are designed to hold up to 900 lbs. (408kg).

Carts with rubber casters can hold up to 600 lbs. (272kg).

Important: When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

All Metro Catalog Sheets are available on our website: www.metro.com



North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741

Product Information. U.S. and Canada: 1.800.992.1776 Outside U.S. and Canada: www.metro.com/contactus

L02-035 Printed in U.S.A Rev. 05/14