

CBS-61H Volume Coffee at Your Fingertips

- Patented Gravity Dispense Tube System resists lime build up to provide dependable performance
- Holds a constant water temperature during 100% of brew cycles
- Maintains sprayover volume consistency
- Utilizes all solid state components



CBS-62H with two
TPD-3.0 LUXUS® dispensers



Brew basket safety locks incorporated into start switch



Stainless steel gourmet-size brew baskets designed for heavier brew ratios



Brews directly into our 3.0 gallon LUXUS® TPD-style Dispenser



LUXUS® TPD-30

Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	1.5	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
40	21 3/8	22 3/8	111	115

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour (1)	
							<i>cold water</i>	<i>hot water</i>
C61016	2x3.0 KW	120/208	1	3+G	4.6	22.1	3.7	8.6
		120/220			5.2	23.4	4.3	9.0
		120/240			6.1	25.5	5.0	9.0
C61026	2x4.0 KW	120/208	1	3+G	6.1	29.3	5.0	9.0
		120/220			6.8	31.0	5.8	9.0
		120/240			8.1	33.8	6.6	9.0
C61036(1)	3x3.0 KW	120/208	3	4+G	6.9	19.5	5.6	9.0
		120/220			7.7	20.6	6.5	9.0
		120/240			9.1	22.4	7.4	9.0
C61046(1)	3x4.0 KW	120/208	3	4+G	9.1	25.8	7.4	9.0
		120/220			10.3	27.3	8.6	9.0
		120/240			12.1	29.7	9.0	9.0
C61146(1)	3x4.0 KW	480	3	3+G	12.1	14.9	9.0	9.0
* C61076(1)	3x3.0 KW	220/380	3	4+G	7.6	12	7.4	9.0
* C61086(1)	3x4.0 KW	220/380	3	4+G	10.1	15.3	9.0	9.0
* C61126(1)	3x3.0 KW	240/415	3	3+G	9.1	12.9	7.4	7.4
* C61136(1)	3x4.0 KW	240/415	3	3+G	12.1	17.5	9.0	9.0

Specifications subject to change without notice

(1) Based on standard factory settings : 4.0 minute brew time, 0% prewet, 200°F water

*EXPORT ONLY

