

roundup

by A.J. Antunes & Co. ®

Miracle Steamer Models: MS-150, MS-155 MS-250, MS-255, MS-355



MS-150



MS-250



MS-355

The Miracle Steamer is the latest addition to our steamer technology product line.

The Miracle Steamer features two steam options. For instant steam that quickly reheats items or melts cheese, a simple push button releases dry, super-heated steam into the food chamber. Because the steam is released from the top of the food chamber, heat penetration is very efficient and fast.

For items that require longer steaming times, a programmable time cycle is also provided.

NOTE: Units with a direct water hookup require a water pressure regulator. The psi should be between 20 and 30.

Features:

- Easy-to-use drawer or spatula system.
- Compact size.
- Digital display electronic controls.
- Ideal for melting cheese, reheating and steaming a variety of food items.
- Quick and easy clean up.
- Patented open steam generator allows use of plain tap water.
- Stainless steel construction for long life.
- Models available with either a self-contained water reservoir or direct water hookup.

roundup

by A.J. Antunes & Co.®

Miracle Steamer Models: MS-150, MS-155 MS-250, MS-255, MS-355

Dimensions			
Model & Mfg. No.	Width (A)	Depth (B)	Height (C)
MS-150 9100420 9100423 9100426 9100428	21" (533 mm)	21 3/8" (543 mm)	10 1/4" (260 mm)
MS-250 9100430 9100433 9100436 9100438 9100439	21" (533 mm)	21 3/8" (543 mm)	9 1/2" (241 mm)
MS-155 9100450 9100452 9100456 9100458	21" (533 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)
MS-255 9100460 9100462 9100466 9100468	21" (533 mm)	17 1/4" (438 mm)	9 1/2" (241 mm)
MS-355 9100480 9100482 9100486	25 1/4" (641 mm)	17 1/4" (438 mm)	10 1/4" (260 mm)

Electrical Ratings and Plug Configurations							
Model	Mfg. No.	Volts	Watts	Amp.	Hz.	Description	Configuration
MS-150 Spatula style with self- contained water reservoir	9100420	208	3300	15.9	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
	9100426	230	3300	14.4	50/60		
	9100423	120	1800	15	50/60	NEMA 5-15P, 15 Amp., 120 Volt	
	9100428	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt	
MS-250 Spatula style with direct water hookup	9100430	208	3300	15.9	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
	9100433	220- 240	3050- 3600	13.9- 15	50/60		
	9100436	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt	
	9100438	230	3300	14.4	50/60		
	9100439	120	1800	15	50/60	NEMA 5-15P, 15 Amp., 120 Volt	
MS-155 Drawer style with self- contained water reservoir	9100450	208	3300	15.9	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
	9100452	120	1800	15	50/60	NEMA 5-15P, 15 Amp., 120 Volt	
	9100456	230	3300	14.4	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
	9100458	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt	
MS-255 Drawer style with direct water hookup	9100460	208	3300	15.9	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
	9100462	120	1800	15	50/60	NEMA 5-15P, 15 Amp., 120 Volt	
	9100466	230	3300	14.4	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
MS-355 Drawer style with self- contained water reservoir	9100468	230	3300	14.4	50/60	CEE 7/7 16 Amp., 250 Volt	
	9100480	208	3300	15.9	50/60	NEMA 6-20P, 20 Amp., 250 Volt	
	9100486	230	3300	14.4	50/60		
9100482	120	1800	15	50/60	NEMA 5-15P, 15 Amp., 120 Volt		

NOTE: Water Pressure Regulator required on units with direct water hookup.



A.J. Antunes & Co.
Headquarters/Manufacturing
180 Kehoe Boulevard
Carol Stream, Illinois 60188 USA
Phone (630) 784-1000
Toll Free (800) 253-2991
Fax: (630) 784-1650

Antunes Equipment
Manufacturing (Suzhou) Ltd.,
9 Hou Ju Road, Building #24,
S&T Park, SND
Suzhou, Jiangsu, China 215011
Phone: 86-512-6841-3637
Fax: 86-512-6841-3907