

FOODWASTE DISPOSERS

Disposers

ACCESSORY GROUPS:



ACCESS-GROUP A	<i>For All Models – Disposer Must Have Long Upper Housing (Order cone from listing below)</i> Group Includes: Vinyl Scrapping Ring, Stainless Steel Silver-Saver Sleeve with Side Feed Hole, Water Swirl and Vacuum Breaker
ACCESS-GROUP B	<i>For All Models – Disposer Must Have Long Upper Housing (Order cone from listing below)</i> Group Includes: Vinyl Silver-Saver Splash Guard Ring, Water Swirl and Vacuum Breaker
ACCESS-GROUP C	<i>For All Models – Disposer Must Have Long Upper Housing (Order sink from listing below)</i> Group Includes: Vinyl Silver-Saver Splash Guard Ring, Vacuum Breaker, Fixed Direction Water Inlet for Sink and Pre-Rinse Spray with Wall Bracket
ACCESS-GROUP D	<i>For All Models – Disposer Must Have Long Upper Housing</i> Group Includes: Vinyl Silver-Saver Splash Guard Ring, 7" I.D. Stainless Steel Weld-in Adapter for Sink, Fixed Direction Water Inlet for Sink and Vacuum Breaker
ACCESS-GROUP E	<i>For Models FD3/50 Thru FD3/125 – Disposer Must Have Short Upper Housing</i> Group Includes: Cover Stopper and Sink Adapter Assembly for 3½" to 4" Sink Opening, Fixed Direction Water Inlet for Sink and Vacuum Breaker

DISPOSER ACCESSORIES:

Cones – Sink (Type 302 - Stainless Steel)

CONE-15INWS	Cone — 15" I.D. with hole for water swirl inlet
CONE-18INWS	Cone — 18" I.D. with hole for water swirl inlet
CONE-15INNS	Cone — 15" I.D. without swirl hole
CONE-18INNS	Cone — 18" I.D. without swirl hole
SINK-WSWIRL	Sink — 16" x 20" x 7" w/adapter (7" opening), with hole for water inlet

Water Inlets – ½" N.P.T.

WATERIN-CONE	Cone water swirl inlet (for models FD3/50 thru FD500)
WATERIN-SINK	Fixed direction water inlet (for sinks or troughs)

Cone Covers (Type 302 - Stainless Steel)

COVER-15INF	15" Cone cover with feed hole
COVER-18INF	18" Cone cover with feed hole

Disposers

DISPOSER ACCESSORIES:

Cone Feeding Accessories

SLEEVE-SILVER	Stainless steel silver-saver sleeve with side feed hole
SCRAP-RING	Vinyl scrapping ring for use with stainless steel silver-saver sleeve

Splash Guard

SPLASH-GUARD	Vinyl splash guard (for 7" opening cones, sinks and adapter)
---------------------	--

Sink Adapter (Standard Group D Accessory)

ADAPTER-7INCH	7" I.D. stainless steel adapter for welding to sink or trough
----------------------	---

Vacuum Breaker

BREAKER-VACUUM	Vacuum breaker
-----------------------	----------------

Pre-Rinse Spray

SPRAY-PR3F	Flexible pre-rinse spray (38" high) with wall bracket
-------------------	---

Flow Controls Valves – 3/4" N.P.T.

FLOW5G-CNTR	5 gallons per minute for models FD3/50 thru FD3/125
FLOW8G-CNTR	8 gallons per minute for models FD3/150 thru FD3/300
FLOW10G-CNTR	10 gallons per minute for model FD500

Adapters – For installation of Hobart Disposers on existing cones (NOTE: Refer to separate adapter chart for selection of proper adapter)

ADAPTER-31167	Kit No. 31167 For cone type 1 – 4½" I.D. throat
ADAPTER-31168	Kit No. 31168 For cone type 2 – 9" I.D. throat
ADAPTER-31159	Kit No. 31159 For cone type 2 or 3 – 4½" I.D. throat
ADAPTER-31160	Kit No. 31160 For cone type 2 or 3 – 6" I.D. throat
ADAPTER-31169	Kit No. 31169 For cone type 3 – 4¾" I.D. throat
ADAPTER-31170	Kit No. 31170 For cone type 3 – 5¼" I.D. throat
ADAPTER-31171	Kit No. 31171 For cone type 3 – 6¾" I.D. throat
ADAPTER-31166	Kit No. 31166 For cone type 3 – 8" I.D. throat
ADAPTER-31162	Kit No. 31162 For cone type 4 – 4½" I.D. throat
ADAPTER-31163	Kit No. 31163 For cone type 4 – 6" I.D. throat
ADAPTER-31165	Kit No. 31165 For cone type 4 – 6¾" I.D. throat
ADAPTER-31164	Kit No. 31164 For cone type 4 – 6½" I.D. throat
ADAPTER-31161	Kit No. 31161 For cone type 5 – 5" I.D. throat

FOODWASTE DISPOSERS

Disposers

Dealer's Choice Products

PRE-CONFIGURED:

FD3/50-1	1/2 H.P. Disposer with short upper housing – 208-240/480/60/3
FD3/50-2	1/2 H.P. Disposer with long upper housing – 208-240/480/60/3
FD3/50-5	1/2 H.P. Disposer with short upper housing – 120/208-240/60/1
FD3/50-6	1/2 H.P. Disposer with long upper housing – 120/208-240/60/1
FD3/75-1	3/4 H.P. Disposer with short upper housing – 208-240/480/60/3
FD3/75-2	3/4 H.P. Disposer with long upper housing – 208-240/480/60/3
FD3/75-5	3/4 H.P. Disposer with short upper housing – 120/208-240/60/1
FD3/75-6	3/4 H.P. Disposer with long upper housing – 120/208-240/60/1
FD3/125-1	1 1/4 H.P. Disposer with short upper housing – 208-240/480/60/3
FD3/125-2	1 1/4 H.P. Disposer with long upper housing – 208-240/480/60/3
FD3/125-5	1 1/4 H.P. Disposer with short upper housing – 120/208-240/60/1
FD3/125-6	1 1/4 H.P. Disposer with long upper housing – 120/208-240/60/1
FD3/150-1	1 1/2 H.P. Disposer with adjustable bullet feet – 208-240/480/60/3
FD3/150-2	1 1/2 H.P. Disposer with lagdown feet – 208-240/480/60/3
FD3/150-5	1 1/2 H.P. Disposer with adjustable bullet feet – 120/208-240/60/1
FD3/150-6	1 1/2 H.P. Disposer with lagdown feet – 120/208-240/60/1
FD3/200-1	2 H.P. Disposer with adjustable bullet feet – 208-240/480/60/3
FD3/200-5	2 H.P. Disposer with adjustable bullet feet – 120/208-240/60/1
FD3/200-6	2 H.P. Disposer with lagdown feet – 120/208-240/60/1
FD3/300-1	3 H.P. Disposer with adjustable bullet feet – 208-240/480/60/3
FD3/300-2	3 H.P. Disposer with lagdown feet – 208-240/480/60/3
FD500-9	5 H.P. Disposer with adjustable legs – 200-230/400-460/60/3

For disposer accessories refer to pages 184-185

ELECTRICAL CONTROL GROUP:



Control Group 4



Control Group 2



Control Group 3

NOTE: Electrical specifications for Control Groups must match Disposer specs.

Group 4: Models FD3/50 Thru FD3/200 (not available above 250 volts; Must order solenoid valve below)
Includes: Manual reversing switch and NEMA 1 enclosure.

CONTROL-GROUP4	110-120/60/1; 200-230/60/1; 200-230/60/3
-----------------------	--

Solenoid Valve: Specify Exact Voltage (required with Group 4)

VALVE-SOL110	Solenoid Valve 110/60/1
VALVE-SOL220	Solenoid Valve 220/60/1

Group 2: All Models
Includes: Magnetic contractors, push button start & stop, automatic reversion, 110V solenoid valve and NEMA 12 enclosure.

CONTROL-GR20AV	110-120/60/1
CONTROL-GR200E	200-230/60/1
CONTROL-GR20DG	200-230/400-460/60/3

Group 3: All Models
Includes: Magnetic contractors, push button start & stop, automatic reversing, low water pressure cut-off, time delay for water after s line disconnect, 110V solenoid valve and NEMA 12 enclosure..

CONTROL-GR300E	200-230/60/1
CONTROL-GR30DG	200-230/400-460/60/3

