APPLICATION:	Р
JOB NAME:	M
QUANTITY: ITEM NO.:	-
5 1/2" [139,7mm] [176,3mm] [176,3mm] [176,3mm] [176,3mm] [176,3mm]	O F * * * * * * * * * * * * * * * * * *
(+)	

PRODUCT NAME:

ELECTRONIC SENSOR SD

MODEL:

- □ 74016 ELECTRONIC SENSOR BS 0.35 GPM
- ☐ 73751 ELECTRONIC SENSOR BS 0.50 GPM
- □ 74011 ELECTRONIC SENSOR BS 1.00 GPM
- ☐ 74017 ELECTRONIC SENSOR BS 1.50 GPM
- ☐ 74010 ELECTRONIC SENSOR BS 1.80 GPM
- □ 74009 ELECTRONIC SENSOR BS 2.20 GPM
- ☐ 74018 ELECTRONIC SENSOR BS 5.00 GPM

OPTIONS OR MODIFICATIONS:

□ OTHER _____

FEATURES:

- * AUTOMATIC SENSOR FAUCET
- * LOW LEAD BRASS WITH CHROME PLATING
- BATTERY INCLUDED FOR DC USE
- * POWER SUPPLY INCLUDED FOR AC USE
- FRESH BATTERY LIFE UP TO 500.000 CYCLES
- * LOW BATTERY INDICATOR: RED LIGHT FLASH
- * 3 BRAIDED SUPPLY LINES
- * MECHANICAL MIXING VALVE

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 160°F MAX.
- * PRESSURE 200 PSI MAX. STATIC

SHIPPING WEIGHT

* 8.0 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com

WARNING:

Proposition 65 requires that we provide you with the following notice: "This product Contains A Chemical Known To The State Of California To Cause Cancer Or Birth Defects Or Other Reproductive Harm."