

Project _____
 Item _____
 Quantity _____
 CSI Section 11400 _____
 Approval _____
 Date _____

Delta[®] HT-E-SEER

Models

Delta HT-E-SEER

No Stand



Standard Features

- Steam Elimination
- Energy Recovery System collects the hot water vapor inside the machine and uses it to preheat the incoming rinse water
- Operates on a single cold water connection
- Soft Start helps protect glassware from chipping and breaking
- Stainless steel rear dress panel
- Automatic fill
- Push button start
- Built-in booster heater with Sani-Sure™ final rinse system
- Door interlock
- Pressure regulator
- Water hammer arrestor
- Automatic pumped drain for floor and wall drain installations
- Stainless steel wash pump
- Universal timer
- Digital LED control panel
- Delime cycle
- Back dress panel
- Simplified controls allow easy access for operation and service
- Built-in chemical pumps and priming switches

Mandatory Specs

Specify voltage _____

Options

- Drain Water Tempering Kit
- Scale Prevention System (SPS)
- Replacement Cartridge for SPS
- Casters (adds 3/4" to height)
- Tie Down

Accessories

- 36-Compartment Rack
 - 4-1/8" tall (105 mm)
 - 5-5/8" tall (143 mm)
 - 7" tall (178 mm)
- Combination Rack
- Peg Rack

NOTE: A vent hood is not recommended above the Jackson Delta HT-E-SEER as it does not produce excessive vapors. Always check with the local building code to know what type of ventilation is required for commercial dish machine or glasswasher installations in your area.

Specifications

High temperature undercounter dishwasher with steam elimination and energy recovery
 Operates on a single cold water connection
 Uses 0.65 gallons (2.47 liters) of water per rack
 Uses 13.0 gallons (49.21 liters) of water per hour
 Cleans 20 racks per hour
 Cleans 720 glasses per hour
 12" (305 mm) chamber clearance

Three selectable cycles:
 Normal - 145 seconds
 Heavy - 213 seconds
 Extra-Heavy - 313 seconds

Powerful 1 hp wash pump motor
 Air insulated between body and stainless steel housing
 One (1) each peg and combination rack included
 Durable stainless steel construction




Intertek



Intertek





Back and side views shown without rear dress panel.

MODEL NO.	MACHINE DIMENSIONS				WALL CLEARANCE	SHIPPING INFORMATION					
	INSIDE CLEARANCE HEIGHT	INSIDE CLEARANCE WIDTH	INSIDE CLEARANCE DEPTH	DOOR OPEN DEPTH		WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
Delta HT-E-SEER	12" (305 mm)	20" (508 mm)	20" (508 mm)	40.88" (1037 mm)	1/4" (7 mm)	275 lbs (125 kg)	85	20.09 cu. ft.	43.5 (1105 mm)	28" (712 mm)	28.5" (724 mm)

APPROXIMATE TOTAL AMP LOADS	
208/60/1	24.7
230/60/1	26.7

OPERATING CAPACITY	
Racks per Hour	20
Dishes per Hour	500
Glasses per Hour	720

WASH PUMP MOTOR	
Wash Pump	1 hp (208/230v)/ 3/4 hp (460v)

OPERATING CYCLE (seconds)	Wash	Rinse	Dwell	Vent	Total Cycle
Cycle I (Normal)	80	09	11	45	145
Cycle II (Heavy)	148	09	11	45	213
Cycle III (Extra Heavy)	248	09	11	45	313

WATER REQUIREMENTS	
Incoming Water Temperature	40-90° F (4.4-32.2° C)
Gallons per Rack	0.65 gal (2.47 L)
Gallons per Hour	13 gal (49.21 L)
Flow Pressure (PSI)	10
Waterline Size (NPT)	3/4" Male GHT (connect to true 1/2" ID Line)
Drainline Size (ID)	5/8"

OPERATING TEMPERATURES	
Wash	155° F (68.3° C)
Rinse	180° F (82.2° C)

HOW TO SPECIFY: Delta HT-E-SEER

Jackson WWS, Inc.
 Shipping Address: 6209 North U.S. Highway 25E, Gray, KY 40734
 Mailing Address: P.O. Box 1060, Barbourville, KY 40906
 Telephone: 888-800-5672 • Fax: 606-523-1799
 Email: info@jacksonwws.com
 07610-004-71-75 [12/14/2020]

www.jacksonwws.com