

SCHOOL MILK COOLERS

Model: 69K-143 69K-144 69K-145



69K-143



69K-144



69K-145

Central School Milk Coolers offer an efficient, low maintenance solution for milk crate storage and cooling. The cold wall construction delivers a consistent temperature range and stainless steel construction makes for a sleek look and easy cleaning.

FEATURES



- CFC-free refrigerant and foam insulation
- Condensate evaporator – no drain connection needed
- Electronic thermostat controls for accurate control
- Digital LED temperature display for easy readability
- Cold wall construction keeps temperatures consistent - holds milk between 36° & 38° F
- Magnetic gasket can be replaced without any tools
- Stainless Steel interior and exterior for easy cleaning
- 3 sizes available to hold 8, 12 or 16 (13"x13"x11") milk cases per unit
- Includes set of four (4) 4-inch caster wheels

REFRIGERANT

Environmentally-friendly R-290a propane

ELECTRIC

115V/60Hz/1Ph



NEMA 5-15P



Certified to
ANSI-NSF 7



Certified to
ANSI UL 471



DOE 2018
Compliant






2020
Compliant

WARRANTY (USA / CANADA)




Three (3) year parts
Three (3) year on-site labor
Administered by Central, 800-289-3637

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.




SCHOOL MILK COOLERS



69K-143



69K-144



69K-145

	Dimensions in / mm	Capacity (13"x13"x11" Crates)	Capacity (19"x13"x11" Crates)	Temperature Range	Voltage	R290 Charge Size	Amps	HP
69K-143	34 x 30.6 x 42 865 x 777 x 1067	8	4	36° to 38°F 2° to 3° C	115V/60Hz/1	3.17 oz	4	1/4
69K-144	49 x 30.6 x 42 1245 x 777 x 1067	12	8	36° to 38°F 2° to 3° C	115V/60Hz/1	3.17 oz	7.5	1/4
69K-145	58 x 30.6 x 42 1475 x 777 x 1067	16	10	36° to 38°F 2° to 3° C	115V/60Hz/1	3.17 oz	7.5	1/3

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice.

While we exercise good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.