

Specifications

F.O.B Sedalia, Missouri 65301



OPTIONS:

	Folos.	Bottom -	ED
_	raise	DOLLOIII .	- го

- Beaded openings, 12" x 20" -HFST
- Tray shelves - PR-2, PR-3, PR-4
- Fluorescent lights - FL-2, FL-3, FL-4
- Incandescent bullet lights - BI-2, BI-3, BI-4
- Adapter bars - 513, 514, 515, 516
- Legs in lieu of casters
- Body latches
- Tray shelf on end

AGENCY LISTINGS:





DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 314.231.5074 Fax www.dukemfg.com

Ар	proval Stamp(s):					
PROITE QU.	ANTITY: DEL: onoMate™ Buffet Uni	ts -				
ivie	chanically Assisted l	ce Pans				
	DPAH-2M		26" liner			
	D () 54"					
BO	2111111111					
	Heavy gauge paint grip steel Choice of (12) powder coat p		(must choose one)			
	#217107 - Hollyberry Red	_ _ _	#217103 - Natural Almond #217154 - Racing Red #217120 - Sky Blue #217152 - Stone Gray #217113 - Brown Kickplate #217125 - Textured Black			
•	Heavy gauge; 300 Series sta Clear plexiglass canopy, with steel ends to match body		l top der coat steel brackets, powder co			

BASES:

- Choice of
 - Open base 0
 - ☐ Closed base D
- 5" NSF listed black swivel casters, 2 with locks

COLD PAN COMPARTMENT:

- Fully insulated stainless steel pan
- 5" deep liner with 1" brass drain and plug
- Width of liner 19-7/8


REFRIGERATION:

- Copper oils attached to bottom of s/s liner
- Open angle- iron base in compressor compartment
- R134A refrigerant
- On/Off switch
- Six foot cord with plug NEMA 5-15
- Five year warranty on compressor motor

SHORT FORM SPECIFICATIONS:

Duke EconoMate Buffet Units - Mechanically Assisted Ice Pan Units. Body shall be constructed of heavy gauge steel, painted in customer's choice of 12 powder coat paint finishes (see list above). Heavy gauge 300 Series stainless steel top shall be supplied, with easy-to-clean, clear plexiglass canopy. All bases shall be enclosed. Cold pan compartment to be fully insulated and 5" deep. Width of liner shall be 19-7/8". Unit shall be refrigerated by copper coils which are attached to bottom of stainless steel liner. Compressor compartment has open angle-iron base to support air cooled condensing unit of adequate size R134A refrigerant. On/Off switch and cord with plug to be provided. Entire unit shall be factory tested, with five year warranty on compressor motor only. Units shall be mounted on 5" NSF listed swivel casters, two with locks. Canopy adds 12-3/4" to width and 20" to height of units. NOT AVAILABLE IN TABLE TOP MODELS.

Econo Mate




TOP VIEW

EconoMate Buffet Units Mechanically Assisted Ice Pans


□ DPAH-2M Portable 26" liner
□ DPAH-3M Portable 40" liner
□ DPAH-4M Portable 54" liner

NOT AVAILABLE IN TABLE TOP MODELS

LEGEND					
▲ - ELECTRICAL CONNECTION					
• - DRAIN LOCATION					
R134A refrigerant					



FRONT VIEW



SIDE VIEW

DIMENSIONS:			FREIGHT CLASS: 100

	Leng	gth	Wic	dth	Heiç	jht	Liner Dimensions in.		Cube ft.	Weight		
Model	in.	cm	in.	cm.	in.	cm	L	W	D	Crated	lbs.	kg
DPAH-2M	30-3/8	77.2	22-1/2	57.2	33-3/8	84.8	26	19-7/8	5	23.1	244	110.9
DPAH-3M	44-3/8	112.8	22-1/2	57.2	33-3/8	84.8	40	19-7/8	5	32.0	291	132.3
DPAH-4M	58-3/8	148.3	22-1/2	57.2	33-3/8	84.8	54	19-7/8	5	40.9	322	146.4

ELECTRICAL SPECIFICATIONS:

	120 Volt						
Model	HP	Amps	NEMA				
DPAH-2M	1/5	4.2	5-15				
DPAH-3M	1/5	4.2	5-15				
DPAH-4M	1/4	5.2	5-15				



DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 800.231.1130 In Missouri 314.231.5074 Fax www.dukemfg.com