

# **Specifications**

F.O.B St. Louis, Missouri 63102





#### **OPTIONS:**

- ☐ Stainless steel overshelf -1056
- Cross bracing welded to table
- ☐ Casters, swivel, two w/locks, 5" diameter, rubber tires
  - Casters, swivel, two w/locks, 5" diameter, polyurethane tires
- □ Spice bins 201
- Portable ingredient bin 5027
- ☐ 5"H maple riser specify back only or sides and back standard or coved
- ☐ Stainless steel adjustable bullet feet
- ☐ Drawer, standard 185 or 186
- ☐ Drawer, deluxe 176 or 177
- ☐ Tiers of drawers 731 (S/S in & out), 732 (galv in S/S out)

#### **AGENCY LISTING:**



DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 314.231.1130 In Missouri 314.231.5074 Fax www.dukemfg.com

Approval	Stamp(s):	
PRODUCT II PROJECT:	NFORMATION:	

MODEL:

### **Duke Worktables - Maple Top Tables**

	7121A	Galvanized undershelf/galvanized legs/plastic feet
--	-------	--

- ☐ 7122A Stainless steel undershelf/stainless steel legs & feet
- ☐ 7123 Galvanized tubular bracing/galvanized legs/plastic feet
- ☐ 7124 Stainless steel tubular bracing/stainless steel legs & feet

#### TOP:

■ 1-3/4" thick laminated edge-grained hard maple

#### **ADJUSTABLE UNDERSHELF:**

- Heavy gauge galvanized or stainless steel, as specified
- Die-formed corners
- Set screws to lock in place

#### LEGS:

- Galvanized leg sockets
- Non-marking, non-corrosive, adjustable plastic bullet feet for galvanized legs
- ☐ Stainless steel feet for stainless steel legs
- 1-5/8" diameter, S/S or galvanized tubular legs

#### **CROSS BRACING:**

- □ 1-5/8" stainless steel or galvanized steel tubing
- 10" from floor
- Attached with slotless, contour-head bolts





# SHORT FORM SPECIFICATIONS:

**Duke Worktables** - Maple Top Tables. Top shall be constructed of 1-3/4" thick laminated edge-grained hard maple. Adjustable undershelf to be or heavy gauge galvanized or stainless steel with aluminum die-cast corners to provide tight sanitary contact with legs. Locks in place with set screws at any height. If adjusted to less than 6" from floor, tables will not be NSF approved. Bracing can be ordered welded integrally to table. Legs shall have heavy gauge galvanized leg sockets screwed securely to underside of top and designed to provide maximum rigidity to 1-5/8" diameter, heavy gauge galvanized legs fitted with adjustable plastic bullet feet or stainless steel tubular legs fitted with adjustable stainless steel feet. As option, legs may be fitted with stainless steel feet. Tables 96" or longer to have 6 legs. Also available mounted on NSF approved 5" diameter swivel casters, two with locks, in lieu of adjustable feet. Shipped knocked down for quick, easy assembly.

SS-DM-00218-AW-07

# **Terohot**






## **DUKE WORKTABLES MAPLE TOP TABLES**

7121A Galvanized undershelf/galvanized legs/plastic feet 7122A Stainless steel undershelf/stainless steel legs & feet 7123 Galvanized tubular bracing/galvanized legs/plastic feet 7124 Stainless steel tubular bracing/stainless steel legs & feet

**NOTE:** To order tables, add numbers in top widths and top lengths columns to model number for specific table sizes.

EXAMPLE: 8121A-2436 for 24" wide x 36" long 7121A table



#### **DIMENSIONS:**

Maple Top Tables with Adjustable Undershelf - Height: 36" (91.4 cm)  Freight Class: 55										t Class: 55
Model	Top Width		Cube Feet Crated							
iviodei	in.	cm	36"/91.4 cm	48"/121.9 cm	60"/152.4 cm	72"/182.9 cm	84"/213.4 cm	96"/243.8 cm	108"/274.3 cm	120"/304.8 cm
<b>7121A</b> Galv. Undershelf Galv Legs	24	61.0	21.8	28.6	35.5	42.4	49.2	56.1	61.0	69.8
	30	76.2	26.8	35.2	43.7	52.1	60.6	69.0	77.5	86.0
	36	91.4	31.8	33.5	51.9	61.9	72.0	82.0	92.0	102.1
7122A	24	61.0	21.8	28.6	35.5	42.4	49.2	56.1	63.0	69.8
S/S Undershelf S/S Legs	30	76.2	26.8	35.2	43.7	52.1	60.6	69.0	77.5	86.0
	36	91.4	31.8	33.5	51.9	61.9	72.0	82.0	92.0	102.1

Maple Top Tables with Tubular Base - Height: 36" (91.4 cm)

Mandal	Top Width		Cube Feet Crated							
Model	in.	cm	36"/91.4 cm	48"/121.9 cm	60"/152.4 cm	72"/182.9 cm	84"/213.4 cm	96"/243.8 cm	108"/274.3 cm	120"/304.8 cm
<b>7123</b> Galv. Tubular Bracing Galv Legs	24	61.0	21.8	28.6	35.5	42.4	49.2	56.1	61.0	69.8
	30	76.2	26.8	35.2	43.7	52.1	60.6	69.0	77.5	86.0
daiv Legs	36	91.4	31.8	33.5	51.9	61.9	72.0	82.0	92.0	102.1
7124	24	61.0	21.8	28.6	35.5	42.4	49.2	56.1	63.0	69.8
S/S Tubular Bracing S/S Legs	30	76.2	26.8	35.2	43.7	52.1	60.6	69.0	77.5	86.0
	36	91.4	31.8	33.5	51.9	61.9	72.0	82.0	92.0	102.1



**DUKE MANUFACTURING CO.** 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 800.231.1130 In Missouri 314.231.5074 Fax www.dukemfg.com