

# S-150 • S-200 • S-250 Servend<sup>®</sup> Ice Dispensers



S-250 with water valve



S-200



S-150 with water valve

Servend's S-Series ice dispensers feature a no-hassle one-piece structural base, strengthened drive train, and modular design, all resulting in a more durable ice dispenser.

- Servend's patented paddle wheel ice dispense technology maximizes counter space.
- Use with Multiplex remote refrigeration unit with optional beverage valves.
- One-piece ABS base provides a solid foundation as well as adding structural rigidity to the dispenser.
- Enhanced agitation and drive system provides consistent ice dispense and ease of serviceability.
- Patented Rocking Chute™ simplifies ice dispensing and storage.
- Surround View™ merchandiser with attractive "ice" graphics draws customer attention.



ISO 9001:2000  
Quality System Certified

**Leader in Ice & Beverage Dispensers**

Countertop Ice/Bev • Drop-in • Countertop Electric  
Undercounter • Beverage Towers • Ice Chests

**Manitowoc**

# S-150 • S-200 • S-250 Ice Dispensers


## Specifications

	S-150	S-200	S-250
<b>Standard Features</b>	Lighted merchandiser, Ice graphics, leg kit, and drain kit.		
<b>Approx. Shipping Weights</b>	185.12 lbs. / 69.09 kgs.	235 lbs. / 107 kgs.	260 lbs. / 152 kgs.
<b>Countertop Weight (w/o ice)</b>	133.12 lbs. / 60.38 kgs.	184 lbs. / 69 kgs.	204 lbs. / 118 kgs.
<b>Ice Storage Capacity</b>	Up to 150 lbs. / 68 kgs.	Up to 200 lbs. / 91 kgs.	Up to 250 lbs. / 114 kgs.
<b>Electrical Requirements</b>	Dispenser: 120V/60Hz/2.8FLA. 220V/50Hz/1 also available.		
<b>Drain</b>	Single 0.75" (1.91 cm) PVC (N.P.T.) drain fitting extends from drain pan. Units can be drained from the bottom or back of unit.		
<b>Ice Machine Compatibility</b>	Manual fill or top-mount with compatible ice machines. Contact MBE for adapter kit requirements for top-mounted ice machine applications.		
<b>Options</b>	Flomatic water valve. Side splash panels. Flomatic 424 and 464 beverage valves, available in sanitary lever, push button, portion control and autofill valve. Other valves available, contact MBE for details.		

Unit	Width	Depth	Height
S-150	23.00"	31.13"	34.88"
	58.42 cm	79.07 cm	88.6 cm
S-200	30.00"	31.13"	34.88"
	76.2 cm	79.07 cm	88.6 cm
S-250	30.00"	31.13"	40.88"
	76.2 cm	79.07 cm	103.8 cm

\*Height dimension without full lid.  
Add .50" (1.27 cm) for full lid.

3769A ©2019 Servend 4109 Continuing product improvement may necessitate change of specifications without notice.



*We are committed to protecting the environment and its resources. For up-to-date product data always view an electronic version on our web site.*



MANITOWOC BEVERAGE  
2100 Future Drive  
Sellersburg, IN 47172, USA  
Ph: 812-246-7000 • Fax: 812-246-7024  
Visit us online at [www.manitowocbeverage.com](http://www.manitowocbeverage.com)

