



# ROYAL SERIES PLUMBING ANGLED SPRAY HEAD

MODEL: \_\_\_\_\_ PROJECT: \_\_\_\_\_ ITEM #: \_\_\_\_\_ QTY: \_\_\_\_\_

## PRODUCT IMAGE



21-131L SHOWN

**21-131L ONLY AVAILABLE IN  
LOW LEAD COMPLIANT MODEL**

## STANDARD FEATURES

- Complies with EPA Act 2005
- Reinforced spray head
- Button valve repair kit available (21-302L)
- Replacement bumper available (21-142)
- Replacement spray face available (21-145)
- **Low Lead Compliance**  
Meets California AB-1953 and Vermont S152 standards

## SPECIFICATIONS

- Flow rate: 1.6 GPM @ 60 PSI
- Temperature Range: 40°F to 180°F
- Shipping weight: 2 lbs.

## AVAILABLE REPLACEMENT PARTS


21-302L



21-142



21-145



**CERTIFICATIONS:**

**APPROVED BY:**

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Printed in the USA

**Krowne Metal Corporation**

100 Haul Rd. Wayne, NJ 07470 • Toll Free: (800) 631-0442 • Fax: (973) 872-1129  
sales@krowne.com • www.krowne.com • www.facebook.com/KrowneMetal • www.twitter.com/KrowneMetal

Rev. 09/2011  
No. 21-131L