



Model: **16-650** Item #: \_\_\_\_\_ Date: \_\_\_\_\_  
 Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

**Electronic Sensor Faucet** Single Hole Deck Mount with 6" Gooseneck Spout

**Royal Series**



**DESCRIPTION**

- Battery Powered Electronic Sensor Faucet with Control Module, Mechanical Mixing Valve, Supply Hoses & Mounting Hardware. Polished Chrome Finish, 6" Gooseneck Spout, 1.5 GPM Female Threaded Aerator Installed

**STANDARD FEATURES**

- Single Hole Deck Mount
- Infrared Sensor Operated
- Battery Powered Control Module, (4) AA Batteries Included, AC Adapter Optional
- Built-In Filter to Prevent Debris from Entering Solenoid Valve
- Low Battery Indicator Light
- Battery Life 1-3 Years Based on Usage
- Warranty: 3 Years

**PRODUCT COMPLIANCE**

- ASME A112.18.1-2011/CSA B125.1-11
- NSF-61
- NSF/ANSI 372
- Meets ANSI A117.1 (ADA)
- CEC Listed
- Massachusetts Approved



**SPECIFICATIONS**

Water Inlet	1/4" Male NPS
Temp. Range	40°F - 180°F
Water Pressure	20 -120 PSI
Sensor Type	Infrared
Flow Rate	1.5 GPM
Default Time Out	30 seconds
Default GPC	0.75
Default Shut-Off Delay	1 Second
Default Auto Flush	Off
Sensor Range	3/4" - 8-1/4"
Battery Life	500,000 cycles
Material	Solid Brass
Finish	Polished Chrome
Weight	8 lbs.


**WARNING:** Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes. California Proposition 65 Warning



Model: **16-650** Item #: \_\_\_\_\_ Date: \_\_\_\_\_  
 Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

**Electronic Sensor Faucet** Single Hole Deck Mount with 6" Gooseneck Spout

**Royal Series**



No.	Replacement Parts	Model
1	Convex Sensor with Cable	16-506
2	Spout Supply Hose	16-511
3	Control Module	16-198
4	Mechanical Mixing Valve	16-402L
5	Water Supply Hoses	16-510
6	Optional AC Adapter	16-199

Flow Control	Setting								
Shut-Off Delay	1s	10s	15s						
Auto Flush	ON				OFF				
Auto Time Out	15s	20s	25s	30s	45s	1m	2m	10m	

Default Flow Control Setting Highlighted in Gray

