

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | | |
|-----------------|------|--|
| Model #: | | |
| Item #: | Qty: | |
| Available W/H : | | |
| Approval : | | |

Undercounter Freezer

Undercounters Super Deluxe Series

Model: TUF-28SD

3 YEAR PARTS & LABOR WARRANTY



___ FEATURES & BENEFITS =__

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

■ LED interior lighting system

Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing less heat, while maximizing the visibility.

Left hinged model available

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Efficient refrigeration system

Turbo Air's solid door freezers are designed with oversized and balanced (CFC Free R-134A, R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ Freezer holds 0°F ~ -10°F for the best in frozen food preservation

ENERGY STAR®
Qualified













| | | | | | | Intertek | |
|----------|---------------|---------|----------------|-----|------|-------------------------|---------------------------------|
| Model | Swing Door | CU./FT. | #of Shelves | НР | AMPS | Crated Weight (lbs.) | L x D*x H [†] (inches) |
| TUF-28SD | 1 | 7 | 1 | 1/3 | 5.3 | 163 | 271/2 x 30 x 305/8 |

(unit: inch)

Model: TUF-28SD

| ELECTRICAL DATA | | | | | |
|--------------------------|---------------|--|--|--|--|
| Voltage | 115/60/1 | | | | |
| Plug Type | ① NEMA 5-15P | | | | |
| Full Load Amperes | 5.3 | | | | |
| Compressor HP | 1/3 | | | | |
| Cord Length ft. | 9 | | | | |
| Refrigerant | R-134A | | | | |
| DIMENSIONAL DATA | | | | | |
| Net Capacity cu. ft. | 7 | | | | |
| Ext. Length Overall in. | 271/2 (699mm) | | | | |
| Ext. Depth Overall in.* | 30 (762mm) | | | | |
| Ext. Height Overall in.† | 305/8 (777mm) | | | | |
| # of Doors | 1 | | | | |
| # of Shelves | 1 | | | | |
| Net Weight lbs. | 146 | | | | |
| Gross Weight lbs. | 163 | | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Legs available for all models (optional)
- Door locks available (optional)
- External digital thermometer available (optional)
- 2.5" dia. casters available (optional) ½" diameter & 13 TPI

■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional stainless steel shelves
- ☐ Additional PE coated wire shelves

PLAN VIEW





SIDE VIEW

Ver.201501













ENERGY STAR® Qualified

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519











^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.