

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model # :		
WOGGI π .		
Item #:	Qty:	
Available W/H :		
Approval :		

Undercounter Refrigerator

Undercounters Super Deluxe Series

Model: TUR-60SD

3 YEAR PARTS & LABOR WARRANTY



___ FEATURES & BENEFITS =__

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

■ Efficient refrigeration system

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ Refrigerator holds 33°F ~ 38°F for the best in food preservation













Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TUR-60SD	2	16	2	1/3	8.9	282	601/4 x 30 x 305/8

(unit: inch)

Undercounter Refrigerator

Model: TUR-60SD

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	8.9				
Compressor HP	1/3				
Cord Length ft.	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Net Capacity cu. ft.	16				
Ext. Length Overall in.	601/4 (1530mm)				
Ext. Depth Overall in.*	30 (762mm)				
Ext. Height Overall in.†	305/8 (777mm)				
# of Doors	2				
# of Shelves	2				
Net Weight lbs.	243				
Gross Weight lbs.	282				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Legs available for all models (optional)
- Stainless steel double overshelf available (optional)
- Door locks available (optional)
- External digital thermometer available (optional)
- 2.5" dia. casters available (optional) ½" diameter & 13 TPI

■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional stainless steel shelves
- ☐ Additional PE coated wire shelves
- ☐ Stainless steel double over-shelf

PLAN VIEW





SIDE VIEW

Ver.201501


























^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.