

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

Sandwich / Salad Unit

Food Prep Tables
M3 Series

Model: MST-60

3 YEAR PARTS & LABOR WARRANTY



= FEATURES & BENEFITS =__

Cold air compartment

Our innovative "Cold Air Compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Stainless steel cabinet construction

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

Convenient cutting board side rail

Our cutting board is 9-1/2" deep and 1/2" thick to provide ample working space, and is made of easy to use and sanitize LDPE (Low Density Polyethylene). The new side rail cutting board bracket makes it easy to secure and remove the cutting board and it accepts different sizes too (max. 1/2" thickness)

Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

Adjustable, heavy duty, PE (polyethylene) coated wire shelves

Efficient refrigeration system

Turbo Air's M3 solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ Refrigerator holds 33°F ~ 39°F for the best in food preservation









_		jittel tek								
	Model	Swing Door	CU./FT.	#of Shelves	#of Pans	#of Hood	HP	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
	MST-60	2	16	2	16	1	1/3	8.9	330	601/4 x 30 x 37

(unit: inch)

Sandwich / Salad Unit

Model: MST-60

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	8.9				
Compressor HP	1/3				
Cord Length ft.	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Ext. Length Overall in.	60 _{1/4} (1530mm)				
Ext. Depth Overall in.*	30 (762mm)				
Ext. Height Overall in.†	37 (940mm)				
# of Doors	2				
# of Shelves	2				
# of Pans	16				
Net Capacity cu. ft.	16				
Net Weight lbs.	308				
Gross Weight lbs.	330				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty **Additional 2 Year Warranty on Compressor**

- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 91/2" deep, ½" thick cutting board included
- Stainless steel double overshelf available (optional)
- Door locks available (optional)
- External digital thermometer available (optional)
- 2.5" dia. casters available (optional) ½" diameter & 13 TPI
- Legs available for all models (optional)


■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional stainless steel shelves
- □ Additional PE coated wire shelves
- ☐ Stainless steel double over-shelf

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201501





















■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002

^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.