

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | | |
|-----------------|------|--|
| Model #: | | |
| Item #: | Qty: | |
| Available W/H : | | |
| Approval : | | |

Undercounter Refrigerator - Drawers

Undercounters Super Deluxe Series

Model: TUR-48SD-D4

3 YEAR PARTS & LABOR WARRANTY

- Each drawer accomodates up to 6" deep sixth (1/6) size pans (drawer pans not included)

___ FEATURES & BENEFITS =__

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

Durable stainless steel drawers Drawers are easy to clean and assemble.

Efficient refrigeration system

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Ergonomically designed doors & drawers

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Refrigerator holds 33°F ~ 38°F for the best in food preservation











| | merek | | | | | | |
|-------------|---------------|---------|----------------|-----|------|-------------------------|---------------------------------|
| Model | Swing Door | CU./FT. | #of Shelves | НР | AMPS | Crated Weight (lbs.) | L x D*x H [†] (inches) |
| TUR-48SD-D4 | - | 12 | - | 1/3 | 6.5 | 260 | 481/4 x 30 x 305/8 |

(unit: inch)

Model: TUR-48SD-D4

| ELECTRICAL DATA | | | | | |
|--------------------------|---------------------------|--|--|--|--|
| Voltage | 115/60/1 | | | | |
| Plug Type | | | | | |
| Full Load Amperes | 6.5 | | | | |
| Compressor HP | 1/3 | | | | |
| Cord Length ft. | 9 | | | | |
| Refrigerant | R-134A | | | | |
| DIMENSIONAL DATA | | | | | |
| Net Capacity cu. ft. | 12 | | | | |
| Ext. Length Overall in. | 481/4 (1226mm) | | | | |
| Ext. Depth Overall in.* | 30 (762mm) | | | | |
| Ext. Height Overall in.† | 30 _{5/8} (777mm) | | | | |
| # of Doors | - | | | | |
| # of Shelves | - | | | | |
| Net Weight lbs. | 238 | | | | |
| Gross Weight lbs. | 260 | | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Legs available for all models (optional)
- Stainless steel double overshelf available (optional)
- Door locks available (optional)
- External digital thermometer available (optional)
- 2.5" dia. casters available (optional) ½" diameter & 13 TPI


■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201501


























^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.