

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project :       |      |
|-----------------|------|
| Model #:        |      |
| Item #:         | Qty: |
| Available W/H : |      |
| Approval :      |      |

# Undercounter Refrigerator - Low Boy

Undercounters M3 Series

**Model: MUR-36L** 

3 YEAR PARTS & LABOR WARRANTY



# \_\_\_ FEATURES & BENEFITS =\_\_

### Stainless steel cabinet construction

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

## ■ Efficient refrigeration system

M3's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

## ■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Adjustable, heavy duty, PE (polyethylene) coated wire shelves

## Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

# ■ Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

 Refrigerator holds 33°F ~ 38°F for the best in food preservation











| Model   | Swing<br>Door | CU./FT. | #of<br>Shelves | НР  | AMPS | Crated<br>Weight (lbs.) | L x D*x H <sup>†</sup> (inches) |
|---------|---------------|---------|----------------|-----|------|-------------------------|---------------------------------|
| MUR-36L | 2             | 7.5     | 2              | 1/5 | 3    | 187                     | 361/4 x 30 x 27                 |

(unit: inch)

# Model: MUR-36L

| ELECTRICAL DATA          |               |  |  |  |
|--------------------------|---------------|--|--|--|
| Voltage                  | 115/60/1      |  |  |  |
| Plug Type                | ① NEMA 5-15P  |  |  |  |
| Full Load Amperes        | 3             |  |  |  |
| Compressor HP            | 1/5           |  |  |  |
| Cord Length ft.          | 9             |  |  |  |
| Refrigerant              | R-134A        |  |  |  |
| DIMENSIONAL DATA         |               |  |  |  |
| Net Capacity cu. ft.     | 7.5           |  |  |  |
| Ext. Length Overall in.  | 361/4 (921mm) |  |  |  |
| Ext. Depth Overall in.*  | 30 (762mm)    |  |  |  |
| Ext. Height Overall in.† | 27 (686mm)    |  |  |  |
| # of Doors               | 2             |  |  |  |
| # of Shelves             | 2             |  |  |  |
| Net Weight lbs.          | 160           |  |  |  |
| Gross Weight lbs.        | 187           |  |  |  |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


## 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor **WARRANTY:**

- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Legs available for all models (optional)
- Stainless steel double overshelf available (optional)
- Door locks available (optional)
- External digital thermometer available (optional)
- 2.5" dia. casters available (optional) 1/2" diameter & 13 TPI


#### ■ OPTIONAL ACCESSORIES:

- ☐ 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs
- Additional stainless steel shelves
- ☐ Additional PE coated wire shelves
- □ Back splash guard


# **PLAN VIEW**



#### **PLAN VIEW**



**FRONT VIEW** 



Ver.201501














■ Warranty: 800-381-7770 ■ AC: 888-900-1002









<sup>\*</sup> Depth does not include 1" for rear spacers.

<sup>†</sup> Height does not include 5-1/8" for caster height.