

PROJECT:		
ITEM #		_ QTY:
MODEL#		
AIA #	SIS #	

VICTORY ELITE™ TOP MOUNT REFRIGERATOR

VERSA-3D-SD-HC



CABINET CONSTRUCTION

- Stainless Steel Front, Aluminum Interior
- Snap-in, Magnetic Door Gaskets With A 2 Year Warranty
- · Heavy Duty Cam Lift Hinges With Lifetime Warranty
- · Stay-Open Door Feature For Easy Product Loading
- Required Clearance Is 12" Top, 3" Rear And 0" Sides
- Field Reversible Doors
- 6" Casters
- 8' Cord and Plug

FEATURES

· High Performance Refrigeration System With An Electronic Control

VICTORY ELITET TOP MOUNT REFRIGERATOR

- · Expansion Valve Technology
- Variable Speed Compressor Technology
- · Energy Efficient LED Lighting
- · Heavy Duty Epoxy Coated Shelves

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All **Environmental Concerns**
- Hot Gas Condensate Evaporator
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Refrigerator Capable Of Maintaining Product Temperature Between 36°F And 38°F



Please verify qualifying units by visiting: www.energystar.gov/cfs



- 3 Year Parts & Labor Warranty Plus An Additional 4 Year Compressor Warranty
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (Parts Only)

OPTIONS & ACCESSORIES

- · Stainless Steel Back
- · Stainless Steel Breaker
- Stainless Steel Exterior
- 6" Legs Or 3" Casters · Stainless Steel Interior (No charge at time of unit order)

Tray Slides

- · Seismic/Flanged Legs
- · Additional Shelves: Heavy Duty Epoxy Coated Chrome Plated Or Stainless Steel
- Remote Models* (6" Legs Only) (Refrigerant must be specified at time of order, see note on back page)

3779 Champion Blvd, Winston-Salem, NC 27105


ph: (888) 845-9800 | fax: (800) 253-5168


Rev. 3/23/20 Printed in U.S.A.

APPROVAL: _ _ DATE: _



VERSA-3D-SD-HC





We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" Top and 3" rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	71.52	Cabinet Voltage	115/60/1	Height	88"
Width, Overall (in.)	78"	Total Amperes	6.0	Width	80"
Depth, Overall (With Handle)	33 7/8"	NEMA Plug* (8' cord)	5-15P	Depth	36"
Height Overall (6" Casters)	84 3/4"	REFRIGERATION DATA		Crated Weight	720 lbs
Depth, Door Open 90°	55 1/8"	Condensing Unit Size, HP*	Variable Speed Technology	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified	
Door Opening (in.)	21 5/8" x 61 3/4"	Refrigerant*	R290		
		i e	i e		

Variable Speed Technology

at time of order.

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168 Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Capacity (BTU/HR) (100°F/20°F)

Rev. 3/23/20 Printed in U.S.A.

No. Of Doors/Shelves

