

SEALED WELL ELECTRIC TABLES WITH UNDERSHELF



SW-3E-240 Shown

FEATURES:

Stainless steel body, top and legs Stainless steel undershelf Fiberglass insulation between each compartment Drains with gate valves per well Stainless steel shelf with removable 3/8" thick poly cutting board - Ships K.D.



Sealed Well with Drain

ltem #:	Qty #:
Model #:	
Project #:	



Featuring as Standard: "THE PROVEN" ORIGINAL ADVANCE TABCO Adjustable Undershelf with Die Cast Leg Clamp

MATERIAL:

TOP: 20 gauge #302 stainless steel with die stamped pan openings. (11.875" x 20.062") **BODY:** 22 gauge #430 stainless steel **LEGS:** 1 5/8" diameter tubular stainless steel 1" adjustable plastic bullet feet Stainless steel gussets

UNDERSHELF: 20 gauge, #430 stainless steel **LINERS:** 20 Gauge stainless steel deep drawn with drain

CUTTING BOARD: White Thermoplastic **CUTTING BOARD BRACKETS:** 16 gauge, #302 stainless steel

ELECTRICAL:

120V units yield 640 Watts 208V/240V dual voltage units yield 825 Watts at 208V and 1100 Watts at 240V 6' electrical cord with plug Infinite control knobs Indicator lights



Model #	Length	# of Wells	Volts	Amps	Watts	NEMA Plug	Wt.	Cu. Ft.
SW-2E-120	A = 31-13/16"	2	120	10.67	1280	5-20P	92 lbs.	28
SW-3E-120	B = 47-1/8"	3	120	16	1920	5-20P	135 lbs.	41.32
SW-4E-120	C = 62-7/16"	4	120	21.33	2560	L5-30P	230 lbs.	54.55
SW-2E-240	A = 31-13/16"	2	208/240	7.94/9.16	1650/2200	6-20P	92 lbs.	28
SW-3E-240	B = 47-1/8"	3	208/240	11.91/13.74	2475/3300	6-20P	135 lbs.	41.32
SW-4E-240	C = 62-7/16"	4	208/240	15.88/18.32	3300/4400	L6-30P	230 lbs.	54.55
SW-5E-240	D = 77-3/4"	5	208/240	19.85/22.90	4125/5500	L6-30P	270 lbs.	66.94

NOTE: Units are not designed to cook or heat frozen or refrigerated foods. Food placed in tables should already be hot, and the table will maintain the proper temperatures

NEMA PLUGS: Your plug will look like this...





Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders: Email: customer@advancetabco.com or Fax To: 631-242-6900 For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax To: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL ± .125"

ALL DIMENSIONS ARE TYPICAL



