

## STAINLESS STEEL

# **EQUIPMENT FILLER TABLE**





ltem #:	Qty #:
Model #: _	
Project #:	

#### **FEATURES:**

TOP is furnished with 1 5/8" sanitary rolled rim edge in front. Square edges on sides and 1/1/2" splash of single metal thickness on rear.

Hat channels stud welded to top which reinforces and maintains a level working surface.

Welded Front to Back Leg Assembly.

Rear (Left to Right) Stretcher bolts to side leg assemblies.

Aluminum die cast "leg-to-shelf" clamp secures shelf to leg eliminating unsightly nuts and bolts. Undershelf is fully adjustable.

#### **CONSTRUCTION:**

All TIG welded. Exposed weld areas polished to match adjacent surfaces.

Entire top mechanically polished to a satin finish.

Top is sound deadened.

Roll formed embossed galvanized hat channels are secured to top by means of structural adhesive and weld studs.

Gussets welded to support hat sections.

#### **MATERIAL:**

**TOP:** 16 gauge stainless steel type "304" series.

SHELF: 16 gauge stainless steel type "304" series.

**STRETCHERS:** 1 5/8" diameter tubular stainless steel.

LEGS: 1 5/8" diameter tubular stainless steel.

Stainless steel gussets.

1" stainless steel bullet feet.

#### **OPEN BASE**

Model	W	L	Wt.	Cu. Ft.
TFMS-182	18"	24"	23 lbs.	2
TFMS-180		30"	25 lbs.	3
TFMS-183		36"	32 lbs.	3
TFMS-152		24"	22 lbs.	2
TFMS-150	15"	30"	24 lbs.	3
TFMS-153		36"	31 lbs.	3
TFMS-122		24"	21 lbs.	2
TFMS-120	12"	30"	22 lbs.	3
TFMS-123		36"	29 lbs.	3

### W/ ADJ. UNDERSHELF

Model	W	L	Wt.	Cu. Ft.
TFMSU-182	18"	24"	29 lbs.	2
TFMSU-180		30"	33 lbs.	2
TFMSU-152	15"	24"	24 lbs.	2
TFMSU-150		30"	29 lbs.	2



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:


Email: customer@advancetabco.com or Fax: 631-242-6900


For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

TOL ± .500" ALL DIMENSIONS ARE TYPICAL







# TFMSU Series w/ Adjustable Undershelf

