

Camshelving® Premium Series

Stationary - Starter Units

5 Shelf Units, Vented Shelf Plates only with Camguard™ antimicrobial

2 Post Heights

64" (162,6 cm) and 72" (182,9 cm)

3 Shelf Depth

18" (45,7 cm), 21" (53,3) and 24" (61 cm)

5 Shelf Lengths

36", 42", 48", 54", 60" (91,4 cm, 106,7 cm, 121,9 cm, 137,2cm, 152,4 cm)

• Starter Unit includes:

- Two Pre-Assembled Post Kits.
- Five Vented Shelf Kits.



Features & Benefits

Versatile Storage

For use in any environment, indoors or outdoors, including walk-in coolers and freezers, dry storage, wet areas or front of the house display. Works in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C). Weldless and rust free.

Fits in Any Space

Units combine together in straight lines by sharing posts of existing units. Corner Connectors, made of reinforced nylon, connect units together in and stability. Simplify assembly and reduce costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

Easy to Clean

Camshelving Shelf Plates contain Camguard an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing. The traverses and post kits are smooth polypropylene so they can be wiped or steam cleaned. The traverses can be easily removed and washed in a conveyor dishwasher.

Easy to Assemble

Assembles in minutes with the use of a rubber mallet. Requires no bolts or nuts, clips or stainless steel connectors. Molded in dovetails on Posts ensure that Traverses set easily into place.

Strong as Steel

Posts and Traverses are made of a steel core coated with polypropylene. Uniquely engineered Post Connectors offer exceptional cross stabilization. Shelves up to 48" (121,9 cm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" - 72" (137,2 - 182,9 cm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold 400 lbs. (182 kg) for any length traverse.

Easy to Adjust

Requires use of rubber mallet. Shelves can be adjusted at 4" (10,2 cm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Sturdy reinforced nylon foot on bottom of each stationary Post adjusts easily for floor irregularities.

Optional Accessories

Includes Wall Fastener and Seismic Foot. Each are packed 4 per case. Identification Tags clip easily onto traverses. Dunnage stand recommended for heavy usage with shelves 54" (137,2 cm) or longer. Increases capacity of bottom shelf to 1,000 lbs. (450 kg).

Item No. _____


Specifier Identification No. _____

Code No. _____


Quantity _____



Five Shelf Starter Unit consists of two Post Kits and five Vented Shelf Kits.



Dunnage Stand



Set of Left and Right Corner Connectors (1 set required per shelf).

Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Tray Slide Rack, Shelf Rails, Divider Bars, and High Density Track and Extension Kits are not NSF Listed.

Camshelving® Premium Series

Stationary - Starter Units 5 Shelf Units, Vented Shelf Plates only

Item No. _____

Specifier Identification No. _____

Code No. _____

Quantity _____

Five shelf Starter Units

67" (170,2 cm) Height

18" (45,7 cm) Depth

Code	traverse		case lbs. (cube)	case kg. (cube m³)
	in.	cm		
CPU183664V5	36"	91,4	88.80 (5.90)	40,28 (0,1671)
CPU184264V5	42"	106,7	99.70 (5.90)	45,22 (0,1671)
CPU184864V5	48"	121,9	106.30 (5.90)	48,21 (0,1671)
CPU185464V5	54"	137,2	117.20 (5.90)	53,16 (0,1671)
CPU186064V5	60"	152,4	125.60 (5.90)	56,97 (0,1671)

21" (53,3 cm) Depth

Code	traverse		case lbs. (cube)	case kg. (cube m³)
	in.	cm		
CPU213664V5	36"	91,4	95.60 (7.17)	43,36 (0,2030)
CPU214264V5	42"	106,7	108.35 (7.17)	49,15 (0,2030)
CPU214864V5	48"	121,9	115.65 (7.17)	52,46 (0,2030)
CPU215464V5	54"	137,2	128.45 (7.17)	58,26 (0,2030)
CPU216064V5	60"	152,4	138.50 (7.17)	62,82 (0,2030)

24" (61 cm) Depth

Code	traverse		case lbs. (cube)	case kg. (cube m³)
	in.	cm		
CPU243664V5	36"	91,4	98.55 (8.50)	44,70 (0,2407)
CPU244264V5	42"	106,7	109.55 (8.50)	49,69 (0,2407)
CPU244864V5	48"	121,9	120.50 (8.50)	54,66 (0,2407)
CPU245464V5	54"	137,2	131.50 (8.50)	60,00 (0,2407)
CPU246064V5	60"	152,4	139.60 (8.50)	63,32 (0,2407)

Five shelf Starter Units

72" (182,9 cm) Height

18" (45,7 cm) Depth

Code	traverse		case lbs. (cube)	case kg. (cube m³)
	in.	cm		
CPU183672V5	36"	91,4	90.90 (5.90)	41,23 (0,1671)
CPU184272V5	42"	106,7	101.80 (5.90)	46,17 (0,1671)
CPU184872V5	48"	121,9	108.40 (5.90)	49,17 (0,1671)
CPU185472V5	54"	137,2	120.70 (5.90)	55,00 (0,1671)
CPU186072V5	60"	152,4	127.70 (5.90)	57,92 (0,1671)

21" (53,3 cm) Depth

Code	traverse		case lbs. (cube)	case kg. (cube m³)
	in.	cm		
CPU213672V5	36"	91,4	99.10 (7.17)	44,95 (0,2030)
CPU214272V5	42"	106,7	111.85 (7.17)	50,74 (0,2030)
CPU214872V5	48"	121,9	119.15 (7.17)	54,05 (0,2030)
CPU215472V5	54"	137,2	131.95 (7.17)	59,85 (0,2030)
CPU216072V5	60"	152,4	142.00 (7.17)	64,41 (0,2030)

24" (61 cm) Depth

Code	traverse		case lbs. (cube)	case kg. (cube m³)
	in.	cm		
CPU243672V5	36"	91,4	102.05 (8.50)	46,49 (0,2407)
CPU244272V5	42"	106,7	113.05 (8.50)	51,28 (0,2407)
CPU244872V5	48"	121,9	118.00 (8.50)	56,25 (0,2407)
CPU245472V5	54"	137,2	124.00 (8.50)	62,50 (0,2407)
CPU246072V5	60"	152,4	143.10 (8.50)	64,91 (0,2407)

Corner Connector Set

Case Pack: 1 set

code	description	case lbs. (cube)	case kg. (cube m³)
CPCC1	Right and Left	0.76 (0.05)	0,34 (0,0014)

Architect Specs

Posts:	Internal steel core, reinforced polypropylene exterior.
Post Connectors:	Reinforced polypropylene.
Traverses:	Internal steel core, reinforced polypropylene exterior.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard™ antimicrobial.
Corner Connectors:	Reinforced nylon.
Adjustable Foot:	Reinforced nylon.
Seismic Foot:	Stainless steel post and wide foot plate, 3 holes for bolts. (Bolts not provided)
Wall Fastener:	Stainless steel.

Dunnage Stands

Case Pack: 1

7½" (19 cm) Height from Floor to Bottom of Traverse

code	depth	case lbs. (cube)	case kg. (cube m³)
CPDS18H6	18"	2.90 (0.22)	1,30 (0,0062)
CPDS21H6	21"	3.10 (0.26)	1,40 (0,0074)
CPDS24H6	24"	3.30 (0.30)	1,50 (0,0085)

Optional Accessories

Seismic Foot (Bolts not provided)	<input type="checkbox"/> CSEQ3	Color: Silver	Case pack: 4 each
Wall Fastener	<input type="checkbox"/> CSWF	Color: Silver	Case pack: 4 each
Identification Tag 6"	<input type="checkbox"/> CSID6	Color: White/Clear	Case pack: 12 each
Identification Tag 3"	<input type="checkbox"/> CSID3	Color: White/Clear	Case pack: 12 each

Standard Colors

Speckled Gray (480)

Approvals



COMPONENT

CAMBRO
www.cambro.com

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, CA 92647-2056, U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service Department 800 833 3003