

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle One, Two, or Three Compartment Sinks, model ______, with 2"-wide "Euro-Style" edging on front and sides. Unit constructed of heavy gauge type 430 stainless steel top and sink bowls. Sinks are deep-drawn, seamless and have all corners coved. Drainboards, when required, are "V" creased for positive drainage. 9½" high backsplash with 1" upturn and tile edge. Legs are 1½" O.D. galvanized tubing, with front-to-back crossbracing, and 1" high impact plastic adjustable bullet feet.



Options / Accessories

- ☐ Stainless steel legs
- ☐ Stainless steel bullet feet
- ☐ White metal bullet feet
- ☐ Lever drains
- ☐ Twist handle drains
- ☐ Twist drain brackets
- □ Faucets
- ☐ Sink covers
- Waste outlet
- □ Sink kits
- Overflow hole

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaqlegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

412 Series Sinks

MODELS:

□ 412-16-1	□ 412-16-2	□ 412-16-3
□ 412-16-1-18	412-16-2-18	□ 412-16-3-18
□ 412-16-1-18*	□ 412-16-2-18*	□ 412-16-3-18
□ 412-16-1-24	□ 412-16-2-24	412-16-3-24
□ 412-16-1-24*	□ <i>412-16-2-24</i> *	□ 412-16-3-24

Materials

- Sink bowls: Heavy gauge type 430 stainless steel.
- Top: Drainboards, backsplash and euro-style edging are heavy gauge type 430 stainless steel.
- Legs: 1%" (41mm)-diameter heavy-gauge galvanized tubing with plated 12-gauge gussets and high-impact corrosion resistant fully adjustable bullet feet.
- Crossbracing, running front-to-back, is 1" (25mm)-diameter heavy-gauge galvanized tubing.

Design and Construction Features

- All bowls have deep-drawn one-piece seamless construction, using state-of-the-art hydraulic presses.
- All sink bowls have a generous radius—3" (76mm) minimum—and are rectangular for maximum capacity.
- 10½" (267mm) water level 13½" (343mm) flood level.
- 44" (1118mm) overall height.
- Entire assembly is fuse-welded and planished, providing a one-piece seamless sink unit.
- Drainboards, when provided, are integrally welded.
- 9½" (241mm)-high full length standard backsplash features 1" (25mm) upturn and tile edge for easy installation and feathering to wall/splash surface.
- Welded areas are blended to match adjacent surfaces with continuity of satin finish.
- Leg gussets are welded to a die-cut heavy gauge reinforcing plate.
- Leg gusset assemblies welded adjacent to sink bowls, providing increased stability and maximum weight support.

Mechanical:

- Faucet holes are 1½" (29mm), punched on 8" (203mm) centers.
- Basket-type waste drains included fit sink bowls' $3\frac{1}{2}$ " (89mm) opening and feature $1\frac{1}{2}$ " (38mm) outlet.

Certifications / Approvals





EG20.03 Rev. 06/16


^{*} See charts on back page for full model numbers.



Item No.:	
Project No.:	
S.I.S. No.:	

412 Series Sinks


Sinks with One Compartment



TOD I	$\mu = \mu = 0$	ONE COL	<i>NPARTMFNT</i>	CINIZO
ILIP	VIEVV UIE	(NPAKIWIFNI	ר אווור.


	BOWL DIMENSIONS				BOWL DIMENSIONS DRAINBOARD					OVER	RALL C	IMENS	IONS	l	
	width length				ler	ngth	wic	ith	leng	jth	wei	ght			
model #	in.	mm	in.	mm	quantity	in.	mm	in.	mm	in.	mm	lbs.	kg		
412-16-1	20″	508	16″	406	0		-	27½″	699	23¼"	591	40	18.1		
412-16-1-18R or L	20″	508	16″	406	1	18″	457	27½"	699	387/8″	987	59	26.8		
412-16-1-18	20″	508	16″	406	2	18″	457	27½"	699	54½″	1384	78	35.4		
412-16-1-24R or L	20″	508	16″	406	1	24"	610	27½"	699	44 ⁷ /8"	1140	65	29.5		
412-16-1-24	20″	508	16″	406	2	24"	610	27½"	699	66½″	1689	90	40.8		

Sinks with Two Compartments



	BOV	VL DIN	/ENS	IONS	DRAIN	OVER	ALL D	I					
	width		width length			length		width		length		weight	
model #	in.	mm	in.	mm	quantity	in.	mm	in.	mm	in.	mm	lbs.	kg
412-16-2	20″	508	16″	406	0		-	27½"	699	41″	1041	64	29.0
412-16-2-18R or L	20″	508	16″	406	1	18″	457	27½"	699	56%"	1438	83	37.6
412-16-2-18	20″	508	16″	406	2	18″	457	27½″	699	721/4"	1835	102	46.3
412-16-2-24R or L	20″	508	16″	406	1	24"	610	27½"	699	62%"	1591	89	40.4
412-16-2-24	20″	508	16″	406	2	24"	610	27½"	699	841/4"	2140	114	51.7

Sinks with Three Compartments



	BOWL DIMENSIONS				DRAIN	OVER	ALL D						
	width		width length			length		width		length		weight	
model #	in.	mm	in.	mm	quantity	in.	mm	in.	mm	in.	mm	lbs.	kg
412-16-3	20″	508	16″	406	0		-	27½"	699	58¾″	1492	85	38.6
412-16-3-18R or L	20″	508	16″	406	1	18″	457	27½"	699	74¾″	1895	104	47.2
412-16-3-18	20″	508	16″	406	2	18″	457	27½″	699	90″	2286	123	55.8
412-16-3-24R or L	20″	508	16″	406	1	24"	610	27½"	699	80%"	2042	110	49.9
412-16-3-24	20″	508	16″	406	2	24"	610	27½″	699	102″	2591	135	61.2

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2016 by Eagle Group Rev. 06/16