


DBSB-18 (Blender not included)

Conforms to ANSI/NSF STD 2



Drainboard **Blender Stations**

DBSA-12, DBSA-14, DBSA-18, DBSA-24, DBSB-12, DBSB-14, DBSB-18

Standard Features

- All stainless steel construction
- One-piece, seamless top and backsplash featuring 1/4" radius corners for easy cleaning
- · CFC free foamed-in-place blender shelf for sound deadening
- Adjustable stainless steel bullet feet
- · Drainboard work surface consists of drain pan with separate removable perforated insert
- Blender shelf features radius interior corners for easy cleaning
- · Power cord access hole with grommet located on front skirt, behind the blender
- Junction box for duplex GFI outlet mounted underneath blender shelf (outlet not included)

NOTE: Blender stations cannot have a speed rail mounted to them. Since speed rails are so common on underbar, blender stations come in 24" and 29" depths to align with underbar that has a speed rail.

To view underbar installation instructions, please visit: http://www.glastender.com/PDF/F-750-165 Underbar Installation Instructions.pdf To view cleaning and care instructions, please visit: http://www.glastender.com/PDF/F-423-011_ss_clean_care.pdf

Specifications

Drain

• 1-1/2" I.P.S. Threaded drain will fit Dearborn part #8033 slipnut and part #W-573P washer.

Legs

- 1-5/8" diameter, 16 gauge stainless steel
- Stainless steel bullet feet

Materials

• 20 gauge stainless steel



Power cord access hole in front skirt, behind blender

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 www.glastender.com	Approval/Notes:
Specifications subject to change without notice. For current specifications please visit our website.	
Printed in USA	Rev. 11-09-15

Dimensional Information

