

PROJECT:		
ITEM #		QTY:
MODEL#		
AIA #	SIS #	

# **BOTTOM MOUNT GLASS DOOR DISPLAY REFRIGERATOR**

## LSR49HC-1



### **CABINET CONSTRUCTION**

- · Stainless Steel Exterior (galvanized back)
- · Aluminum Interior
- · LED Lighting
- · High-Performance, Balanced, Bottom-Mounted Refrigeration
- · Triple-Pane Glass Doors
- Spring-Loaded Hinge With Stay-Open Door Feature For Easy Product Loading
- · One-Piece, Snap-In Magnetic Door Gasket
- · Door Lock Standard
- · Ten (10) Heavy-Duty Epoxy Coated Shelves
- · 6" Overall Height Casters Standard
- · Field Reversible Doors (hinge kit not included)
- · 8' Cord And Plug (see electrical data for details)

### **FEATURES**

· Full Electronic Control

### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- Epoxy Coated Evaporator Coil
- Refrigerator Capable Of Maintaining Product Temperature 36°F To 38°F













- 3 Year Parts & Labor Warranty
  Plus An Additional 4 Year Compressor Warranty
- ► Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)



Please verify qualifying units by visiting: www.energystar.gov/cfs

## **OPTIONS & ACCESSORIES**

- Secure-Temp™ Technology
- Black Or White InteriorCustom Color Cabinet
- Electronic Lock Models Door Swing Orientation (at time of order)
- Additional Shelves


- 3", 6" Casters Or 6" Seismic Legs
- Remote Models\* (6" legs only) (refrigerant must be specified at time of order, see note on back page)


3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 | fax: (800) 253-5168


Rev. 10/12/21 Printed in the U.S.A.

APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_









We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	46.15	Cabinet Voltage	115/60/1	Height	85"
Width, Overall (in.)	51 15/16"	Total Amperes	5.4	Width	54"
Depth, Overall (with handle)	34 1/16"	NEMA Plug (8' cord)	5-15P	Depth	36"
Height Overall (with casters)	83 15/16"	REFRIGERATION DATA		Crated Weight	610 lbs
Depth, Doors Open 90°	56 1/16"	Condensing Unit Size, HP	1/3	*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at	
Door Opening (in.)	22 13/16" x 52 9/16"	Refrigerant*	R-290		
No. Of Doors/Shelves	2/10	Capacity (BTU/HR) (100°F/20°F)	2392		
		Heat Rejection (BTU/HR)	3588	time of order.	
		Charge (lbs/grams)	0.2535/115		

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 10/12/21 Printed in the U.S.A.

