


The Dishwashing Machine Specialists

Project _		
Item No.		
Quantity .		

STANDARD FEATURES

Heat recovery: Cold water feed only!
 Up to 50% more energy efficient!
 Quicker drying of wares!
 Condensation is removed!
 Reduced operating costs!



- "Vari-cycle," 3 cycle time options for enhanced cleaning
- Insulated panels and booster
- Soft Start protects glasses and dishes from chipping and breaking
- Simple field conversion from single to three phase
- Precise digital temperature display and control
- ENERGY STAR® Qualified
- Rinse Sentry ensures 180°F/82°C final rinse for sanitized wares
- Standard liquid detergent and rinse-aid pumps
- Advanced service diagnostics
- Pumped drain
- Automatic drain cycle
- 1 HP corrosion resistant pump
- Independent stainless steel interchangeable upper and lower wash and rinse arms
- Includes two racks: 1 peg and 1 flat





UH330B Heat Recovery

Undercounter High Temperature
Dishwashing Machine
with Built-in Booster Heater









SPECIFIER STATEMENT

Specified unit will be high temperature undercounter dishwasher operating on a 1/2" cold water supply only with heat recovery. Unit shall incorporate a "dry assist" feature to improve and speed-up the drying of wares.

Features selectable 150, 200 and 277 second cycle times, 3 time cycle options, LED temp display, Rinse Sentry, rinse aid and detergent pumps, flexible fill and drain hoses, stainless steel top and side panels. Constructed of stainless steel.

1 year parts and labor warranty.

Champion Industries, Inc. 3765 Champion Blvd, Winston-Salem, NC 27105 Tel: 336/661-1556 Fax: 336/661-1979

sales@championindustries.com www.championindustries.com

2674 North Service Rd Jordan Station, Ontario, Canada LOR 1S0 Tel: 800/263-5798 Fax: 905/562-5422

sales@moyerdiebellimited.com www.championindustries.com/canada

UH330B Heat Recovery

Undercounter High Temperature
Dishwashing Machine with Built-in Booster Heater

33-3/4" [857]

Champion®

The Dishwashing Machine Specialists

Volume crated: 15 cu. ft./0.42 cu.m. Shipping weight crated: 215 lbs./97.5 kg.

- 24" [610] -

∞ ∞ 0 0:°0

3 17-3/4" [451] 26-3/4" [679]

Plan View

Dimensions shown in inches and [millimeters]

Front View Side View

-42-3/8" [1076]·

(1)

14-3/4"

[375] Clearance

-2" [51]

Utilities

1 Electrical

208-240/60/1; 3 wire plus ground, (See Box). 208-240/60/3; 4 wire plus ground, (See Box). Field convertible to accept 3 phase power see st

Field convertible to accept 3 phase power, see service manual for details

2 Cold Water

1/2" supply; 55-80°F [12-26°C] cold water; 25 PSI min. Machine equipped with 3/4" [19] hose connector.

3 Pumped Drain

5/8" [15.9] I.D. flexible reinforced hose, 6 ft. [1829] long.

Max. drain flow 15 US gpm. [12.5 imp gal] Max. drain height 3 ft. [914]

UH330B with Booster

Elec. Specs.	Rated Amps	Minimum Supply Ckt. Conductor Ampacity	Maximum Overcurrent Protective Device
115/208/60/1	32	40	40
115/240/60/1	36	40	40
115/208/60/3	22	30	30
115/240/60/3	24	30	30

Field convertible to accept 3 phase power

Warning Plumbing and electrical connections should be made by qualified personnel who will observe all the applicable plumbing, sanitary and safety codes and the National Electrical Code.

SPECIFICATIONS

[267]

Capacities

Cycle time (seconds) 150/200/277 Racks per hr. 24/18/13

Motor horsepower

Wash 1

Water consumption

U.S. Gal. (max. use) per hr. 15.2/12.7 U.S. Gal. per rack 0.76/0.63

Temperatures °F/°C

Wash 150/66 Rinse 180/82

Heating

Tank heat, electric, kW 2.0 Electric booster, kW 5

Time Cycle in Seconds

Wash 70/120/197 Rinse 20 Heat recovery/condense 55

Standard 20" x 20" [508 x 508]

Rack Complement

Dish 1 Open 1

Due to an ongoing value analysis program at Champion, specifications contained in this catalog are subject to change without notice.

Champion Industries, Inc.,

3765 Champion Blvd., NC 27105 • 336/661-1556 • Fax: 336/661-1979 2674 N. Service Rd, Jordan Station, Ontario, Canada LOR 1SO • 800/263-5798 • Fax: 905/562-4618

ChampionIndustries.com • ChampionIndustries.com/canada sales@moyerdiebellimited.com

