



## **DYNAMIC PREPARATION**

SALAD SPINNERS



## Salad Dryer ES-100 120/50-60/1

CAPACITY PER CYCLE: 6 KG. / 13 LBS.

Fast, sleek, user-friendly, safe, smooth running salad spinner designed to efficiently dry up to 6 Kg. / 13 lbs. of salad per cycle at a maximum speed of 900rpm.

| <ul> <li>Stainless steel construction.</li> <li>Lightweight and removable stainless steel basket.</li> <li>Compact geometry: easily fits under conventional standard countertops.</li> <li>Equipped with castors allowing operator to wheel unit around kitchen and under a countertop for easy storage.</li> <li>Transparent, heavy duty lid for ease of control.</li> <li>Lid seld opening mechanism, for ease of access to basket.</li> <li>User-friendly, waterproof control panel.</li> <li>Advanced features:</li> <li>Electronic timer with 3 fix cycles.</li> <li>2 speeds, up to 900 rpm for optimum drying.</li> <li>Equipped with powerful three-phase motors controlled by highly reliable electronic speed variator, which enables the salad dryer to be connected to a single-phase electrical mains supply.</li> <li>Safety features:</li> <li>Weight distribution detection system (VCS) to prevent undesirable rattling of the unit.</li> <li>Self lock-in mechanism to ensure basket is properly locked in before cycle starts.</li> </ul> |                    | •Width: 21.3 "<br>•Depth: 29.5 "<br>•Height: 26.2 "<br>Net weight: 106 lbs.<br>NSF and ETL listings in process as |
|--|--------------------|---|
| DEFAULT EQUIPMENT<br>· Castors with brake.<br>· Stainless steel drying basket.<br>· Cord and pluge.  | OPTIONAL EQUIPMENT |   |
| INSE<br>INSE   |                    |   |

## **TECHNICAL SPECIFICATIONS**

Load capacity per programme: 13 lbs. Drainer hourly production: 250 lbs. - 800 lbs. Timer (min-max): 60 " - 120 " - 180 " Motor speed: 900 rpm Loading: 0.75 Hp Electrical supply: 120 V / 50 Hz-60 Hz / 1 ~ (with land connection)

External dimensions

·W/idth: 21.3 "

s for March 2013.