

## Sammic



## DYNAMIC PREPARATION

SALAD SPINNERS



## Salad dryer ES-200 120/50-60/1

CAPACITY PER CYCLE: 12 KG. / 26 LBS.

Fast, sleek, user-friendly, safe, smooth running salad spinner designed to efficiently dry up to 12 Kg. / 26 lbs. of salad per cycle at a maximum speed of 900rpm.

<ul> <li>Stainless steel construction.</li> <li>Lightweight and removable stainless steel basket.</li> <li>Compact geometry: easily fits under conventional standard countertops.</li> <li>Equipped with castors allowing operator to wheel unit around kitchen and under a countertop for easy storage.</li> <li>Transparent, heavy duty lid for ease of control.</li> <li>Lid seld opening mechanism, for ease of access to basket.</li> <li>User-friendly, waterproof control panel.</li> <li>Advanced features:</li> <li>Electronic timer with 3 fix cycles.</li> <li>2 speeds, up to 900 rpm for optimum drying.</li> <li>Equipped with powerful three-phase motors controlled by highly reliable electronic speed variator, which enables the salad dryer to be connected to a single-phase electrical mains supply.</li> <li>Safety features: <ul> <li>Weight distribution detection system (VCS) to prevent undesirable rattling of the unit.</li> <li>Self lock-in mechanism to ensure basket is properly locked in before cycle starts.</li> </ul> </li> </ul>		•Width: 21.3 " •Depth: 29.5 " •Height: 32.1 " Net weight: 115 lbs. NSF and ETL listings
DEFAULT EQUIPMENT · Castors with brake. · Stainless steel drying basket. · Cord and pluge.	OPTIONAL EQUIPMENT	
NSE ET		



UNE-EN 60335-2-64:2001, UNE-EN 60335-1:1997; UNE-EN 55014-1:2002+A1:02, UNE-EN 61000-3-2:01; UNE-EN 61000-3-

## **TECHNICAL SPECIFICATIONS**

Load capacity per programme: 26 lbs. Drainer hourly production: 500 lbs. - 1600 lbs. Timer (min-max): 60 " - 120 " - 180 " Motor speed: 900 rpm Loading: 0.75 Hp Electrical supply: 120 V / 50 Hz-60 Hz / 1 ~ (with land connection)

External dimensions

.\Width: 21.3 "

gs in process as for March 2013.