


# Glass Door Under Counter




TUCGR-260

Model No.	Temp	Doors	No. Of Shelves	Capacity (Cu. Ft.)	HP	Volts	Amps	Dimensions L x D x H*	Weight lbs.
<b>Side Mount Compressor - Digital Temperature Read Out</b>									
TUCGR-248	REF	2 (sliding)	4	13	1/5	115	4.08	47.5" x 31.5" x 34.5"	282
TUCGR-260	REF	2 (sliding)	4	18	1/5	115	4.13	59.5" x 31.5" x 34.5"	339
TUCGR-272	REF	2 (sliding)	4	23	1/3	115	4.89	71.5" x 31.5" x 34.5"	390


\*Height dimension includes casters    ▪ Sizes nominal, specifications subject to change without notice.



TUCGR-248



TUCGR-260



TUCGR-272

## Standard Features

### Cabinet Construction

Heavy duty 430 stainless steel, and galvanized steel finished bottom and back wall of exterior. High quality 304 stainless steel interior and worktop, ABS evaporator drain cover. Insulated with 2.5" thick high density foamed-in-place polyurethane foam. Four 4" diameter casters (front casters with brakes). Door heater installed around inside cabinet frame to prevent moisture build up.

### Refrigeration System

- Side mounted condensing unit for bigger compartment use compared to back mounted units
- Oversized condenser and evaporator coil cools to set temperature in a minimum time period and maintains it
- Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Environmentally friendly CFC free R-134A refrigerant
- Air defrost, temperature initiated and terminated
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pressure relief port located at exterior back wall for rapid re-entry
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

### Doors (Sliding)

- Black PVC door frames
- Double pane glass system with a layer of transparent thermal insulation film in between two layers
- Removable doors with stainless steel door tracks for easy cleaning

### Lighting

- Safety shielded fluorescent interior lighting with on/off switch

### Shelving

- Two epoxy coated wire shelves per section
- 304 stainless steel pilasters and shelf clips

### Temperature Control

- Factory preset temperature, 35° F
- Setting temperature range from 33° F to 41° F
- Easy to read digital temperature display
- Easy to control temperature by simply pushing buttons on control box
- Microchip digital monitoring system provided with various functions for monitoring and maintaining ideal temperature