

TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

	Project N ame	LOCATION			
	Ітем #	Q TY	AIA#		
١	Model #	SIS#			

Models

TDM-DZ-77-GE/GE-B-W


TDM-DZ-77-GE/GE-W-W TDM-DZ-77-GE/GE-S-W

TDM-DZ-77-GE/GE-S-S

True Display Merchandiser

Curved Glass, Glass End Dual Zone







TDM-DZ-77-GE/GE-W-W

FEATURES

- True's refrigerated display merchandisers combine efficient, high volume merchandising and exceptional refrigeration with an elegant curved glass front for sophisticated presentation of high end desserts and pastries.
- Refrigerated section features factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Refrigerated section features high capacity, factory balanced refrigeration system that has two (2) temperature range options. Standard temperature range maintains cabinet temperatures of 33°F to 41°F (.5°C to 5°C), ideally suited for refrigerated bakery and cold deli products. Optional temperature range maintains cabinet temperatures of 42°F to 65°F (5.5°C to 18.3°C), ideally suited for chocolate & wine options.
- Refrigerated section features exclusive reversing condenser fan motors. Fan motors reverse during defrost off cycles to help keep condenser coil free from dirt, dust and debris.
- Cabinet is NSF-7 certified to hold open food product.
- Two (2) rear sliding glass doors for back access.
- Exterior powder coated FDA black rounded front and back, black aluminum aesthetic side and front panels. Color options available at no charge - white or stainless. Curved glass front and side glass panels.
- Interior powder coated FDA white over CRS material. Color options available (upcharge applies) - black or stainless.
- Six (6) tiered levels of adjustable wire cantilever shelves that match cabinet interior color. Chrome plated wire shelves standard on stainless units.
- Front glass swings Up for easy cleaning access.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

OPTIONS								
Exterior Color	Black, White, or Stainless Steel							
Interior Color	Black, White, or Stainless Steel							
End Type	Glass or Mirrored Ends							
Shelving	White, Black, Chrome, or Mezzanine							

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest $\frac{1}{2}$ " (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight White/Black Model (lbs.)	Crated Weight Stainless Model (lbs.)	
Model	Doors	Shelves	W	D	Н	НР	Voltage	Amps		(total rt.)	` '	(kg)
TDM-DZ-77-GE/GE-Δ/Δ	2	3	771⁄4	39	491/8	1/4	115/60/1	10.0	5-15P	8	795	TBD
			1963	991	1248	N/A		N/A		2.44	361	TBD

Δ Represents Exterior/Interior (B-black, W-White, S-Stainless)

MADE IN STATE OF LONG IN THE S		APPROVALS:	AVAILABLE AT:
8/16	Printed in U.S.A.		

Models:

TDM-DZ-77-GE/GE-B-W TDM-DZ-77-GE/GE-W-W

TDM-DZ-77-GE/GE-S-W TDM-DZ-77-GE/GE-S-S

True Display Merchandiser: Curved Glass, Glass End Dual Zone



STANDARD FEATURES

DESIGN

 True's combination "refrigerated" and "dry" display case combines efficient, high volume merchandising and exceptional refrigeration with an elegant curved glass front for sophisticated presentation of high end deli, desserts and pastries.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Exclusive reversing condenser fan motors. Fan motors reverse during defrost off cycles to help keep condenser coil free from dirt, dust and debris. Keeping coils clean optimizes the unit's performance providing colder holding temperatures and increased energy efficiency. Regularly scheduled thorough cleaning of coils still recommended.
- High capacity, factory balanced refrigeration system that has two (2) temperature range options in refrigerated section. Standard temperature range maintains cabinet temperatures of 33°F to 41°F (.5°C to 5°C), ideally suited for refrigerated bakery and cold deli products. Optional temperature range maintains cabinet temperatures of 42°F to 65°F (5.5°C to 18.3°C), ideally suited for chocolate & wine options.
- Pull Out Condensing unit slides out for easy cleaning and maintenance

CABINET CONSTRUCTION

 Exterior - powder coated FDA black rounded front and back, black aluminum aesthetic side and front panels.
 Color options available at no charge - white or stainless.

- Curved glass front and side glass panels.
- Interior powder coated FDA white over CRS material.
 Color options available (upcharge applies) black or stainless.
- Insulation entire cabinet structure is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with leg levelers.

CURVED FRONT DISPLAY GLASS

 Curved glass front and side panels are single pane tempered glass. Front glass opens from closed to fully open to provide extra large viewing area to maximize product presentation while allowing full frontal access.

REAR DOORS

- Two (2) rear sliding glass doors for back access.
- Each door fitted with 12" (305 mm) long aluminum handle
- Sliding doors ride on stainless steel V-channel with stainless steel bearings. Doors fit within plastic channel frame.

SHELVING

- Six (6) adjustable heavy duty PVC coated wire shelves standard.
- Each shelf supports a maximum weight of 150 lbs. (69 kg).

PAN CAPACITY

 Cabinet holds eight (8) 18"L x 26"D (458 mm x 661 mm) display pans and twelve (12) 12"L x 18"D (305 mm x 458 mm) display pans. Pans supplied by others.

LIGHTING

 LED interior lighting, two (2) clips underneath shelf to keep wires in place. Safety shielded.

MODEL FEATURES

- Refrigerator evaporator is epoxy coated to eliminate the potential of corrosion.
- Front glass swings Up for easy cleaning access.
- Pull out condensing unit slides out for easy cleaning and maintenance.
- Electronic temperature control.
- NSF-7 compliant for open food product. Tested and certified for performance at NSF Type II: 80°F (27°C) and 55% relative humidity.

ELECTRIC

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply.

- ☐ Black interior
- White exterior
- Stainless steel interior
- Stainless steel exterior
- Mirrored interior ends
- Black wire shelves
- ☐ Chrome plated wire shelves
- ☐ Stainless mezzanine shelves

TDM MODEL NUMBER NOMENCLATURE SYSTEM




DZ - Dual Zone DC - Dry Case CW - Chocolate/Wine GE - Standard Glass ME - Mirrored Glass

B - Black W - White

S - Stainless Steel


PLAN VIEW



FRONT VIEW

(991 mm) 491/8" (1248 mm)

RIGHT VIEW



RIGHT VIEW (FRONT GLASS OPEN)

WARRANTY*

Three year warranty on all parts and labor and an additional 2 year warranty on compressor. (U.S.A. only)

ESIDENTIAL APPLICATIONS: True assumes no liability for parts or labor coverage for component failure, facts fect or any other damages for units installed in non-commercial foodservice or residential applications.

METRIC DIMENSIONS ROUNDED UP TO
THE NEAREST WHOLE MILLIMETER
SPECIFICATIONS SUBJECT TO

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

KCL	Elevation	Right	Plan	3D	Back
KCL					