

## TRUE FOOD SERVICE EQUIPMENT, INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

	Project <b>N</b> ame	LOCATION				
	Ітем #	<b>Q</b> TY	AIA#			
١	Model #	SIS#				

Models

TDM-R-36-GE/GE-B-W

TDM-R-36-GE/GE-W-W TDM-R-36-GE/GE-S-W

TDM-R-36-GE/GE-S-S

True Display Merchandiser

Curved Glass, Glass End Refrigerator



TDM-R-36-GE/GE-B-W



TDM-R-36-GE/GE-W-W

# **FEATURES**

- True's refrigerated display merchandisers combine efficient, high volume merchandising and exceptional refrigeration with an elegant curved glass front for sophisticated presentation of high end desserts and pastries.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system that has two (2) temperature range options. Standard temperature range maintains cabinet temperatures of 33°F to 41°F (.5°C to 5°C), ideally suited for refrigerated bakery and cold deli products. Optional temperature range maintains cabinet temperatures of 42°F to 65°F (5.5°C to 18.3°C), ideally suited for chocolate & wine options.
- Exclusive reversing condenser fan motors. Fan motors reverse during defrost off cycles to help keep condenser coil free from dirt, dust and debris.
- Cabinet is NSF-7 certified to hold open food product.
- Two (2) rear sliding glass doors for back access.
- Exterior powder coated FDA black rounded front and back, black aluminum aesthetic side and front panels. Color options available at no charge - white or stainless. Curved glass front and side glass panels.
- Interior powder coated FDA white over CRS material. Color options available (upcharge applies) - black or stainless.
- Three (3) tiered levels of adjustable wire cantilever shelves that match cabinet interior color. Chrome plated wire shelves standard on stainless units.
- Front glass swings Up for easy cleaning access.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

OPTIONS							
Exterior Color	Black, White, or Stainless Steel						
Interior Color	Black, White, or Stainless Steel						
End Type	Glass or Mirrored Ends						
Shelving	White, Black, Chrome, or Mezzanine						

# ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest  $\frac{1}{2}$  (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight White/Black Model (lbs.)	Crated Weight Stainless Model (lbs.)	
Model	Doors	Shelves	W	D	Н	НР	Voltage	Amps		(total m)	` '	(kg)
TDM-R-36-GE/GE-Δ/Δ	2	3	361/4	39	491/8	1/4	115/60/1	10.0	5-15P	8	540	TBD
			921	991	1248	N/A		N/A		2.44	245	TBD

Δ Represents Exterior/Interior (B-black, W-White, S-Stainless)

MADE IN SAME COLUMN IN INCIDENT AND INCIDENT		APPROVALS:	AVAILABLE AT:
8/16	Printed in U.S.A.		

Models:

TDM-R-36-GE/GE-B-W

TDM-R-36-GE/GE-W-W

TDM-R-36-GE/GE-S-W TDM-R-36-GE/GE-S-S **True Display Merchandiser:** Curved Glass, Glass End Refrigerator



## STANDARD FEATURES

#### DESIGN

- True's refrigerated display case combines efficient, high volume merchandising and exceptional refrigeration with an elegant curved glass front for sophisticated presentation of high end deli, desserts and pastries.
- Designed to provide an attractive companion to our TDM-DC "dry case" display merchandiser.

#### **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Exclusive reversing condenser fan motors. Fan motors reverse during defrost off cycles to help keep condenser coil free from dirt, dust and debris. Keeping coils clean optimizes the unit's performance providing colder holding temperatures and increased energy efficiency. Regularly scheduled thorough cleaning of coils still recommended.
- High capacity, factory balanced refrigeration system that has two (2) temperature range options. Standard temperature range maintains cabinet temperatures of 33°F to 41°F (.5°C to 5°C), ideally suited for refrigerated bakery and cold deli products. Optional temperature range maintains cabinet temperatures of 42°F to 65°F (5.5°C to 18.3°C), ideally suited for chocolate & wine options
- Pull Out Condensing unit slides out for easy cleaning and maintenance.

#### CABINET CONSTRUCTION

- Exterior powder coated FDA black rounded front and back, black aluminum aesthetic side and front panels. Color options available at no charge - white or stainless.
- Curved glass front and side glass panels.

- Interior powder coated FDA white over CRS material. Color options available (upcharge applies) - black or stainless.
- Insulation entire cabinet structure is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with leg levelers.

#### **CURVED FRONT DISPLAY GLASS**

Curved glass front and side panels are single pane tempered glass. Front glass opens from closed to fully open to provide extra large viewing area to maximize product presentation while allowing full frontal access.

#### **REAR DOORS**

- Two (2) rear sliding glass doors for back access.
- Each door fitted with 12" (305 mm) long aluminum
- Sliding doors ride on stainless steel V-channel with stainless steel bearings. Doors fit within plastic channel

#### **SHELVING**

- Three (3) adjustable heavy duty PVC coated wire shelves standard.
- Each shelf supports a maximum weight of 150 lbs. (69 kg).

### ΡΔΝ CΔΡΔCΙΤΥ

Cabinet holds two (2) 18"L x 26"D (458 mm x 661 mm) display pans, two (2) 9"L x 26"D (229 mm x 661 mm) display pans and four (4) 12"L x 18"D (305 mm x 458 mm) display pans. Pans supplied by others.

#### LIGHTING

LED interior lighting, two (2) clips underneath shelf to keep wires in place. Safety shielded.

#### **MODEL FEATURES**

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- Front glass swings Up for easy cleaning access.
- Pull out condensing unit slides out for easy cleaning and maintenance.
- Electronic temperature control.
- NSF-7 compliant for open food product. Tested and certified for performance at NSF Type II: 80°F (27°C) and 55% relative humidity.

#### **ELECTRICAL**

Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



#### **OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply.

- ☐ Black interior
- White exterior
- Stainless steel interior
- Stainless steel exterior Mirrored interior ends
- Black wire shelves
- Chrome plated wire shelves
- Stainless mezzanine shelves



Type:

R - Refrigerator DZ - Dual Zone DC - Dry Case

CW - Chocolate/Wine

**END TYPE** COLOR Left Position / Right Position Exterior / Interior GF

Side Type: GE - Standard Glass ME - Mirrored Glass

491/8"

Color: B - Black

W - White

S - Stainless Steel

# PLAN VIEW




FRONT VIEW WARRANTY\*

Three year warranty on all parts and labor and an additional 2 year warranty on compressor. (U.S.A. only) ESIDENTIAL APPLICATIONS: True assumes no liability for parts or labor coverage for component failure, factor effect or any other damages for units installed in non-commercial foodservice or residential applications.

METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER SPECIFICATIONS SUBJECT TO

CHANGE WITHOUT NOTICE



RIGHT VIEW (FRONT GLASS OPEN)

Elevation Right Plan 3D Back KCI

TRUE FOOD SERVICE EQUIPMENT