

UNDERCOUNTER REFRIGERATORS

VUR36

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

VICTORY ULTRASPEC™
FEATURING: **SecureTemp™**
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Secure-Temp 1.0 Technology
- Full Electronic Control
- Stainless Steel Exterior/Aluminum Interior
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Cartridge Style Hinges
- 1/2" Thick Durable Sub Top
- Self-Closing Doors with 120° Stay-Open Feature
- (2) Epoxy Coated Shelves Per Door Section
- 6" Casters, 2 with Brakes
- 10' Cord & Plug



VUR36

OPTIONS & ACCESSORIES

- 3" ADA Casters
- 6" Legs or 6" Seismic Legs
- Richlite Cutting Board
- Overshelves
- Stainless Steel Interior
- LED Lighting
- Door Locks
- 220/50 Hz, 220/60Hz Voltages
- Remote Models
- Change Door Swing - at time of order
- Extra Shelves
- Epoxy, Chrome Plated, or Stainless Steel
- Gasket Guards
- Stainless Steel Back



CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

Cabinets are insulated with 2" thick foamed-in-place polyurethane insulation. Sub-top insulated with 1-1/2" foamed-in-place polyurethane insulation. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Doors are equipped with a snap-in-place vinyl magnetic gasket for positive seal. Convenient, double pull style door handle. 6" high casters are standard, 2 include brakes.

An 10' cord set is provided with 115 volt models. Cabinet interior standard with 2 steel wire epoxy coated shelves per section. Interior light with manual switch is provided with glass door models.

REFRIGERATION SYSTEM

Forced air refrigeration systems use a cap tube to meter refrigerant. Automatic electric defrost is standard. Automatic (non-electric) condensate evaporator is provided.

Refrigerators operate at 36° - 38°F

CHARACTERISTICS	VUR36
Net Capacity	8.5
Width, Overall (in.)	36"
Depth, Overall	32 3/4"
Depth, Door(s) Open 90°	62 1/4"
Height Overall	34 5/8"
No. of Doors	1
No. of Shelves	2

ELECTRICAL DATA

Condensing Unit Voltage	115/60/1
Total Amperes	3.3

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA

Condensing Unit Size	1/5 HP
Refrigerant	R-134A

CRATED WEIGHT	210 LBS
----------------------	---------

* Remote units use R-404A refrigerant standard and come with 6" legs

