

Project:

Item Number:

Quantity:

SIGNATURE SERVER® UTILITY STATIONS WITH STAINLESS STEEL COUNTERS



Signature Server® Utility Station with Stainless Steel Counter

DESCRIPTION

Signature Server[®] is the choice when functionality and modular ease of use are your top priorities. Signature Server[®] Serving Equipment is an industry standard, with updated features to better serve the operator.

FEATURES

- Reinforced stainless steel unibody construction provides extra durability in a lightweight, mobile base
- Base is 18-gauge 400 series stainless steel clad with black laminate. Optional colors and finishes are also available.
- Top is one-piece 16-gauge 300 series stainless steel
- Optional 14 gauge work surface available
- Heavy-duty 4" (10 cm) swivel casters with brakes

Note: Signature Server® equipment orders cannot be canceled or returned.

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to www.Vollrath.com.

Base								
	Height / Item No.							
Length In (cm)	27" (69 cm)	30" (76 cm)	34" (86 cm)					
28 (71)	36220	36120	37020					
46 (117)	36221	36121	37021					
60 (152)	36222	36122	37022					
74 (188)	36223	36123	37023					
88 (224)	_	_	98711					

	Options							
	Color (Black is standard)							
)	Matte Laminate	Wood Grain	Stainless Steel					
	36683	36690	36696					
	36680	36687	36693					
	36681	36688	36694					
	36682	36689	36695					
	98835	98835	93836					

Breath Guards	Lighting / Heating	Accessories
Choose from:	Choose from:	Choose from:
Progressive, Contempo-	Incandescent, infra-	Plate rests, cutting
rary, Traditional, Classic	red, fluorescent, heat	boards, end shelf, tray
Cafeteria, Classic Econ-	strips and heat strips	slides, storage modules,
omy Buffet, Access [®] and	with lights. See Breath	false bottoms, bag in box,
Classic Speed Serve. See		stationary legs. See
Breath Guard spec sheets	vollrath.com for	Accessories spec sheet
on vollrath.com for selec-	selection information.	
tion information.		tion information.
İ		

Use only Vollrath accessories, including breath guards. Vollrath is not responsible for the fit or installation of custom made accessories and components. Custom accessories and components may void agency listings.

Agency Listings





Due to continued product improvement, please consult www.vollrath.com for current product specifications.

Approvals	Date




The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560 Main Fax: 800.752.5620 or 920.459.6573 Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462


SIGNATURE SERVER® UTILITY STATIONS WITH STAINLESS STEEL COUNTERS

DIMENSIONS (Shown in inches (cm))



Top View





Item No.	(A) Length	(B) Height
36220	00	27 (69)
36120	28 (71)	30 (76)
37020	(71)	34 (86)
36221	46	27 (69)
36121	46 (117)	30 (76)
37021	(117)	34 (86)
36222	40	27 (69)
36122	46 (117)	30 (76)
37022	(117)	34 (86)
36223	74	27 (69)
36123	74 (188)	30 (76)
37023	(100)	34 (86)
98711	88 (224)	34 (86)

For breath guard and accessory dimensions, see the breath guard and accessory spec sheets on vollrath.com

ELECTRICAL SPECIFICATIONS

	Length In (cm)										
		28 (71)		46 (117)		60 (117)		74 (188)		88 (224)	
	Lighting/Heating Choice	Total Amps	NEMA Plug	Total Amps	Plug	Total Amps	Plug	Total Amps	Plug	Total Amps	Plug
	Heat Strip	4.7	5-15P	5.1	5-15P	9.2	5-15P	12.6	5-15P	13.9	5-20P
	Heat Strip w/ Lights	5.7		7.1		11.2		15.6	5-20P	16.9	5-30P
	Fluorescent	0.2		0.3		0.6		0.6	5-15P	0.6	5-15P
	Incandescent	1		2		2		2.5		3	
	Infrared	4.2		6.3		8.4		10.5		12.5	

Receptacles





120V

GG
W

NEMA
5-20R

NOTE: Standard base with stainless steel countertop has a maximum load capacity of 250 LB (113.4 KG). Contact Vollrath for construction options to support heavier loads.



The Vollrath Company, L.L.C. 1236 North 18th Street

Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560

Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462