

## WORKTOP REFRIGERATORS

VWR60

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

**VICTORY ULTRASPEC™**  
FEATURING: **SecureTemp™**  
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

**There are NO software or monthly monitoring fees.**  
Optional add on kits are available for additional units.

## STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- Expansion Valve Technology
- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Exterior / Stainless Steel Interior
- Cabinet back and bottom galvanized steel
- Stainless steel 2 1/2" thick worktop with 4" high foamed in place backsplash
- Environmentally Safe R134A Refrigerant For Freezers
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Self-Closing Door(s) with 120° Hold Open Feature
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- 2 Epoxy Coated Shelves Per Section
- 6" Casters Standard, 2 with Brakes
- Cartridge Style Hinges
- 10' Cord and Plug (see electrical data for details)

**Image Coming Soon**  
**VWR60**

## OPTIONS & ACCESSORIES

- Change Door Swing
- Extra Shelves
- 3" Overall Height Casters (Set of 4)
- 220/50Hz, 220/60 Hz Voltages



3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

**CABINET CONSTRUCTION**

Heavy duty construction includes stainless steel on front, sides, doors and grille. Stainless steel 2 1/2" thick worktop with 4" high foamed in place backplash. Cabinet back and bottom are galvanized steel. Interior liner is made of aluminum for longer lasting corrosion protection. Interior thermometer is standard.

Cabinet is insulated with foamed-in-place polyurethane insulation of 2" minimum thickness. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. A plug-in type vinyl magnetic gasket is attached to each door for positive seal. Convenient, contoured, pull handle is made of black anodized aluminum. Interior arrangement includes 2 steel wire epoxy coated shelves, adjustable in 1/2 inch increments.

**ELECTRONIC CONTROL**

**REFRIGERATION SYSTEM**

Refrigeration system utilizes R134a refrigerant metered by expansion valve. Automatic (non-electric) condensate evaporator is standard. Interior forced air system, with high humidity evaporator coils, provides the ideal environment for food preservation.

Refrigerators operate at 36° - 38°F

CHARACTERISTICS	VWR60
<b>DIMENSIONAL DATA</b>	
Width, Overall (in.)	60"
Depth, Overall (inc. Handles)	30 3/4"
Depth, Door(s) Open 90°	53 13/16"
Height Overall (in.)	39 1/2"
Capacity Net (cu ft)	17.1
No. Full Doors	2
No. of Shelves	4

ELECTRICAL DATA	
Cabinet Voltage	115/60/1
Total Amperes	8.2

**NOTE:** Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA	
Condensing Unit Size	1/4 HP
Refrigerant	R-134A

CRATED WEIGHT ONE SECTION	306LBS
---------------------------	--------

\* Remote units use R-404A refrigerant standard and come with 6" legs

